7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|-----------------------------|------------|-------------------------------------|----------------------------------|---------------|
| 2-Hydroxyethyl methacrylate | None | None | None | 3 ppm Ceiling |
| Poly (ethyl methacrylate) | None | None | None | None |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) TWA (SKIN) | None |
| Saccharin | None | None | None | None |
| Methacrylic acid | 20 ppm TWA | None | None | None |
| Cumene | 50 ppm TWA | 50 ppm (245 mg/m3) PEL (SKIN) | None | None |

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eyelface protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves. Glove recommendations are based upon

permeation study results for similar products.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:GreenOdor:MildOdor threshold:Not available.pH:Not applicable

Vapor pressure: < 5 mm hg (27 °C (80.6 °F)) **Boiling point/range:** > 149 °C (> 300.2 °F)

Melting point/ range: Not available.

Specific gravity: 1.

Vapor density: Not available.

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable **Evaporation rate:** Not available. Solubility in water: Slight Partition coefficient (n-octanol/water): Not available. **VOC** content: 0.22 %; 2.46 g/l