

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	IDLH	2500 mg/m3
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	IDLH	2500 mg/m3
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	IDLH	2500 mg/m3
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	IDLH	2500 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.