



Hazard Phrases	
H241	Heating may cause a fire or explosion.

Precautionary Phrases	
P235	Keep cool.

Section 3: Composition/Information on Ingredients

Rated Capacity: 38.8Ah

Energy: 140Wh

Ingredients	% WT	CAS Number	EC Number
Aluminum Foil	1-5	7429-90-5	231-072-3
Metal Oxide (proprietary)	30-50		
Polyvinylidene Fluoride (PVDF)	<3	24937-79-9	
Copper Foil	3-10	7440-50-8	231-159-6
Carbon (proprietary)	20-30	7440-44-0	231-153-3
Electrolyte (proprietary)	10-20		
Aluminum, inert materials	Remainder	N/A	

Lithium-equivalent Content: 18g/cell

Section 4: First Aid Measures

Eye contact: Rinse eyes with water for 15 minutes and seek medical attention.

Skin contact: Wash area thoroughly with soap and water and seek medical attention.

Ingestion: Never give fluids or induce vomiting if patient is unconscious or having convulsion. To conscious individual give one full cup of water to dilute ingested material.

Get medical attention immediately.

Inhalation: Leave area immediately and seek medical attention.

Section 5: Firefighting Measures

Extinguishing Media

Use a dry chemical ABC extinguisher. Do not use extinguisher containing metal or water.

Special Firefighting Instructions

If possible, remove cell(s) from fire fighting area. If heated above 150°C, cell(s) may explode/vent.

Firefighting Equipment