Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Fiberglass (CAS 65997-17-3)	TWA	3 fibers/cm3	Fiber.
		3 fibers/cm3	Fibrous dust.
		5 mg/m3	Fiber, total
		5 mg/m3	fibers, total dust
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Zirconium silicate (CAS 14940-68-2)	STEL	10 mg/m3	
	TWA	5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Use explosion-proof electrical equipment if airborne dust levels are high. Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Wear protective gloves (i.e. latex, nitrile). Suitable gloves can be recommended by the glove **Hand protection**

supplier.

Other Wear suitable protective clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

> limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. During dust-raising work: In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 1910.134. Respirator type: Any powered, air-purifying respirator with a

high-efficiency particulate filter.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Always observe good personal hygiene measures, such as washing after handling the material General hygiene and before eating, drinking, and/or smoking. Routinely wash work clothing and protective considerations

equipment to remove contaminants.

9. Physical and chemical properties

Solid (article). **Appearance**

Solid. **Physical state** Solid. **Form** Color Grev. None. Odor

Odor threshold Not applicable. Not applicable. Ha Melting point/freezing point Not applicable. Initial boiling point and boiling Not applicable.

range

Flash point Not applicable. **Evaporation rate** Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

Flammability limit - upper

(%)

942730 Version #: 01

Not applicable.

Vapor pressure Not applicable.

Revision date: -

FER3644, MPV 2022 SDS US

Issue date: 14-February-2018

4/8