

Safety Data Sheet

Material: 70702640 ELASTOSIL® A 442

Version: 2.0 (US) Date of print: 06/03/2015 Date of last alteration: 05/27/2015

1. Product and company identification

1.1 Identification of the substance or preparation:

Commercial product name: ELASTOSIL® A 442

Use of substance / preparation Industrial.

automobile industry Sealants

1.2 Company/undertaking identification:

Manufacturer/distributor: Wacker Chemical Corporation

3301 Sutton Road Adrian, MI 49221-9397

USA

Customer information: InfoLine:

Tel (517) 264-8240, Fax (517) 264-8740

Hours of operation:

Monday - Friday,8 am to 5 pm (eastern standard time)

Corporate website: www.wacker.com

Emergency telephone no. (24h): (517) 264-8500

Transportation emergency: (800) 424-9300 (CHEMTREC, USA)

(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Class	Category	Route of
		exposure
Serious eye damage / eye irritation	Category 2	
Skin corrosion/irritation	Category 2	

2.2 Label elements

Labelling (GHS):

Pictogram(s):



Signal Word: Warning

H-Code	Hazard Statements
H315	Causes skin irritation.
H319	Causes serious eye irritation.
P-Code	Precautionary Statements
P103	Read label before use.
P280	Wear protective gloves/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/soap.
P332+P313	If skin irritation occurs: Get medical advice/ attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to waste disposal.

Reportable ingredients for labelling:	
Polydimethyl siloxane diol	