

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not applicable.

Flammability limit - upper (%) Not applicable.

Vapor pressure Not applicable.

Vapor density Not applicable.

Relative density 2 - 3.7 (20° C)

Solubility(ies)

Solubility (water) Insoluble in water.

Partition coefficient (n-octanol/water) Not applicable.

Auto-ignition temperature Not applicable.

Decomposition temperature Not available.

Viscosity Not applicable.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Will not occur.

Conditions to avoid None known.

Incompatible materials None known.

Hazardous decomposition products Carbon oxides. Metallic fumes.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Dust may cause eye, skin and respiratory tract irritation. Inhalation of powder or fumes may cause metal fume fever. Inhalation may lead to deposition in lung and in sufficient quantities produce baritosis.

Skin contact Dust may irritate skin.

Eye contact Dust may irritate the eyes.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Exposed individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects

Acute toxicity The ingredients may be released as general dust from the product by operations such as overheating, burning, machining, abrading, or riveting. Dust may cause eye, skin and respiratory tract irritation.

Components	Species	Test Results
Barium sulphate (CAS 7727-43-7)		
<u>Acute</u>		
Oral		
LD50	Rat	307 g/kg
Copper (CAS 7440-50-8)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 2.77 mg/l, 4 hours