Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

Treat symptomatically.

medical attention and special treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Direct contact with eyes may cause temporary irritation.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes, skin, and clothing. Keep unnecessary personnel away. For personal

During fire, gases hazardous to health may be formed. Upon decomposition, this product emits

protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Observe good industrial hygiene practices. For personal protection, see Section 8 of the SDS.

Conditions for safe storage,

including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Туре	Value	Form
Silane, dichlorodimethyl-, reaction products with silica (CAS 68611-44-9)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		0.8 mg/m3	
		20 mppcf	
NIOSH. Immediately Dangerous to	Life or Health (IDLH) Values	s, as amended	
Components	Туре	Value	
Silane, dichlorodimethyl-, reaction products with silica	IDLH	3000 mg/m3	

FIR No.: 184665 SDS US
Version: 01 2 / 6

Issue Date: 06-02-2025

(CAS 68611-44-9)