7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and

cause eye irritation.

Storage: For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)

Keep container closed. Store in a dry area below 90° F.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Calcium carbonate	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Garnet-group minerals	None	None	None	None
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime	None	None	None	None
Octadecanoic acid	10 mg/m3 TWA	None	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL (as Al) Respirable dust. 15 mg/m3 PEL (as Al) Total dust.	None	None
Butan-2-one O,O',O",O"'- silanetetrayltetraoxime	None	None	None	None
Butanone oxime	None	None	10 ppm (36 mg/m3) TWA (Skin sensitizer)	None
White mineral oil (petroleum), highly refined	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 PEL Mist.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Safety showers and eye

wash stations should be available.

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Nitrile gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste
Color: Gray
Odor: Mild

IDH number: 135270

Odor threshold:Not available.pH:Not applicableVapor pressure:< 5 mm hg</th>

Boiling point/range: > 200 °C (> 392°F) no method

Melting point/ range:Not available.Specific gravity:1.5 at 20 °C (68°F)Vapor density:Heavier than air.Flash point:> 93 °C (> 199.4 °F)Flammable/Explosive limits - lower:Not applicableFlammable/Explosive limits - upper:Not applicable