

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not re-use empty containers. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. For personal protection, see Section 8 of the SDS. Do not breathe mist/vapors. Use only in well-ventilated areas.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ammonia, aqueous solution (CAS 1336-21-6)	PEL	35 mg/m3
		50 ppm
PROPANE (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
Ammonia, aqueous solution (CAS 1336-21-6)	STEL	35 ppm	
	TWA	25 ppm	
BUTANE (CAS 106-97-8)	STEL	1000 ppm	

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Ammonia, aqueous solution (CAS 1336-21-6)	IDLH	15 %
		300 ppm
BUTANE (CAS 106-97-8)	IDLH	1.6 %
		2000 ppm
		1600 ppm
PROPANE (CAS 74-98-6)	IDLH	2.1 %
		2100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value
Ammonia, aqueous solution (CAS 1336-21-6)	STEL	27 mg/m3
		35 ppm
	TWA	18 mg/m3