

SECTION-3 COMPOSITION / INFORMATION ON INGREDIENTS**OSHA Hazardous Components :**

Ingredients	CAS No.	TSCA No.	Weight %
Cured Phenolic Resin	Not Applicable	Not Listed	1-10
Calcium hydroxide	1305-62-0	1305-62-0	10-20
Silica/Quarts(impurity)	14808-60-7	14808-60-7	0.1-0.5
Calcium carbonate	471-34-1	471-34-1	10-20
Cellulose	9004-34-6	9004-34-6	1-10
Kaolin	1332-58-7	1332-58-7	1-10
Glass fiber	65997-17-3	65997-17-3	1-10
Carbon black	1333-86-4	1333-86-4	<1
Barium sulfate	7727-43-7	7727-43-7	10-20

SECTION-4 FIRST AID MEASURES

If any of the symptoms persist, seek medical attention immediately.

Skin : Wash skin with soap and water after handling parts. Seek medical attention for persistent irritation.

Eyes : Flush eye with cool running water if dust becomes embedded.
Seek medical attention if reddening persists.

Inhalation : Remove affected person to fresh air.

Ingestion : Not anticipated route of entry.

Note to Physician : No special first aid or medical treatment procedures are required.

SECTION-5 FIRE FIGHTING MEASURES

Suitable extinguishing media : Water, Spray, Dry, Chemical, Foam, CO₂

Protection of firefighters : Decomposition product may be irritating to eyes, skin and the respiratory tract. Firefighters should wear self-contained breathing apparatus.

SECTION-6 ACCIDENTAL RELEASE MEASURES

Personal Precautions : In case dust may occur, use personal protective equipment recommended in Section 8.

Environmental Precautions : Not applicable.

Method for containment : Not applicable.

Method for clean-up : Use wet method or vacuum to clean up dust from products.

Other information : Not required.

SECTION-7 HANDLING AND STORAGE

Handling : Keep away from fire, heat, and flame. Avoid breathing or creating dust.

Storage : Keep away from fire, heat, and flame. Keep material dry. Keep away from acids, alkalis.
Exhaust ventilation is recommended.