

MSDS No. : NAMI-DP-21-05-12
Current Issue Date : Oct.03 2012

Material Data Sheet for D6304

Page 2 of 8

SECTION-3 COMPOSITION / INFORMATION ON INGREDIENTS**OSHA Hazardous Components :**

Ingredients	CAS No.	TSCA No.	Weight %
Cured Phenolic Resin	Not Applicable	Not Listed	5-10
Calcium hydroxide	1305-62-0	1305-62-0	1-5
Calcium carbonate	471-34-1	471-34-1	1-5
Zirconium silicate	10101-52-7	10101-52-7	1-5
Glass fiber	65997-17-3	65997-17-3	1-5
Copper	7440-50-8	7440-50-8	10-30
Tin	7440-31-5	7440-31-5	1-5
Molybdenum disulfide	1317-33-5	1317-33-5	1-5
Graphite	7782-42-5	7782-42-5	1-5
Barium sulfate	7727-43-7	7727-43-7	15-40
Magnesium Potassium titanium oxide	39290-90-9	39290-90-9	1-5
Tin sulfide	1314-95-0	1314-95-0	1-5

SECTION-4 FIRST AID MEASURES

If any of the symptoms persist, seek medical attention immediately.

Skin : Wash skin with soap and water after handling parts. Seek medical attention for persistent irritation.

Eyes : Flush eye with cool running water if dust becomes embedded.
Seek medical attention if reddening persists.

Inhalation : Remove affected person to fresh air.

Ingestion : Not anticipated route of entry.

Note to Physician : No special first aid or medical treatment procedures are required.

SECTION-5 FIRE FIGHTING MEASURES

Suitable extinguishing media : Water, Spray, Dry, Chemical, Foam, CO₂

Protection of firefighters : Decomposition product may be irritating to eyes, skin and the respiratory tract. Firefighters should wear self-contained breathing apparatus.

SECTION-6 ACCIDENTAL RELEASE MEASURES

Personal Precautions : In case dust may occur, use personal protective equipment recommended in Section 8.

Environmental Precautions : Not applicable.

Method for containment : Not applicable.

Method for clean-up : Use wet method or vacuum to clean up dust from products.

Other information : Not required.