

Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Based on available data, the classification criteria are not met. Prolonged inhalation may be harmful.
Skin contact	Based on available data, the classification criteria are not met. Prolonged skin contact may cause temporary irritation.
Eye contact	Based on available data, the classification criteria are not met. Direct contact with eyes may cause temporary irritation.
Ingestion	Based on available data, the classification criteria are not met. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Calculated/Test Results
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
<u>Acute</u>		
Inhalation		
LC50	Rat	73680 mg/l, 4 Hours 61 mg/l, 4 Hours
Oral		
LD50	Rat	> 25 ml/kg
Other		
LD50	Rabbit	> 5 mg/kg, 4 Hours
PROPAN-2-OL (CAS 67-63-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12800 mg/kg
Oral		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg 4.5 g/kg
	Rabbit	6410 mg/kg 8 g/kg 5.03 g/kg
	Rat	5045 mg/kg 4.7 g/kg
Other		
LD50	Mouse	4477 mg/kg 1509 mg/kg
	Rat	2735 mg/kg 1099 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.