



SAFETY DATA SHEET OSHA HCS (29 CFR 1910.1200)

DAIKALUB 528D

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade Name : DAIKALUB 528D

Recommended Product Use : Lubricating

Restricted Uses : No limited use

Manufacturing Company or Supplier : Daishin Kako Company Ltd,
5F Makita Building, 2-5-8 Shiba Daimon,
Minato-Ku, Tokyo 105-0012, JAPAN
Tel: +81 3 34358561
Fax : +81 3 34358564

Information in case of emergency : Tel: 1-949 407 7994 (USA)
+81 3 34358561 (Japan)

2. HAZARDS IDENTIFICATION

OSHA/HCS status : This material is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

OSHA/GHS signal word : None

OSHA/GHS pictograms : None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product description : This product is a mixture

Chemical Characterisation : Silicone Grease

Ingredients	CAS Number	% by weight
Graphite	7782-42-5	10 - 30%
Dimethyl Polysiloxane	63148-62-9	60 - 80%
Silicon dioxide	7631-86-9	< 5%

4. FIRST - AID MEASURES

General : None special

After inhalation : Remove the exposed person immediately and provide fresh air. Get medical attention.

After skin contact : Promptly flush contaminated skin with soap or mild detergent and water.
Contact physician if irritation continues

After eye contact : Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

After ingestion : Rinse mouth and throat with water. Get medical attention immediately.

The most important things of symptoms and effects on acute and delay : Do not try to smell, if exposed smell longtermly, may get dizziness

Other Note to physicians : Treat symptomatically