

protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ETHYLBENZENE	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
ETHYLBENZENE	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
ETHYLBENZENE	100-41-4	CMRG	TWA:25 ppm;STEL:75 ppm	
TOLUENE	108-88-3	CMRG	STEL:75 ppm	Skin Notation
TOLUENE	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
CYCLOHEXANE	110-82-7	OSHA	TWA:1050 mg/m3(300 ppm)	
CYCLOHEXANE	110-82-7	ACGIH	TWA:100 ppm	
XYLENE	1330-20-7	CMRG	TWA:50 ppm;STEL:75 ppm	
XYLENE	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	
XYLENE	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
ETHYL ACETATE	141-78-6	ACGIH	TWA:400 ppm	
ETHYL ACETATE	141-78-6	OSHA	TWA:1400 mg/m3(400 ppm)	
ETHYL ALCOHOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	
ETHYL ALCOHOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
METHYL ALCOHOL	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	
METHYL ALCOHOL	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Skin Notation

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection