## 3. Composition/information on ingredients

## **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated light		64742-47-8	53.95
Alcohols C9-11 Ethoxylated		68439-46-3	1 - < 3
Quaternary Ammonium Compounds, Coco Alkylbis(hydroxyethyl)methyl, Ethoxylated, Chlorides		61791-10-4	1 - < 3
D-limonene		5989-27-5	24.9
PROPANE		74-98-6	11.05
ISOBUTANE		75-28-5	5.95
Methane		74-82-8	< 0.01
POTASSIUM HYDROXIDE		1310-58-3	< 0.01
1,4-DIOXANE		123-91-1	< 0.001
ETHYLENE OXIDE		75-21-8	< 0.001

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

**General information** 

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol. Combustible liquid. Will burn if involved in a fire.

FIR No.: 197247 SDS US Version: 02 2 / 10

Issue Date: 02-21-2025

Specific methods