

**US. ACGIH Threshold Limit Values (TLV)**

Components	Type	Value
CARBON DIOXIDE (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
HEPTANE (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
METHYLCYCLOHEXANE (CAS 108-87-2)	TWA	400 ppm
PROPAN-2-OL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

**NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended**

Components	Type	Value
CARBON DIOXIDE (CAS 124-38-9)	IDLH	40000 ppm
HEPTANE (CAS 142-82-5)	IDLH	1.05 %
		750 ppm
METHYLCYCLOHEXANE (CAS 108-87-2)	IDLH	1.2 %
		1200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	IDLH	1 %
		1000 ppm
PROPAN-2-OL (CAS 67-63-0)	IDLH	2 %
		2000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)**

Components	Type	Value
CARBON DIOXIDE (CAS 124-38-9)	STEL	54000 mg/m3
		30000 ppm
		9000 mg/m3
HEPTANE (CAS 142-82-5)	TWA	5000 ppm
		1800 mg/m3
	Ceiling	440 ppm
		350 mg/m3
METHYLCYCLOHEXANE (CAS 108-87-2)	TWA	85 ppm
		1600 mg/m3
		400 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3
		100 ppm
		1225 mg/m3
PROPAN-2-OL (CAS 67-63-0)	STEL	500 ppm
		980 mg/m3
		400 ppm