

骆驼集团北美电池销售股份公司 CAMEL BATTERY MX SA DE CV.

neutralizing agent. Place battery in suitable container for disposal. Dispose of contaminated material in accordance with applicable local, state and federal regulations. Sodium bicarbonate, soda ash, sand, lime or other neutralizing agent should be kept on-site for spill remediation.

Personal Precautions: Acid resistant aprons, boots and protective clothing. ANSI approved safety glasses with side shields/face shield recommended. Ventilate enclosed areas.

Environmental Precautions: Lead and its compounds and sulfuric acid can pose a severe threat to the environment. Contamination of water, soil, and air should be prevented.

SECTION 7 - HANDLING AND STORAGE

Precautions	Keep away from flames during and immediately after charging. Combustion or					
to be Taken	overcharging may create or liberate toxic and hazardous gases and liquids					
in Handling	including hydrogen, sulfuric acid mist, sulfur dioxide, sulfur trioxide, stibine, arsine					
and	and sulfuric acid. Store batteries in cool, dry, well-ventilated area. Do not short					
Storage	circuit battery terminals, or remove vent caps during storage or recharging.					
	Protect battery from physical damage.					
Other	GOOD PERSONAL HYGIENE AND WORK PRACTICES ARE MANDATORY. Refrain					
Precautions	from eating, drinking or smoking in work areas. Thoroughly wash hands, face, neck, and					
	arms before eating, drinking or smoking. Launder soiled clothing before reuse. Emptied					
	batteries contain hazardous sulfuric acid residue.					

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory Protection (Specify Type)	Acid gas NIOSH approved respirator is required when the PEL is exceeded or employee experiences respiratory irritation. When exposure levels are unknown or when firefighting, wear a self-contained breathing apparatus with a full facepiece operated in positive pressure mode					
Ventilation	Must be provided when charging in an enclosed area. Change air every 15 min.	Local Exhaust	When PP is exceeded	(General)	Normal mechanical ventilation recommended for stationary applications.	
Protective	Wear rubber or plastic acid Eye resistant gloves with elbow					

POST CODE:441705

FAX:+86 710 334 4151