

Thyborønvej 78 DK-7673 Harboøre Denmark

+45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group	031	Page 1 of 13
Product name	Danafloat™ 070	
		Revision: August 2020
Safety data sheet	according to EU Reg. 1907/2006 as amended	Supersedes February 2019

SAFETY DATA SHEET

Danafloat™ 070

Revision: Sections containing a revision or new information are marked with a .

♣ SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier Danafloat™ 070

Contains cresols and O,O-ditolyl S-hydrogen phosphorodi-

thioate

1.2. Relevant identified uses of the substance or mixture and uses

advised against Can be used as flotation reagent (flotation collector) only.

1.3. Details of the supplier of the safety

data sheet

FMC Agricultural Solutions A/S

Thyborønvej 78 DK-7673 Harboøre

Denmark

SDS.Ronland@fmc.com

1.4. Emergency telephone number

Medical emergencies:

Austria: +43 1 406 43 43 Malta: 112

Belgium: +32 70 245 245

Bulgaria: +359 2 9154 409

Cyprus: 1401

Netherlands: +31 30 274 88 88

Norway: +47 22 591300

Poland: +48 22 619 66 54

Czech Republic: +420 224 919 293 +48 22 619 08 97

+420 224 915 402 Portugal: 800 250 250 (in Portugal only)

Denmark: +45 82 12 12 12 +351 21 330 3284
England and Wales: 111 Romania: +40 21318 3606
Estonia: +372 7943500 Scotland: +8454 24 24 24
Finland: +358 9 471 977 Slovakia: +421 2 54 77 4 166
France: +33 (0) 1 45 42 59 59 Slovenia: +386 41 650 500

Greece: 30 210 77 93 777 South Africa: +27 83 123 3911 (Bateleur Emergency Response Co.)

Hungary: +36 80 20 11 99 Spain: +34 91 562 04 20 Ireland (Republic): +353 1 837 9964 Sweden: +46 08-331231

Italy: +39 02 6610 1029 112 Latvia: +371 670 42 473 Switzerland: 145 112 Turkey: 114

Lithuania: +370 523 62052 U.S.A. & Canada: +1 800 / 331 3148

+370 687 53378 All other countries: +1 651 / 632 6793 (Collect) Luxembourg: +352 8002 5500



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 2 of 13
Product name	Danafloat™ 070	
		August 2020

For fire, leak, spill or other accident emergencies:

U.S.A.: +1 800 / 424 9300 (CHEMTREC)

All other countries: +1 703 / 741 5970 (CHEMTREC - Collect)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Acute oral toxicity: Category 3 (H301) Acute dermal toxicity: Category 3 (H311) Skin corrosion: Category 1B (H314) Eye damage: Category 1 (H318)

Health hazards

The hazardous properties of the product are expected to be dominated

by those of cresols.

Cresols are poisonous and can cause severe irritation to skin, eyes, airways and digestive tract. They can cause permanent damage, indepth burns and blindness. They enter the body on contact with all skin surfaces, eyes, and by inhalation. They attack the central nervous system, respiratory tract, liver and kidneys. After severe contamination death can rapidly occur.

Long-term effects include permanent damage to tissues, most often skin, lungs, central nervous system, liver and kidneys. Hypersensitivity develops in certain individuals.

Cresols may have a local anaesthetic effect. Permanent damage to health may already occur before the smell threshold is crossed. Moreover, the amount of pain experienced on exposure is no measure for the actual damage. Long-term effects may be more severe.

Environmental hazards

The product may be hazardous in the aquatic environment.

2.2. Label elements

According to EU Reg. 1272/2008 as amended

Product identifier DanafloatTM 070

Contains cresols and O,O-ditolyl S-hydrogen phosphorodithioate

Hazard pictograms (GHS06, GHS05)





Signal word Danger

Hazard statements

H314 Causes severe skin burns and eye damage.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 3 of 13
Product name	Danafloat™ 070	August 2020

Precautionary statements P264 Wash thoroughly after handling. Wear protective gloves, protective clothing and eye protection or face P280 P303+P361+P353 protection. IF ON SKIN (or hair): Take off immediately all contaminated P305+P351+P338 clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 P501 Immediately call a POISON CENTER or physician. Dispose of contents and container as hazardous waste. 2.3. Other hazards None of the ingredients in the product meets the criteria for being PBT or vPvB.

♣ SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. **Mixtures** See section 16 for full text of hazard statements.

Active ingredient

Cresyl-dtpContent: 70 - 80% by weightCAS namePhosphorodithioic acid, O,O-bis(methylphenyl) esterCAS no.27157-94-4IUPAC nameO,O-Ditolyl S-hydrogen phosphorodithioateEU nameO,O-bis(Methylphenyl) hydrogen dithiophosphateOther name(s)O,O-bis(Methylphenyl) phosphorodithioateCresyl-dtp

Molecular weight 310.37

Classification of the ingredient Acute oral toxicity: Category 3 (H301)

Acute dermal toxicity: Category 3 (H311)

Acute dermal toxicity: Category 3 (H311) Skin corrosion: Category 1B (H314)

Reportable ingredient CAS no. EC no. Classification

(% w/w) (EINECS no.)

Mix-cresol max. 20 1319-77-3 215-293-2 Acute Tox. 3 (H311)

Acute Tox. 3 (H301) Skin Corr. 1B (H314)

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

In case of exposure, do not wait for symptoms to develop. Immediately start the recommended procedures below. The speed of decontamination is essential in preventing dermal burns as well as systemic toxicity from cresol.

If breathing has stopped, start artificial respiration immediately and



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 4 of 13
Product name	Danafloat™ 070	August 2020

	maintain until a physician takes care of the victim.
Inhalation	If experiencing any discomfort, immediately remove from exposure. Light cases: Keep person under surveillance. Get medical attention immediately if symptoms develop. Serious cases: Get medical attention immediately or call for an ambulance.
Skin contact	Immediately flush with much polyethylene glycol/ethanol mixture or if this is not available with water while removing contaminated clothing and footwear. Do not wipe off. Wash with water and soap. See physician immediately if experiencing pain or if irritation develops.
Eye contact	Immediately rinse eyes with much water or eyewash solution, occasionally opening eyelids. Remove contact lenses after a few minutes and rinse again. See physician immediately. Continue rinsing underway to physician, also after initial pain has subsided.
Ingestion	Let the exposed person rinse mouth and let him/her drink several glasses of water or milk. Let the exposed person take a few spoonfuls of food oil (olive oil or other plant oil, no paraffin oil). Do not induce vomiting. If vomiting does occur, give fluids again. Never give anything by mouth to an unconscious person. Make the exposed person sit in half-upright position and keep him/her steady. Get medical attention immediately.
4.2. Most important symptoms and effects, both acute and delayed	Burning pain in nose, mouth, eyes and skin, nausea, headache, vomiting, convulsions, tightness in chest, laboured breathing, unconsciousness, cardiac arrest.
4.3. Indication of any immediate medical attention and special treatment needed	Call a physician, poison centre or hospital immediately. Describe the type and extent of exposure and the victim's condition.
treatment needed	A mixture of polyethylene glycol and ethanol (2:1) has proven most suitable for removal of cresols from skin. It should be kept available for rapid use at the workplace.
	It may be helpful to show this safety data sheet to physician.
Note to physician	In case lungs are affected watch for pulmonary oedema
SECTION 5: FIRE-FIGHTING MEASUR	ES

SEC

Dry chemical or carbon dioxide for small fires, water spray or foam 5.1. Extinguishing media for large fires. Avoid heavy hose streams.

5.2. Special hazards arising from the substance or mixture

The essential breakdown products are volatile, toxic, malodorous, irritant and inflammable compounds such as alkyl mercaptans, hydrogen sulphide, dialkyl sulphide, sulphur dioxide, phosphorous pentoxide, carbon monoxide and carbon dioxide.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 5 of 13
Product name	Danafloat™ 070	August 2020

5.3. Advice for firefighters

Use water spray to keep fire-exposed containers cool. Approach fire from upwind to avoid hazardous vapours and toxic decomposition products. Fight fire from protected location or maximum possible distance. Dike area to prevent water runoff. Firemen should wear self-contained breathing apparatus and protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

It is recommended to have a predetermined plan for the handling of spills. Empty, closable vessels for the collection of spills should be available.

In case of large spill (involving 1 tonne of the product or more):

- 1. use personal protection equipment; see section 8
- 2. call emergency telephone no.; see section 1
- 3. alert authorities.

Observe all safety precautions when cleaning up spills. Use personal protection equipment. Depending on the magnitude of the spill this may mean wearing respirator, face mask or eye protection, chemical resistant clothing, gloves and rubber boots.

Stop the source of the spill immediately if safe to do so. Keep unprotected persons away from the spill area. Remove sources of ignition. Avoid and reduce mist formation as much as possible. Personal exposure by splashing must be avoided.

6.2. Environmental precautions

Contain the spill to prevent any further contamination of surface, soil or water. Wash waters must be prevented from entering surface water drains. Uncontrolled discharge into water courses must be alerted to the appropriate regulatory body.

6.3. Methods and materials for containment and cleaning up

It is recommended to consider possibilities to prevent damaging effects of spills, such as bunding or capping. See GHS (Annex 4, Section 6).

Surface water drains should be covered if appropriate. Minor spills on the floor or other impervious surface should be absorbed onto an absorptive material such as universal binder, bentonite, Fuller's earth or other absorbent clays. Collect the contaminated absorbent in suitable containers. Clean area with much water and industrial detergent. Absorb wash liquid onto absorbent and transfer to suitable containers. The used containers should be properly closed and labelled.

Large spills which soak into the ground should be dug up and transferred to suitable containers.

Spills in water should be contained as much as possible by isolation of



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 6 of 13
Product name	Danafloat™ 070	August 2020

the contaminated water. The contaminated water must be collected and removed for treatment or disposal.

6.4. **Reference to other sections** See subsection 8.2. for personal protection. See section 13 for disposal.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

In an industrial environment, it is recommended to avoid all personal contact with the product, if possible by using closed systems with remote system control. The material should be handled by mechanical means as much as possible. Adequate ventilation or local exhaust ventilation is required. The exhaust gases should be filtered or treated otherwise.

Remove contaminated clothing immediately. Wash thoroughly after handling. Before removing gloves, wash them with water and soap. After work, take off all work clothes and footwear. Take a shower, using water and soap. Wear only clean clothes when leaving job. Wash protective clothing and protective equipment with water and soap after each use.

Do not discharge to the environment. Collect all waste material and remains from cleaning equipment, etc., and dispose of as hazardous waste. See section 13 for disposal.

7.2. Conditions for safe storage, including any incompatibilities

The product is stable under normal conditions of warehouse storage. To avoid freezing, store wherever possible above 5° C.

Store in labelled, tightly closed plastic drums or coated steel drums. The storage room should be constructed of incombustible material, closed, dry, ventilated and with impermeable floor, without access of unauthorised persons or children. A warning sign reading "POISON" is recommended. The room should only be used for storage of chemicals. Food, drink, feed and seed should not be present. A hand wash station should be available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1.	Control	l parameters
------	---------	--------------

Year

Cresol ACGIH (USA) TLV 2015 TWA 20 mg/m³ inhalable fraction and vapour

Skin notation

OSHA (USA) PEL 2015 8-hr TWA 5 ppm (22 mg/m³); skin notation



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 7 of 13
Product name	Danafloat™ 070	
		August 2020

EU, 2000/39/EC as amended

2017 Not established

Germany, MAK

2014 Biological limit value 200 mg/l in urine; skin notation

HSE (UK) WEL 2011 Not established

However, other personal exposure limits defined by local regulations may exist and must be observed.

Cresyl-dtp

DNEL, inhalation 0.54 mg/m³

DNEL, dermal 0.15 mg/kg bw/day

Mix-cresol

8.2. Exposure controls

When used in a closed system, personal protection equipment will not be required. The following is meant for other situations, when the use of a closed system is not possible, or when it is necessary to open the system. Consider the need to render equipment or piping systems non-hazardous before opening.

In cases of incidental high exposure, maximal personal protection equipment may be necessary, such as respirator, face mask, chemical resistant coveralls.



Respiratory protection

In the event of an accidental discharge of the material which produces a heavy vapour or mist, workers must put on officially approved respiratory protection equipment with a universal filter type including particle filter.



Protective gloves

Wear chemical resistant gloves, such as barrier laminate, butyl rubber or nitrile rubber. The breakthrough time of these materials for this product are unknown. Generally, however, the use of protective gloves will give only partial protection against dermal exposure. Small tears in the gloves and cross-contamination can easily occur. It is recommended to limit the work to be done manually and to change the gloves regularly. Used gloves should be thrown out and not be reused.



Eye protection

Preferably wear a face shield, rather than goggles or safety glasses. It is recommended to have an eye wash fountain immediately available in the workplace when there is a potential for eye contact.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 8 of 13
Product name	Danafloat™ 070	
		August 2020



Other skin protection

Wear appropriate chemical resistant clothing to prevent skin contact depending on the extent of exposure. During most normal work situations where exposure to the material cannot be avoided for a limited time span, waterproof pants and apron of chemical resistant material or coveralls of polyethylene (PE) will be sufficient. Coveralls of PE must be discarded after use if contaminated. In cases of excessive or prolonged exposure, coveralls of barrier laminate may be required.

♣ SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid (solution in water)

Colour Black
Odour Tar-like

Melting point/freezing point Not determined

Boiling point or initial boiling point

The product is miscible with water

Vapour pressure Not determined

Density and/or relative density Density: 1.18 - 1.22 g/ml

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity	etivities.
-------------------------	------------

temperatures.

10.3. **Possibility of hazardous reactions** An acid-base neutralisation reaction can be hazardous because of heat

release.

10.4. **Conditions to avoid** Heating of the product will evolve harmful and irritant vapours.

10.5. **Incompatible materials** Alkalis



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group	031	Page 9 of 13
Product name	Danafloat™ 070	
		August 2020

10.6. **Hazardous decomposition products** See subsection 5.2.

♣ SECTION 11: TOXICOLOGICAL INFORMATION

11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008	* = Based on available data, the classification criteria are not met.	
	Product Acute toxicity	The product is expected to be harmful by ingestion and may be harmful by skin contact.	
	Route(s) of entry - ingestion	LD ₅₀ , oral, rat: 500 - 2000 mg/kg (estimated)	
	- skin	LD ₅₀ , dermal, rat: 1500 - 5000 mg/kg (estimated)	
	- inhalation	LC ₅₀ , inhalation, rat: not available	
	Skin corrosion/irritation	Expected to be seriously irritating to skin.	
	Serious eye damage/irritation	Expected to be severely irritating to eyes with the potential to cause permanent eye damage.	
	Respiratory or skin sensitisation	To our knowledge, no indications of allergenic properties have been recorded. Not expected to have sensitising properties. *	
	Germ cell mutagenicity	Positive results have been observed for cresols in Chinese hamster ovary cells, but not in ovaries of <i>Drosophila melanogaster</i> . Results from other mutagenicity tests were mixed as well.	
	Carcinogenicity	The product contains no ingredient known to be carcinogenic. *	
	Reproductive toxicity	The product contains no ingredient found to have adverse effects on reproduction. *	
	STOT – single exposure	Cresols may have narcotic effects. They may cause irritation of airways. *	
	STOT – repeated exposure	The following has been measured on cresyl-dtp: NOAEL 45.7 mg/kg bw/day in a combined repeated dose toxicity study (method OECD 422). Various minor findings were observed at higher dosage.	
	Aspiration hazard	The product contains no ingredients known to present an aspiration pneumonia hazard. *	

O,O-Ditolyl S-hydrogen phosphorodithioate

Route(s) of entry - ingestion LD_{50} , oral, rat: 500 - 2000 mg/kg (estimated)



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group	031	Page 10 of 13
Product name	Danafloat™ 070	
		August 2020

- skin LD₅₀, dermal, rat: not available

- inhalation LC₅₀, inhalation, rat: not available

Skin corrosion/irritation Expected to be seriously irritating to skin.

Serious eye damage/irritation Expected to be severely irritating to eyes with the potential to cause

permanent eye damage.

Respiratory or skin sensitisation ... To our knowledge, no indications of allergenic properties have been

reported. *

Mix-cresol

Toxicokinetics, metabolism and

distribution

Cresols are readily absorbed by all routes of exposure. They are extensively metabolised and metabolites are mainly found in the

kidneys. It is excreted almost completely within 24 hours in the urine.

the isomers have different toxicities. Toxicity of isomer mixtures can vary between toxic and harmful. Some of the lowest measured data

are mentioned here, but other data exist.

Route(s) of entry - ingestion LD₅₀, cresol, oral, rat: 121 - 242 mg/kg

- skin LD₅₀, cresol, dermal, rabbit: 301 - 2050 mg/kg

- inhalation LC₅₀, o-cresol, inhalation, rat: 0.029 mg/l

Skin corrosion/irritation Severely irritating to skin.

Serious eye damage/irritation Severely irritating to eyes with the possibility to cause permanent eye

damage.

Respiratory or skin sensitisation ... Hypersensitivity develops in certain individuals. *

11.2. **Information on other hazards** No more relevant information is available.

SECTION 12: ECOLOGICAL INFORMATION

The following has been measured on the product:

12.2. **Persistence and degradability** The product is biodegradable at low concentrations, but does not meet

the criteria for being readily biodegradable. It undergoes degradation

in the environment and in waste water treatment plants.

In the environment, cresols are degraded (but only at low



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 11 of 13
Product name	Danafloat™ 070	August 2020

concentrations), especially by bacteria that are widely distributed in soil and water, particularly *Pseudomonas* species. Degradation by other organisms, including yeasts, fungi, algae, and higher plants, as well as by photolysis, is also known. Accordingly, cresols do not persist in the environment at low concentrations.

Cresols impair the taste of edible fish and drinking water even at very low concentrations.

12.3. **Bioaccumulative potential** See section 9 for octanol-water partition coefficient.

Bioaccumulation is not expected. A bioaccumulation test on *o*-cresol with *Brachydanio rerio* yielded a bioconcentration factor of 10.7. Approximately similar behaviour is expected for other components in this product.

12.4. **Mobility in soil** In the environment the product is expected to be moderately mobile.

12.5. Results of PBT and vPvB assessment

None of the ingredients meets the criteria for being PBT or vPvB.

12.6. Endocrine disrupting properties

None of the ingredients is known to have endocrine disrupting

properties.

12.7. Other adverse effects Other relevant hazardous effects in the environment are not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. **Waste treatment methods** Remaining quantities of the material and empty but unclean packaging should be regarded as hazardous waste.

Disposal of waste and packagings must always be in accordance with all applicable local regulations.

possibilities for reuse or reprocessing should first be considered. If this is not possible, the material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with

flue gas scrubbing.

Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Disposal of packaging It is recommended to consider possible ways of disposal in the following order:

- 1. Reuse or recycling should first be considered. If offered for recycling, containers must be emptied and triply rinsed (or equivalent). Do not discharge rinsing water to sewer systems.
- 2. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com

CVR No. DK 12 76 00 43

Material group	031	Page 12 of 13
Product name	Danafloat™ 070	
		August 2020

- 3. Delivery of the packaging to a licensed service for disposal of hazardous waste.
- 4. Disposal in a landfill or burning in open air should only occur as a last resort. For disposal in a landfill, containers should be emptied completely, rinsed and punctured to make them unusable for other purposes. If burned, stay out of smoke.

SECTION 14: TRANSPORT INFORMATION

ADR/RID/IMDG/IATA/ICAO classification

phenyl) dithiophosphate)

14.3. **Transport hazard class(es)** 6.1 (8)

14.4. Packing group II

14.6. **Special precautions for user** Avoid any unnecessary contact with the product. Misuse can result in

damage to health. Do not discharge to the environment.

14.7. Maritime transport in bulk

according to IMO instruments .. The product is not transported in bulk by ship.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category (Dir. 2012/18/EU): toxic

Young people under the age of 18 are not allowed to work with the

product.

All ingredients are covered by EU chemical legislation.

15.2. Chemical safety assessment A chemical safety assessment has not been performed.

SECTION 16: OTHER INFORMATION

Relevant changes in the safety data

sheet Minor corrections only.

List of abbreviations ACGIH American Conference of Governmental Industrial

Hygienists

CAS Chemical Abstracts Service

Dir. Directive

DNEL Derived No Effect Level EC European Community



Thyborønvej 78 DK-7673 Harboøre Denmark +45 9690 9690 www.fmc.com CVR No. DK 12 76 00 43

Material group	031	Page 13 of 13
Product name	Danafloat™ 070	August 2020

	EC_{50}	50% Effect Concentration	
	E_rC_{50}	50% Effect Concentration based on growth	
	EINECS	European INventory of Existing Commercial Chemical	
		Substances	
	GHS	Globally Harmonized classification and labelling System of	
		chemicals, Seventh revised edition 2017	
	HSE	Health and Safety Executive, UK	
	IMO	International Maritime Organisation	
	IUPAC	International Union of Pure and Applied Chemistry	
	LC_{50}	50% Lethal Concentration	
	LD_{50}	50% Lethal Dose	
	MAK	Maximale Arbeitspaltz-Konzentration	
	NOAEL	No Observed Adverse Effect Level	
	n.o.s.	Not otherwise specified	
	OECD	Organisation for Economic Cooperation and Development.	
	OSHA	Occupational Safety and Health Administration	
	PBT	Persistent, Bioaccumulative, Toxic	
	PEL	Personal Exposure Limit	
	PNEC	Predicted No Effect Concentration	
	Reg.	Regulation	
	STOT	Specific Target Organ Toxicity	
	TLV	Threshold Limit Value	
	TWA	Time Weighted Average	
	vPvB	very Persistent, very Bioaccumulative	
	WEL	Workplace Exposure Limit	
References	Data on ingredients are available from published literature and can be found several places.		
Method for classification	Calculation method		
Used hazard statement	H301	Toxic if swallowed.	
esed mazard statement	H311	Toxic in contact with skin.	
	H314	Causes severe skin burns and eye damage.	
	H318	Causes serious eye damage.	
Advice on training	This material should only be used by persons who are made aware of its hazardous properties and have been instructed in the required safety precautions.		
The information provided in this safety	v data sheet	is believed to be accurate and reliable, but uses of the	

The information provided in this safety data sheet is believed to be accurate and reliable, but uses of the product vary and situations unforeseen by FMC Corporation may exist. The user has to check the validity of the information under local circumstances.

Prepared by: FMC Agricultural Solutions A/S / GHB