according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

SECTION 1. IDENTIFICATION

Product identifier

Product name ROVRAL® 50 WP

Other means of identification

Product code 50000150

Product Registration Num-

ber

RSCO-FUNG-0320-001-002-050

Recommended use of the chemical and restrictions on use

Recommended use Can be used as fungicide only.

Restrictions on useUse as recommended by the label.

For professional users only.

Details of the supplier of the safety data sheet

<u>Manufacturer</u> FMC Corporation

2929 WALNUT ST

PHILADELPHIA PA 19104

USA

(215) 299-6000 SDS-Info@fmc.com

Emergency telephone

For leak, fire, spill or accident emergencies, call:

1 800 / 424-9300 (CHEMTREC - U.S.A.) 1 703 / 741-5970 (CHEMTREC - International) 1 703 / 527-3887 (CHEMTREC - Alternate)

Medical emergency:

U.S.A. & Canada: +1 800 / 331-3148

All other countries: +1 651 / 632-6793 (Collect)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Signal Word : Warning

Hazard Statements : H351 Suspected of causing cancer.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|------------------------------------|------------|-----------------------|
| iprodione (ISO) | 36734-19-7 | 50 |
| kaolin | 1332-58-7 | >= 30 - < 50 |
| Polyethylene glycol, C12-15-alkyl | 68131-39-5 | >= 1 - < 5 |
| ethers | | |
| Silicic acid, aluminum sodium salt | 1344-00-9 | >= 1 - < 5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

Take off all contaminated clothing immediately.

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Call a physician if irritation develops or persists.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Suspected of causing cancer.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Avoid inhalation, ingestion and contact with skin and eyes. If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray, fog, or regular foam.

Unsuitable extinguishing

media

Do not spread spilled material with high-pressure water

streams.

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Thermal decomposition can lead to release of irritating gases

and vapors.

Nitrogen oxides (NOx) Carbon oxides

Chlorine compounds

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Firefighters should wear protective clothing and self-contained

breathing apparatus.

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

02/01/2024 50000150 Date of first issue: 03/19/2015 1.1

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emergency procedures

Personal precautions, protec- : Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Pick up and arrange disposal without creating dust. Never return spills in original containers for re-use. For disposal considerations see section 13.

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Pick up and transfer to properly labeled containers without

creating dust.

Move it to a safe place.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Avoid formation of respirable particles. Advice on safe handling

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Keep container tightly closed in a dry and well-ventilated Conditions for safe storage

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type | Control parame- | Basis |
|------------|---------|------------|-----------------|-------|

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

| | | (Form of exposure) | ters / Permissible concentration | |
|------------------------------------|-----------|--|----------------------------------|-----------|
| kaolin | 1332-58-7 | TWA (Respirable particulate matter) | 2 mg/m3 | ACGIH |
| | | TWA (Respirable) | 5 mg/m3 | NIOSH REL |
| | | TWA (total) | 10 mg/m3 | NIOSH REL |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 10 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| Silicic acid, aluminum sodium salt | 1344-00-9 | TWA (Res- pirable par- ticulate mat- ter) | 1 mg/m3 (Aluminum) | ACGIH |

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Dust impervious protective suit

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Plan first aid action before beginning work with this product.

Always have on hand a first-aid kit, together with proper in-

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

structions.

Ensure that eye flushing systems and safety showers are

located close to the working place. Wear suitable protective equipment.

In the context of professional plant protection use as recommended, the end user must refer to the label and the instruc-

tions for use.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : solid

Form : powder

Color : gray

Odor : slight

Odor Threshold : No data available

pH : 5-6

(1% emulsion)

Melting point/range : No data available

Initial boiling point and boiling :

range

No data available

Flash point : Not applicable

Flammability (solid, gas) : Will not burn

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Relative density : No data available

Density : 1.024 g/cm3

Bulk density : 224 - 368 kg/m3

Solubility(ies)

Water solubility : dispersible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 68 mPa.s (68 °F / 20 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

Conditions to avoid : Heat, flames and sparks.

Avoid extreme temperatures.

Incompatible materials : Avoid strong acids, bases, and oxidizers.

Hazardous decomposition

products

Nitrogen oxides (NOx)

Sulfur oxides

Carbon oxides

Halogenated compounds

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 425

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.18 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Components:

iprodione (ISO):

Acute oral toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Assessment: The component/mixture is minimally toxic after

single ingestion.

Acute inhalation toxicity : LC50 (Rat): > 3.29 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Symptoms: Breathing difficulties

Assessment: The component/mixture is minimally toxic after

short term inhalation. Remarks: no mortality

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: EPA OPP 81-2 Symptoms: Irritation

GLP: yes

Assessment: The component/mixture is minimally toxic after

single contact with skin.

kaolin:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

LD50: > 2,000 mg/kg

Method: OECD Test Guideline 420

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LD50: 5.07 mg/l

Method: OECD Test Guideline 436

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

LD50: > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Polyethylene glycol, C12-15-alkyl ethers:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Expert judgment

Acute inhalation toxicity : LC50 (Rat, male and female): > 1.6 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Silicic acid, aluminum sodium salt:

Acute oral toxicity : LD50 (Rat, male and female): 10,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC0 (Rat, male and female): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

no mortality

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit

Method : OECD Test Guideline 404

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Result : slight irritation

Components:

iprodione (ISO):

Species : Rabbit

Assessment : Not classified as irritant

Method : EPA OPP 81-5
Result : No skin irritation

GLP : yes

kaolin:

Method : OECD Test Guideline 404

Result : No skin irritation

Polyethylene glycol, C12-15-alkyl ethers:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Silicic acid, aluminum sodium salt:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Components:

iprodione (ISO):

Species : Rabbit

Result : Mild eye irritant
Assessment : Mild eye irritation
Method : EPA OPP 81-4

GLP : yes

kaolin:

Result : No eye irritation

Method : OECD Test Guideline 405

Polyethylene glycol, C12-15-alkyl ethers:

Result : Irreversible effects on the eye

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Silicic acid, aluminum sodium salt:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Product:

Test Type : Local lymph node assay (LLNA)

Species : mice

Method : OECD Test Guideline 429
Result : Not a skin sensitizer.

Components:

iprodione (ISO):

Test Type : Buehler Test Species : Guinea pig

Assessment : Not a skin sensitizer.

Method : EPA OPP 81-6

Result : Does not cause skin sensitization.

kaolin:

Method : OECD Test Guideline 429
Result : Does not cause skin sensitization.

Polyethylene glycol, C12-15-alkyl ethers:

Test Type : Maximization Test

Routes of exposure : Intradermal Species : Guinea pig

Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

Remarks : Based on data from similar materials

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

iprodione (ISO):

Genotoxicity in vitro : Test Type: Ames test

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: in vitro DNA damage and/or repair study

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

02/01/2024 50000150 Date of first issue: 03/19/2015 1.1

Test system: Bacillus subtilis

Metabolic activation: with and without metabolic activation

Result: positive

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo Test Type: Micronucleus test

> Species: Mouse Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

kaolin:

Genotoxicity in vitro Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Remarks: No data available Genotoxicity in vivo

Polyethylene glycol, C12-15-alkyl ethers:

Test Type: Chromosome aberration test in vitro Genotoxicity in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo Test Type: Micronucleus test

> Species: Mouse (male and female) Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Test Type: Bone marrow chromosome aberration.

Species: Rat (male and female) Method: OECD Test Guideline 475

Result: negative

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Silicic acid, aluminum sodium salt:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: chromosome aberration assay

Species: Rat (male) Application Route: Oral

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

Components:

iprodione (ISO):

Species : Rat, male

Exposure time : 2 y

6.1 mg/kg bw/day 12.4 mg/kg bw/day

Result : positive

Symptoms : Testicular effects
Target Organs : Adrenal gland, Testes

Species : Rat, female

Exposure time : 2 y

8.4 mg/kg bw/day 16.5 mg/kg bw/day

Target Organs : Adrenal gland

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

Silicic acid, aluminum sodium salt:

Species : Rat, male and female

Application Route : Oral
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

IARC Group 1: Carcinogenic to humans

kaolin 1332-58-7

(Silica dust, crystalline)

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

kaolin 1332-58-7

(Silica, Crystalline (Respirable Size))

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:

iprodione (ISO):

Effects on fetal development : Species: Rabbit

General Toxicity Maternal: NOAEL: 20 mg/kg bw/day Developmental Toxicity: NOAEL: 60 mg/kg bw/day

Symptoms: Reduced body weight, Total Resorptions / resorp-

tion rate.

Species: Rat

General Toxicity Maternal: NOAEL: 20 mg/kg bw/day Developmental Toxicity: NOAEL: 20 mg/kg bw/day Symptoms: Reduced body weight, Fetal mortality.

Target Organs: Adrenal gland

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

kaolin:

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

Polyethylene glycol, C12-15-alkyl ethers:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female Application Route: Dermal

General Toxicity Parent: NOAEL: 250 mg/kg body weight Fertility: NOAEC Mating/Fertility: 250 mg/kg body weight

Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: reproductive and developmental toxicity study

Species: Rat

Application Route: Dermal

General Toxicity Maternal: NOEL: 100 mg/kg body weight Embryo-fetal toxicity.: NOAEL: > 250 mg/kg body weight

Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Based on available data, the classification criteria are not met.

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Components:

iprodione (ISO):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

kaolin:

Remarks : No significant adverse effects were reported

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Components:

iprodione (ISO):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

kaolin:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

iprodione (ISO):

Species: Rat, maleNOAEL: 78 mg/kgLOAEL: 151 mg/kgApplication Route: Oral

Exposure time : 90 d

Target Organs : Reproductive organs

Species : Rat, female
NOAEL : 89 mg/kg
LOAEL : 189 mg/kg
Application Route : Oral
Exposure time : 90 d

Target Organs : Reproductive organs

Species : Rat, male
NOAEL : 28 mg/kg
LOAEL : 207 mg/kg
Application Route : Inhalation
Exposure time : 28 d

Target Organs : Adrenal gland

Species : Rat, female
NOAEL : 43 mg/kg
LOAEL : 241 mg/kg
Application Route : Inhalation

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Exposure time : 28 d

Target Organs : Adrenal gland

kaolin:

Remarks : No data available

Polyethylene glycol, C12-15-alkyl ethers:

Species : Rat, male and female

NOAEL : 500 mg/kg Application Route : Oral Exposure time : 90d

Method : OECD Test Guideline 408

Remarks : Based on data from similar materials

Silicic acid, aluminum sodium salt:

Species : Rat, male and female NOAEL : 2,500 - 3,200 mg/kg

Application Route : Oral Exposure time : 2 years

Remarks : Based on data from similar materials

Species : Rat, male and female

NOAEL : 0.0013 mg/l Application Route : Inhalation Exposure time : 13 weeks

Remarks : Based on data from similar materials

Aspiration toxicity

Based on available data, the classification criteria are not met.

Components:

iprodione (ISO):

The substance does not have properties associated with aspiration hazard potential.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

iprodione (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.1 mg/l

Exposure time: 96 h

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Toxicity to daphnia and other : aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.25 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Scenedesmus subspicatus): > 0.5 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Fish): 0.26 mg/l Exposure time: 21 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.17 mg/l

Exposure time: 21 d

Toxicity to soil dwelling or-

ganisms

LC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg

Exposure time: 14 d

Toxicity to terrestrial organ-

isms

LD50 (Colinus virginianus (Bobwhite quail)): > 2,000 mg/kg

LD50 (Apis mellifera (bees)): > 250 µg/bee

Exposure time: 48 h Remarks: Contact

LD50 (Apis mellifera (bees)): > 25 μg/bee

Exposure time: 48 h Remarks: Oral

kaolin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Polyethylene glycol, C12-15-alkyl ethers:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 2 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 2 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.11 - 0.28

mg/l

Exposure time: 30 d

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1.75 mg/l

End point: Immobilization Exposure time: 21 d

Remarks: Based on data from similar materials

NOEC (Daphnia magna (Water flea)): 0.77 mg/l

End point: reproduction Exposure time: 21 d

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 10 g/l

Exposure time: 16.9 h

Remarks: Based on data from similar materials

Toxicity to soil dwelling or-

ganisms

LC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg

Silicic acid, aluminum sodium salt:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): 10,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Desmodesmus subspicatus (green algae)): 10,000 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

Components:

iprodione (ISO):

Biodegradability : Result: Not readily biodegradable.

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Stability in water : Degradation half life (DT50): 146 d pH: 5

Degradation half life (DT50): 0.2 d pH: 8

kaolin:

Biodegradability : Remarks: The methods for determining biodegradability are

not applicable to inorganic substances.

Polyethylene glycol, C12-15-alkyl ethers:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301B

Remarks: Based on data from similar materials

Silicic acid, aluminum sodium salt:

Biodegradability : Remarks: The methods for determining biodegradability are

not applicable to inorganic substances.

Bioaccumulative potential

Components:

iprodione (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 70 Remarks: Bioaccumulation is unlikely.

See section 9 for octanol-water partition coefficient.

Partition coefficient: n-

octanol/water

log Pow: 3 (68 °F / 20 °C)

pH: 7

kaolin:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

: Remarks: Not applicable

Polyethylene glycol, C12-15-alkyl ethers:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 237

Exposure time: 24 d

Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

log Pow: 4.91 - 6.78 (104 °F / 40 °C)

Silicic acid, aluminum sodium salt:

Partition coefficient: n-

octanol/water

: Remarks: No data available

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Mobility in soil

Components:

iprodione (ISO):

Distribution among environ-

mental compartments

Remarks: Low mobility in soil.

kaolin:

Distribution among environ-

mental compartments

Remarks: Low mobility in soil.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (Iprodione)

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version **Revision Date:** SDS Number: Date of last issue: -

02/01/2024 50000150 Date of first issue: 03/19/2015 1.1

Class 9

Subsidiary risk ENVIRONM.

Packing group Ш

Labels 9 (ENVIRONM.)

Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 3077

Proper shipping name Environmentally hazardous substance, solid, n.o.s.

(Iprodione)

956

Class 9 Packing group Ш

Miscellaneous Labels

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

956

Environmentally hazardous yes

IMDG-Code

UN number UN 3077

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, Proper shipping name

> N.O.S. (Iprodione)

Class 9 Ш Packing group Labels 9 **EmS Code**

F-A, S-F Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Road

UN/ID/NA number UN 3077

Environmentally hazardous substance, solid, n.o.s. Proper shipping name

(Iprodione)

Class 9 Packing group III

Labels CLASS 9 **ERG Code** 171 Marine pollutant yes

Remarks Shipment by ground under DOT is non-regulated; however it

may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

Remarks 49CFR: no dangerous good in non-bulk packaging

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311. Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

| kaolin | 1332-58-7 |
|----------------------------|------------|
| tert-butyl-4-methoxyphenol | 25013-16-5 |

Pennsylvania Right To Know

| iprodione (ISO) | 36734-19-7 |
|------------------------|------------|
| kaolin | 1332-58-7 |
| Calcium lignosulfonate | 8061-52-7 |
| Sodium lignosulfonate | 8061-51-6 |

Maine Chemicals of High Concern

tert-butyl-4-methoxyphenol 25013-16-5

Vermont Chemicals of High Concern

tert-butyl-4-methoxyphenol 25013-16-5

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

Washington Chemicals of High Concern

tert-butyl-4-methoxyphenol 25013-16-5

California Prop. 65

WARNING: This product can expose you to chemicals including iprodione (ISO), kaolin, tert-butyl-4-methoxyphenol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

kaolin 1332-58-7

California Regulated Carcinogens

kaolin 1332-58-7

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

3-(3,5-DICHLOROPHENYL)-N-ISOPROPYL-2,4-DIOXOIMIDAZOLIDINE-1-CARBOXAMIDE

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

TECI: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

NFPA 704:

Health O O Instability

Special hazard

0 No health threat, **1** Slightly Hazardous, **2** Hazardous, **3** Extreme danger, **4** Deadly

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DOT - Department of Transportation: DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response: EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response: EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-

according to the OSHA Hazard Communication Standard



ROVRAL® 50 WP

Version Revision Date: SDS Number: Date of last issue: -

1.1 02/01/2024 50000150 Date of first issue: 03/19/2015

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

US / EN

Prepared by:

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.

© 2021-2024 FMC Corporation. All Rights Reserved.

End of Material Safety Data Sheet