according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 12/19/2023 50000482 Date of first issue: 05/26/2016 1.4

SECTION 1. IDENTIFICATION

Product identifier

Product name BIFLEX® TC TERMITICIDE

Other means of identification

Product code 50000482

Recommended use of the chemical and restrictions on use Recommended use Can be used as insecticide only.

Restrictions on use Use as recommended by the label.

Details of the supplier of the safety data sheet

Manufacturer FMC Corporation

2929 WALNUT ST

PHILADELPHIA PA 19104

USA

(215) 299-6000 SDS-Info@fmc.com

Emergency telephone

For leak, fire, spill or accident emergencies, call:

1 800 / 424-9300 (CHEMTREC - U.S.A.) 1 703 / 741-5970 (CHEMTREC - International) 1 703 / 527-3887 (CHEMTREC - Alternate)

Medical emergency:

U.S.A. & Canada: +1 800 / 331-3148

All other countries: +1 651 / 632-6793 (Collect)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 3

Acute toxicity (Oral) Category 3

Acute toxicity (Inhalation) Category 4

Skin sensitization Category 1

Carcinogenicity Category 2

Specific target organ toxicity

: Category 3 (Respiratory system, Central nervous system)

- single exposure

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Specific target organ toxicity

- repeated exposure

Category 1

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms









Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated

exposure.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6	>= 30 - < 40
Distillates (petroleum), solvent- dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	>= 30 - < 40
Bifenthrin	82657-04-3	25.1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Toxic if swallowed.

May be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : Avoid inhalation, ingestion and contact with skin and eyes.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry chemical, CO2, water spray or regular foam.

Unsuitable extinguishing

media

Do not spread spilled material with high-pressure water

streams.

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

May form explosive mixtures in air.

Hazardous combustion prod: :

ucts

Carbon oxides

Hazardous combustion products

Thermal decomposition can lead to release of irritating gases

and vapors.

Halogenated compounds

Specific extinguishing meth-

ods

Remove undamaged containers from fire area if it is safe to do

SO.

Use a water spray to cool fully closed containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment :

for fire-fighters

Firefighters should wear protective clothing and self-contained

breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentra-

tions. Vapors can accumulate in low areas.

Evacuate personnel to safe areas. Use personal protective equipment. If it can be safely done, stop the leak.

Do not touch or walk through the spilled material.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Never return spills in original containers for re-use. Pick up and transfer to properly labeled containers.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Keep away from open flames, hot surfaces and sources of

ignition.

Normal measures for preventive fire protection.

Advice on safe handling : Avoid

Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage

Prevent unauthorized access.

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	TWA	400 ppm 1,600 mg/m3	OSHA P0
Distillates (petroleum), solvent- dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Plan first aid action before beginning work with this product.

Hygiene measures : Avoid contact with skin, eyes and clothing.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

General industrial hygiene practice.

Do not inhale aerosol.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Color : brown

Odor : aromatic

Odor Threshold : No data available

pH : 4.8

Melting point/range : No data available

Boiling point/boiling range : Decomposition: yes

Flash point : $108 \, ^{\circ}\text{F} \, / \, 42 \, ^{\circ}\text{C}$

Evaporation rate : No data available

Flammability (liquids) : Sustains combustion

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Relative vapor density : No data available

Relative density : 0.952 - 0.955 (68 °F / 20 °C)

Density : No data available

Solubility(ies)

Water solubility : dispersible

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 5.5 mm2/s (68 °F / 20 °C)

Explosive properties : Not explosive

Oxidizing properties : Non-oxidizing

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Avoid extreme temperatures. Avoid formation of aerosol.

Incompatible materials : Avoid strong acids, bases, and oxidizers.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Toxic if swallowed. Harmful if inhaled.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Product:

Acute oral toxicity : LD50 (Rat): 275 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD50 (Rat, female): 3,492 mg/kg

Method: OECD Test Guideline 401

LD50 (Rat, male): 6,984 mg/kg Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 6.193 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: no mortality

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,160 mg/kg

Assessment: The component/mixture is minimally toxic after

single contact with skin.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Bifenthrin:

Acute oral toxicity : LD50 (Rat, male and female): 50.2 - 58.8 mg/kg

Symptoms: Convulsions, Tremors

Acute inhalation toxicity : LC50 (Rat, female): 0.6 - 1.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016
1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Method: OECD Test Guideline 403 Symptoms: Tremors, Convulsions

LC50 (Rat, male): 1.10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403 Symptoms: Tremors, Fatality

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Remarks: no mortality

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : slight irritation

Remarks : May cause skin irritation and/or dermatitis.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Mild skin irritation

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

Bifenthrin:

Species : Rabbit

Result : slight or no skin irritation.

GLP : yes

Species : Rabbit

Method : OECD Test Guideline 404
Result : slight or no skin irritation.

GLP : yes

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : slight irritation

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rabbit

Result : No eye irritation

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Bifenthrin:

Species : Rabbit

Result : Slight or no eye irritation
Method : OECD Test Guideline 405

GLP : ves

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Result : Probability or evidence of skin sensitization in humans

Remarks : Causes sensitization.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406 Result : Not a skin sensitizer.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

Remarks : Based on data from similar materials

Bifenthrin:

Test Type : Maximization Test

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/26/2016

 1.4
 12/19/2023
 50000482
 Date of first issue: 05/26/2016

Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : May cause sensitization by skin contact.

GLP : yes

Germ cell mutagenicity

Not classified based on available information.

Product:

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Genotoxicity in vitro : Test Type: in vitro DNA damage and/or repair study

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: reverse mutation assay

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Test Type: Bone marrow chromosome aberration.

Species: Rat (male and female)
Application Route: Inhalation

Result: negative

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Genotoxicity in vitro : Test Type: reverse mutation assay

Metabolic activation: Metabolic activation Method: OECD Test Guideline 471

Result: positive

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)
Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Bifenthrin:

Genotoxicity in vitro : Test Type: gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: reverse mutation assay

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mouse lymphoma assay

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Test Type: Sex-linked Recessive Lethal Test

Species: Drosophila melanogaster (vinegar fly)

Result: negative

Test Type: unscheduled DNA synthesis assay

Species: Rat

Method: OECD Test Guideline 486

Result: negative

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Species : Mouse, female

Application Route : Dermal Exposure time : 78 weeks Result : negative

Remarks : Based on data from similar materials

Bifenthrin:

Species : Rat, female
Application Route : Oral
Exposure time : 2 Years

NOAEL : 3 mg/kg bw/day

Result : negative

Species : Mouse, male

Application Route : Oral

Exposure time : 18 month(s)

NOAEL : 7.6 mg/kg bw/day

Result : positive

Symptoms : malignant tumors

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/26/2016

 1.4
 12/19/2023
 50000482
 Date of first issue: 05/26/2016

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Effects on fertility : Test Type: Three-generation study

Species: Rat

Application Route: inhalation (vapor) Fertility: NOAEC Mating/Fertility: 7.5 mg/l

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Species: Mouse

Application Route: inhalation (vapor)

General Toxicity Maternal: LOAEC: 500 part per million

Symptoms: Maternal effects.

Bifenthrin:

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: Oral

General Toxicity Parent: NOAEL: 3 mg/kg bw/day General Toxicity F1: NOAEL: 5 mg/kg bw/day

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Oral

General Toxicity Maternal: NOAEL: 2.7 mg/kg bw/day

Teratogenicity: NOAEL: 2.7 mg/kg bw/day

Symptoms: Maternal effects. Result: No teratogenic effects.

Test Type: Embryo-fetal development

Species: Rat

Application Route: Oral

General Toxicity Maternal: NOAEL: 1 mg/kg bw/day

Teratogenicity: NOAEL: 2 mg/kg bw/day

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Result: No teratogenic effects.

Species: Rat

Application Route: Oral

General Toxicity Maternal: LOAEL: 7.2 mg/kg bw/day Developmental Toxicity: LOAEL: 7.2 mg/kg bw/day Embryo-fetal toxicity.: NOEL: 9.0 mg/kg bw/day

Method: OECD Test Guideline 426

Result: Animal testing did not show any effects on fertility., Some evidence of adverse effects on development, based on

animal experiments.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Product:

Assessment : May cause respiratory irritation., May cause drowsiness or

dizziness.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Assessment : May cause respiratory irritation., May cause drowsiness or

dizziness.

Bifenthrin:

Target Organs : Central nervous system
Assessment : Causes damage to organs.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Product:

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Bifenthrin:

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Repeated dose toxicity

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rat, male and female

NOAEC : 0.8 - 0.9 mg/l Application Route : Inhalation Test atmosphere : vapor

Remarks : Based on data from similar materials

Species : Rat, male
NOAEL : 600 mg/kg
Application Route : Oral

Remarks : Based on data from similar materials

Bifenthrin:

Species : Rat, male and female

NOEL : 100 ppm Application Route : Oral - feed Exposure time : 90 d

Remarks : No toxicologically significant effects were found.

Tremors

Species : Dog, male and female NOEL : 2.5 mg/kg bw/day
Application Route : Oral - feed
Exposure time : 13 w

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Symptoms

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Bifenthrin:

The substance does not have properties associated with aspiration hazard potential.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 12/19/2023 50000482 Date of first issue: 05/26/2016 1.4

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish NOEC (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l

Exposure time: 96 h Test Type: semi-static test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (microalgae)): 3.1 mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l

Exposure time: 14 d

Method: OECD Test Guideline 204

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): 2.6 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms EC50 (Tetrahymena pyriformis): 15.41 mg/l

Exposure time: 40 h

Test Type: Growth inhibition

Remarks: The value is given based on a SAR/AAR approach

using OECD Toolbox, DEREK, VEGA QSAR models

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

(CAESAR models), etc.

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): 100

mg/

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 14 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

(Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d
Test Type: semi-static test

Method: OECD Test Guideline 211

Toxicity to microorganisms : NOEL: > 1.93 mg/l

Exposure time: 0.16 h

Bifenthrin:

Toxicity to fish : LC50 (Salmo gairdneri): 0.00015 mg/l

Exposure time: 96 h

Test Type: flow-through test

LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.00035 mg/l

Exposure time: 96 h

Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.000256 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

LC50 (Pimephales promelas (fathead minnow)): 0.000234

mg/l

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016
1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 0.00011 mg/l

Exposure time: 48 h

LC50 (Daphnia): 0.0016 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (algae): 0.822 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.00012 mg/l

Exposure time: 21 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0013 μg/l

Exposure time: 21 d

NOEC (Daphnia magna (Water flea)): 0.00095 µg/l

Exposure time: 21 d

Toxicity to soil dwelling or-

ganisms

LD50 (Eisenia fetida (earthworms)): > 16 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 216

Remarks: No significant adverse effect on Nitrogen minerali-

zation.

Toxicity to terrestrial organ-

isms

LD50 (Colinus virginianus (Bobwhite quail)): 1,800 mg/kg

LD50 (Anas platyrhynchos (Mallard duck)): > 2,150 mg/kg

LD50 (Apis mellifera (bees)): 0.1 - 0.35 µg/bee

Exposure time: 24 h

End point: Acute oral toxicity Method: OECD Test Guideline 213

LD50 (Apis mellifera (bees)): 0.1 - 0.3 µg/bee

Exposure time: 24 h

End point: Acute contact toxicity Method: OECD Test Guideline 214

Persistence and degradability

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Biodegradability : Concentration: 49.2 mg/l

Result: Inherently biodegradable.

Biodegradation: 77.05 %

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/26/2016

 1.4
 12/19/2023
 50000482
 Date of first issue: 05/26/2016

Exposure time: 28 d

Method: OECD Test Guideline 301F

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Bifenthrin:

Biodegradability : Result: Not readily biodegradable.

Bioaccumulative potential

Components:

Bifenthrin:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1,709

Remarks: Due to the distribution coefficient n-octanol/water,

accumulation in organisms is possible.

See section 9 for octanol-water partition coefficient.

Partition coefficient: n-

octanol/water

log Pow: 6

Mobility in soil

Components:

Bifenthrin:

Distribution among environ-

mental compartments

Koc: 236610 ml/g, log Koc: 5.37

Remarks: immobile

Stability in soil :

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3351

Proper shipping name : PYRETHROID PESTICIDE, LIQUID, TOXIC, FLAMMABLE

(Bifenthrin, Aromatic hydrocarbons, C10)

Class : 6.1
Subsidiary risk : 3
Packing group : III
Labels : 6.1 (3)
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3351

Proper shipping name : Pyrethroid pesticide, liquid, toxic, flammable

(Bifenthrin, Aromatic hydrocarbons, C10)

Class : 6.1 Subsidiary risk : 3 Packing group : III

Labels : Toxic, Flammable Liquids

Packing instruction (cargo : 663

aircraft)

Packing instruction (passen: 655

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3351

Proper shipping name : PYRETHROID PESTICIDE, LIQUID, TOXIC, FLAMMABLE

(Bifenthrin, Aromatic hydrocarbons, C10)

Class : 6.1 Subsidiary risk : 3 Packing group : III Labels : 6.1 (3)

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

EmS Code : F-E, S-D Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Road

UN/ID/NA number : UN 3351

Proper shipping name : Pyrethroid pesticide, liquid, toxic, flammable

(Bifenthrin, Aromatic hydrocarbons, C10)

Class : 6.1
Subsidiary risk : 3
Packing group : III

Labels : TOXIC, FLAMMABLE LIQUID

ERG Code : 131 Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ Calculated product RQ	
		(lbs)	(lbs)
butan-1-ol	71-36-3	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) Respiratory or skin sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Skin corrosion or irritation

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Bifenthrin 82657-04-3 >= 20 - < 30 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

propylene oxide 75-56-9 >= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

propylene oxide 75-56-9 >= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Distillates (petroleum), solvent-dewaxed light paraffinic; 64742-56-9

Baseoil — unspecified

ethylene oxide 75-21-8 propylene oxide 75-56-9

Pennsylvania Right To Know

Solvent naphtha (petroleum), light arom.; Low boiling point 64742-95-6

naphtha -unspecified

Distillates (petroleum), solvent-dewaxed light paraffinic; 64742-56-9

Baseoil — unspecified

Bifenthrin 82657-04-3 butan-1-ol 71-36-3

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including ethylene oxide, propylene oxide, which is/are known to the State of California to cause cancer, and ethylene oxide, which is/are known to the State of California to cause birth defects or other repro-

ductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), solvent-dewaxed light paraffinic; 64742-56-9

Baseoil — unspecified

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version 1.4	Revision Date: 12/19/2023		S Number: 000482	Date of last issue: 05/26/2016 Date of first issue: 05/26/2016
TSCA		:	Product contains s	substance(s) not listed on TSCA inventory.
AIIC		:	Not in compliance	with the inventory
DSL		:	This product conta on the Canadian I	ains the following components that are not DSL nor NDSL.
			CHLORO-3,3,3-TI	NYL-3-YLMETHYL (Z)-(1RS,3RS)-3-(2- RIFLUOROPROP-1-ENYL)-2,2- OPROPANECARBOXYLATE
ENCS		:	Not in compliance	with the inventory
ISHL		:	Not in compliance	with the inventory
KECI		:	On the inventory,	or in compliance with the inventory
PICCS		:	Not in compliance	with the inventory
IECSC		:	On the inventory,	or in compliance with the inventory
NZIoC		:	Not in compliance	with the inventory
TECI		:	Not in compliance	with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

Version Revision Date: SDS Number: Date of last issue: 05/26/2016 1.4 12/19/2023 50000482 Date of first issue: 05/26/2016

NFPA 704:

Flammability Health 2 0 Instability

Special hazard

0 No health threat, **1** Slightly Hazardous, **2** Hazardous, **3** Extreme danger, **4** Deadly

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

ACGIH / TWA : 8-hour, time-weighted average OSHA P0 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substanc-

according to the OSHA Hazard Communication Standard



BIFLEX® TC TERMITICIDE

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/26/2016

 1.4
 12/19/2023
 50000482
 Date of first issue: 05/26/2016

es; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

US / EN

Prepared by:

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.

© 2021-2023 FMC Corporation. All Rights Reserved.

End of Material Safety Data Sheet