#### SAFETY DATA SHEET

Jett Mn 235 (SDS + ES)

This safety data sheet complies with the requirements of: Regulation (EC) No. 453/2010 and Regulation (EC) No. 1272/2008



SDS #: NP-0013-1-A

Revision date: 2018-07-20

Format: EU Version 1.01

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Code(s) NP-0013-1-A

Product Name Jett Mn 235 (SDS + ES)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use: A fertilizer with micronutrients for use in agriculture and horticulture

**Restrictions on use**Use as recommended by the label.

1.3. Details of the supplier of the safety data sheet

Manufacturer FMC Agro Limited

Rectors Lane
Pentre
Flintshire
CH5 2DH
United Kingdom
Tel: + 44 1244 537370
E-mail: fmc.agro.uk@fmc.com

For further information, please contact:

Contact point Tel: +44(0) 1244 537370 Email: fmc.agro.uk@fmc.com

1.4. Emergency telephone number

**Emergency telephone** Medical emergencies:

Austria: +43 1 406 43 43 Belgium: +32 70 245 245 Bulgaria: +359 2 9154 409

Cyprus: 1401

Czech Republic: +420 224 919 293, +420 224 915 402

Denmark: +45 82 12 12 12 France: +33 (0) 1 45 42 59 59 Finland: +358 9 471 977 Greece: 30 210 77 93 777 Hungary: +36 80 20 11 99

Ireland (Republic): +352 1 809 2166

Italy: +39 02 6610 1029

Lithuania: +370 523 62052, +370 687 53378

Luxembourg: +352 8002 5500 Netherlands: +31 30 274 88 88 Norway: +47 22 591300

Poland: +48 22 619 66 54, +48 22 619 08 97

Portugal: 808 250 143 (in Portugal only), +351 21 330 3284

Romania: +40 21318 3606

Page 1/20

Version 1.01

Slovakia: +421 2 54 77 4 166 Slovenia: +386 41 650 500 Spain: +34 91 562 04 20 Sweden: +46 08-331231112

Switzerland: 145

United Kingdom: 0870 600 6266 (in the UK only)

U.S.A. & Canada: +1 800 / 331-3148

All other countries: +1 651 / 632-6793 (Collect)

#### **Section 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture Regulation (EC) No 1272/2008

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1 Sub-category C
Specific target organ toxicity — repeated exposure	Category 2
Chronic aquatic toxicity	Category 3

#### 2.2. Label elements





Signal Word Danger

#### **Hazard Statements**

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

#### **Precautionary Statements**

P260 - Do not breathe spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P314 - Get medical advice/attention if you feel unwell

#### 2.3. Other hazards

This product is not identified as a PBT/vPvB substance.

#### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Chemical name	EC-No	CAS-No	Weight percent	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH registration number
MANGANESE DINITRATE	233-828-8	10377-66-9	30-60	Ox. Sol. 2 (H272); Acute Tox. 4 (H302); Skin Corr. 1C (H314); STOT RE 2 (H373); Aquatic Chronic 3 (H412);	01-2119487993-17- 0002

Version 1.01

			(EUH071)	
Nitric acid	 7697-37-2	<1	Acute tox. 3 (H331) Skin Corr. 1A (H314) Met. Corr. 1 (H290)	01-2119487297-23- XXXX

#### **Section 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact** Remove contaminated clothing and shoes. Do not remove clothing if adhering to skin.

Rinse skin immediately with plenty of water for 15-20 minutes. Transfer to hospital if there

are burns or symptoms of poisoning.

Inhalation Remove person from exposure ensuring one's own safety while doing so. If unconscious

and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if

available. Transfer to hospital as soon as possible.

Ingestion Rinse mouth. Do NOT induce vomiting. Give 1 cup of water to drink every 10 minutes. If

unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as

soon as possible.

#### 4.2. Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed

Skin contact: Severe burns may occur. Progressive ulceration will occur if treatment is not

immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may

be difficulty swallowing.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Indication of immediate medical attention and special treatment needed, if necessary

Eye bathing equipment should be available on the premises.

#### **Section 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Using spraywater to cool the containers.

#### Unsuitable extinguishing media

None known

#### 5.2. Special hazards arising from the substance or mixture

Corrosive. Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

Version 1.01

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus and full protective gear. Wear protective clothing to prevent contact with skin and eyes.

#### Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

In case of spill, avoid contact. Isolate area and keep out animals and unprotected persons. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do it without risk.

### For emergency responders

Use personal protection recommended in Section 8.

#### 6.2. Environmental precautions

Keep people and animals away from and upwind of spill/leak. Keep material out of lakes, streams, ponds, and sewer drains. Keep out of waterways. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13). Prevent product from entering drains.

#### 6.4. Reference to other sections

See section 8 for more information. See section 13 for more information.

#### Section 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

#### Handling

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

#### Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage

Protect from freezing. Store above 5°C. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store in a cool dry place away from direct sunlight. Keep out of reach of children and animals. Keep away from food, drink and animal feedingstuffs.

Packageing material Must only be kept in original packaging.

#### 7.3. Specific end use(s)

#### Specific Use(s)

No data available.

#### **Risk Management Methods (RMM)**

The information required is contained in this Safety Data Sheet.

Version 1.01

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Chemical name	European Union	The United Kingdom	France	Spain	Germany
Nitric acid	STEL 1 ppm	STEL 1 ppm	STEL 1 ppm	STEL 1 ppm	-
7697-37-2	STEL 2.6 mg/m <sup>3</sup>				
Chemical name	Italy	Portugal	The Netherlands	Finland	Denmark
Nitric acid	STEL 1 ppm	TWA 2 ppm	STEL 1.3 mg/m <sup>3</sup>	TWA 0.5 ppm	STEL 1 ppm
7697-37-2	STEL 2.6 mg/m <sup>3</sup>	STEL 4 ppm	-	TWA 1.3 mg/m <sup>3</sup>	STEL 2.6 mg/m <sup>3</sup>
				STEL 1 ppm	
				STEL 2.6 mg/m <sup>3</sup>	
Chemical name	Austria	Switzerland	Poland	Norway	Ireland
Nitric acid	STEL 1 ppm	TWA 2 ppm	TWA 1.4 mg/m <sup>3</sup>	TWA 2 ppm	STEL 1 ppm
7697-37-2	STEL 2.6 mg/m <sup>3</sup>	TWA 5 mg/m <sup>3</sup>	STEL 2.6 mg/m <sup>3</sup>	TWA 5 mg/m <sup>3</sup>	STEL 2.6 mg/m <sup>3</sup>
		STEL 2 ppm	_	STEL 4 ppm	
		STEL 5 mg/m <sup>3</sup>		STEL 10 mg/m <sup>3</sup>	

**Derived No Effect Level (DNEL)** No information available.

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

**Engineering measures** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

**Eye/Face Protection** Tightly fitting safety goggles. Maintain eye wash fountain and quick-drench facilities in work

**Hand Protection** Gloves (acid resistant). PVC gloves.

**Skin and Body Protection** Wear impervious gloves and/or clothing if needed to prevent contact with the material.

**Respiratory Protection** Not required under normal use.

No special environmental precautions required. **Environmental exposure controls** 

#### **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1. Information on basic physical and chemical properties

**Physical State** Liquid

**Appearance** No information available Barely perceptible Odour

Colour Red brown

No information available **Odour threshold** 

<2

No information available Melting point/freezing point Boiling point/boiling range No information available Flash point No information available No information available **Evaporation Rate** 

Flammability (solid, gas)

Flammability Limit in Air

**Upper flammability limit:** No information available Lower flammability limit No information available Vapour pressure No information available Vapour density No information available Specific gravity 1.54 - 1.56

Water solubility Soluble in water

No information available Solubility in other solvents No information available Partition coefficient **Autoignition temperature** No information available

#### NP-0013-1-A Jett Mn 235 (SDS + ES)

**SDS #**: NP-0013-1-A **Revision date**: 2018-07-20

Version 1.01

Decomposition temperature
Viscosity, kinematic
Viscosity, dynamic
Explosive properties
Oxidising properties
No information available
No information available
No information available
Non-oxidizing (by EC criteria)

9.2. Other information

Softening point
Molecular weight
VOC content (%)
Density
Bulk density
No information available

#### **Section 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

Stable under recommended storage conditions

#### 10.2. Chemical stability

Stable under recommended storage conditions.

#### **Explosion data**

**Sensitivity to Mechanical Impact** No information available. **Sensitivity to Static Discharge** No information available.

#### 10.3. Possibility of hazardous reactions

#### **Hazardous polymerisation**

None under normal processing.

#### **Hazardous reactions**

None under normal processing. Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Heat.

#### 10.5. Incompatible materials

Strong oxidising agents. Strong bases.

#### 10.6. Hazardous decomposition products

May emit toxic fumes under fire conditions.

#### Section 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

#### **Acute toxicity**

#### **Product Information**

Product is harmful by ingestion.

Product is harmful by inhalation.

This product is corrosive to living tissue.

Version 1.01

Chemical name	LD50 Oral	LD50 Dermal	Inhalation LC50
MANGANESE DINITRATE	>300 mg/kg (rat)		
Nitric acid			= 130 mg/m <sup>3</sup> (Rat) 4 h = 2500 ppm (Rat) 1 h

Skin corrosion/irritation
Serious eye damage/eye irritation
Sensitisation
Mutagenicity

No information available. No information available. No information available No information available. No information available.

Reproductive toxicity STOT - single exposure STOT - repeated exposure No information available. No information available. No information available.

**Symptoms** 

Carcinogenicity

Skin contact: Severe burns may occur. Progressive ulceration will occur if treatment is not

immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may

be difficulty swallowing.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

**Aspiration hazard** 

No information available.

#### **Section 12: ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

.

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other
			aquatic invertebrates
MANGANESE DINITRATE	Desmodesmus subspicatus:	Rainbow trout	Daphnia magna:
	72 ErC50 = 64.6 mg/L	(Oncorhynchus mykiss):	48H EC50 = >100 mg/L
	Ī	96H LC50 = 47.2 mg/L	_
Nitric acid	-	96 h LC50: = 72 mg/L (Gambusia	-
		affinis)	

#### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

No information available.

#### 12.4. Mobility in soil

Mobility in soil Soluble in water.

Version 1.01

#### **Mobility**

Soluble in water.

#### 12.5. Results of PBT and vPvB assessment

This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Harmful to aquatic life

#### **Section 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from residues / unused

products

Transfer to a suitable container and arrange for collection by specialised disposal company. Do not contaminate ponds, waterways or ditches with chemical or used containers. Do not

discharge to sewer systems.

Contaminated Packaging Clean container with water. Dispose of rinse water in accordance with local and national

guidelines.

EWC Waste Disposal No 02 01 08

OTHER INFORMATION NOTE: The user's attention is drawn to the possible existence of specific European,

national or local regulations regarding disposal.

#### **Section 14: TRANSPORT INFORMATION**

IMDG/IMO

**14.1 UN/ID no** UN3264

**14.2 Proper Shipping Name** Corrosive liquid, acidic, inorganic, n.o.s. (manganese dinitrate)

14.3 Hazard class 8
14.4 Packing Group III

14.5 Marine Pollutant Not applicable

14.6 Special Provisions None

14.7 Transport in bulk according to This product is not transported in bulk containers.

Annex II of MARPOL and the IBC

Code

<u>RID</u>

**14.1 UN/ID no** UN3264

**14.2 Proper Shipping Name** Corrosive liquid, acidic, inorganic, n.o.s. (manganese dinitrate)

14.3 Hazard class814.4 Packing GroupIII

14.5 Environmental Hazard Not applicable

14.6 Special Provisions None

ADR/RID

14.1 UN/ID no UN3264

**14.2 Proper Shipping Name** Corrosive liquid, acidic, inorganic, n.o.s. (manganese dinitrate)

14.3 Hazard class 8
14.4 Packing Group III

14.5 Environmental Hazard Not applicable

14.6 Special Provisions None

ICAO/IATA

**14.1 UN/ID no** UN3264

SDS #: NP-0013-1-A

Revision date: 2018-07-20 Version 1.01

**14.2 Proper Shipping Name** Corrosive liquid, acidic, inorganic, n.o.s. (manganese dinitrate)

14.3 Hazard class 8
14.4 Packing Group III

14.5 Environmental Hazard Not applicable

14.6 Special Provisions None

#### Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

#### Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

#### **Persistent Organic Pollutants**

Not Applicable

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not Applicable

#### **International Inventories**

Chemical name	TSCA (United States)	DSL (Canada)	EINECS/ELINC S (Europe)	ENCS (Japan)	China (IECSC)	KECL (Korea)	PICCS (Philippines)	AICS (Australia)
MANGANESE DINITRATE 10377-66-9	Х	Х	Х	Х	Х	Х	Х	Х
Nitric acid 7697-37-2	Х	Х	Х	Х	Х	Х	X	X

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment has not yet been completed for this substance

#### Section 16: OTHER INFORMATION

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under sections 2 and 3

EUH071 - Corrosive to the respiratory tract

H272 - May intensify fire; oxidiser

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

**Legend** 

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: CAS (Chemical Abstracts Service)

Ceiling: Maximum limit value:

**DNEL:** Derived No Effect Level (DNEL)

**EINECS**: EINECS (European Inventory of Existing Chemical Substances)

GHS: Globally Harmonised System (GHS)

#### NP-0013-1-A Jett Mn 235 (SDS + ES)

**SDS #**: NP-0013-1-A **Revision date**: 2018-07-20

Version 1.01

IATA: International Air Transport Association (IATA)
ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods (IMDG)

LC50: LC50 (lethal concentration)

LD50: LD50 (lethal dose)

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail

STEL: Short term exposure limit

**SVHC**: Substances of Very High Concern for Authorisation:

**TWA:** time weighted average

vPvB: very Persistent and very Bioaccumulative

**Revision date:** 2018-07-20

Reason for revision: SDS sections updated.

#### **Disclaimer**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

#### Prepared By

**FMC** Corporation

FMC Logo - Trademark of FMC Corporation

© 2019 FMC Corporation. All Rights Reserved.

**End of Safety Data Sheet** 



# EXPOSURE SCENARIO FOR COMMUNICATION

Substance Name: Manganese Dinitrate 10377-66-9 for CSR

**EC Number:** 233-828-8 **CAS Number:** 10377-66-9

**Registration Number:** 01-2119487993-17-0002 **Date of Generation/Revision:** 10/07/2017

**Author:** Cheminova A/S



## **Table of Contents**

1. ES 1: Manufacture	3
2. ES 2: Formulation or re-packing	6
3. ES 3: Widespread use by professional workers; Fertilizers; Agriculture, forestry, fishery	9



### 1. ES 1: Manufacture

#### 1.1. Title section

ES name: Manufacture

Environment	
1: Manufacture	ERC 1
Worker	
2: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC 1
3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC 3
4: Manual maintenance (cleaning and repair) of machinery	PROC 4
5: Bulk transfers	PROC 8b
6: Drum/batch transfers	PROC 9
7: Use of the substance within laboratory settings, including material transfers and equipment cleaning	PROC 15

### 1.2. Conditions of use affecting exposure

### 1.2.1. Control of environmental exposure: Manufacture (ERC 1)

#### Amount used, frequency and duration of use (or from service life)

Daily amount per site <= 50.0 tonnes/day

Annual amount per site <= 999.0 tonnes/year

#### Conditions and measures related to external treatment of waste (including article waste)

Dispose of waste product or used containers according to local regulations.

#### Other conditions affecting environmental exposure

Assumed effluent discharge flow from site  $>= 0.0 \text{ m} \frac{3}{\text{day}}$ 

#### 1.2.2. Control of worker exposure

#### Conditions of use applicable to all contributing scenarios

#### Product (Article) characteristics

Covers concentrations up to 25.0% (The IOELV is based on the Manganese ion  $(Mn^{2+})$  and therefore it is the concentration of  $Mn^{2+}$  in the  $Mn(NO_3)_2$  solution that is crucial)

#### Technical and organisational conditions and measures

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.; Ensure control measures are regularly inspected and maintained.

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.; For further specification, refer to section 8 of the SDS.

Use suitable eye protection.

#### Other conditions affecting workers exposure

Indoor use

Assumes process temperature up to 40.0 °C



#### Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC 1)	Covers use up to 8.0 h/day Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC 3)	Covers use up to 8.0 h/day Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 %
Manual maintenance (cleaning and repair) of machinery (PROC 4)	Covers use up to 8.0 h/day Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 %
Bulk transfers (PROC 8b)	Covers use up to 4.0 h/day Local exhaust ventilation. Inhalation - minimum efficiency of 95.0 %
Drum/batch transfers (PROC 9)	Covers use up to 8.0 h/day Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 %
Use of the substance within laboratory settings, including material transfers and equipment cleaning (PROC 15)	Covers use up to 8.0 h/day Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 %

## 1.3. Exposure estimation and reference to its source

### 1.3.1. Environmental release and exposure: Manufacture (ERC 1)

Release route	Release rate	Release estimation method
Water	0 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Sewage Treatment Plant	0 mg/L (EUSES 2.1.2)	< 0.01

# 1.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	1.02E-3 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.068

# 1.3.3. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
	l =	



Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.021 mg/kg bw/day (TRA Workers 3.0)	0.018
Combined, systemic, long term		0.085

# 1.3.4. Worker exposure: Manual maintenance (cleaning and repair) of machinery (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.206 mg/kg bw/day (TRA Workers 3.0)	0.182
Combined, systemic, long term		0.249

## 1.3.5. Worker exposure: Bulk transfers (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.03E-3 mg/m³ (TRA Workers 3.0)	0.02
Dermal, systemic, long term	0.411 mg/kg bw/day (TRA Workers 3.0)	0.364
Combined, systemic, long term		0.384

### 1.3.6. Worker exposure: Drum/batch transfers (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.206 mg/kg bw/day (TRA Workers 3.0)	0.182
Combined, systemic, long term		0.249

# 1.3.7. Worker exposure: Use of the substance within laboratory settings, including material transfers and equipment cleaning (PROC 15)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.01 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.076

# 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES



## 2. ES 2: Formulation or re-packing

#### 2.1. Title section

ES name: Formulation or re-packing

Environment	
1: Formulation [mixing] of preparations and/or re-packaging	ERC 2
Worker	
2: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC 3
3: Bulk transfers	PROC 8b
4: Drum/batch transfers	PROC 9
5: Transfer of solution outside (Without additional ventilation)	PROC 9
6: Use of the substance within laboratory settings, including material transfers and equipment cleaning	PROC 15

## 2.2. Conditions of use affecting exposure

# 2.2.1. Control of environmental exposure: Formulation [mixing] of preparations and/or re-packaging (ERC 2)

Amount used, frequency and duration of use (or from service life)	
Daily amount per site <= 10.0 tonnes/day	
Annual amount per site <= 999.0 tonnes/year	
Other conditions affecting environmental exposure	
Assumed effluent discharge flow from site $\geq 0.0 \text{ m}$ 3/day	

### 2.2.2. Control of worker exposure

#### Conditions of use applicable to all contributing scenarios

#### **Product (Article) characteristics**

Covers concentrations up to 25.0% (The IOELV is based on the Manganese ion  $(Mn^{2+})$  and therefore it is the concentration of  $Mn^{2+}$  in the  $Mn(NO_3)_2$  solution that is crucial)

#### Technical and organisational conditions and measures

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.; Ensure control measures are regularly inspected and maintained.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.; For further specification, refer to section 8 of the SDS.

Use suitable eye protection.

#### Other conditions affecting workers exposure

Assumes process temperature up to 40.0 °C

#### Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Manufacture or formulation	Covers use up to 8.0 h/day
in the chemical industry in	Manufacture or formulation in the chemical industry in closed batch
closed batch processes with	processes with occasional controlled exposure or processes with equivalent
occasional controlled	containment condition



exposure or processes with equivalent containment condition (PROC 3)	Provide a good standard of controlled ventilation (5 to 10 air changes per hour).  Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 %  Indoor use
Bulk transfers (PROC 8b)	Covers use up to 8.0 h/day Provide a good standard of controlled ventilation (5 to 10 air changes per hour).  Local exhaust ventilation. Inhalation - minimum efficiency of 95.0 % Indoor use
Drum/batch transfers (PROC 9)	Covers use up to 8.0 h/day Provide a good standard of controlled ventilation (5 to 10 air changes per hour).  Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 % Indoor use
Transfer of solution outside (Without additional ventilation) (PROC 9)	Covers use up to 1.0 h/day Outdoor use
Use of the substance within laboratory settings, including material transfers and equipment cleaning (PROC 15)	Covers use up to 8.0 h/day Provide a good standard of controlled ventilation (5 to 10 air changes per hour).  Local exhaust ventilation. Inhalation - minimum efficiency of 90.0 % Indoor use

## 2.3. Exposure estimation and reference to its source

# 2.3.1. Environmental release and exposure: Formulation [mixing] of preparations and/or re-packaging (ERC 2)

Release route	Release rate	Release estimation method
Water	0 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Sewage Treatment Plant	0 mg/L (EUSES 2.1.2)	< 0.01

# 2.3.2. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.021 mg/kg bw/day (TRA Workers 3.0)	0.018
Combined, systemic, long term		0.085

### **2.3.3.** Worker exposure: Bulk transfers (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	6.71E-3 mg/m³ (TRA Workers 3.0)	0.034
Dermal, systemic, long term	0.411 mg/kg bw/day (TRA Workers 3.0)	0.364
Combined, systemic, long term		0.398

### 2.3.4. Worker exposure: Drum/batch transfers (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
---------------------------------------	-------------------	-----



Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.206 mg/kg bw/day (TRA Workers 3.0)	0.182
Combined, systemic, long term		0.249

# **2.3.5.** Worker exposure: Transfer of solution outside (Without additional ventilation) (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.063 mg/m³ (TRA Workers 3.0)	0.313
Dermal, systemic, long term	0.206 mg/kg bw/day (TRA Workers 3.0)	0.182
Combined, systemic, long term		0.495

# 2.3.6. Worker exposure: Use of the substance within laboratory settings, including material transfers and equipment cleaning (PROC 15)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.013 mg/m³ (TRA Workers 3.0)	0.067
Dermal, systemic, long term	0.01 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.076

# 2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES



# 3. ES 3: Widespread use by professional workers; Fertilizers; Agriculture, forestry, fishery

#### 3.1. Title section

ES name: Fertilizers (soil amendments) Product category: Fertilizers (PC 12)

Sector of use: Agriculture, forestry, fishery (SU 1)

#### **Environment**

1: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) ERC 8e

Worker

2: Widespread use by professional workers PROC 11

### 3.2. Conditions of use affecting exposure

# 3.2.1. Control of environmental exposure: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC 8e)

Conditions and measures related to biological sewage treatment plant

Municipal sewage treatment plant is assumed.

Conditions and measures related to external treatment of waste (including article waste)

Dispose of waste product or used containers according to local regulations.

#### 3.2.2. Control of worker exposure

#### Conditions of use applicable to all contributing scenarios

#### **Product (Article) characteristics**

Covers concentrations up to 25.0% (The IOELV is based on the Manganese ion  $(Mn^{2+})$  and therefore it is the concentration of  $Mn^{2+}$  in the  $Mn(NO_3)_2$  solution that is crucial)

#### Amount used (or contained in articles), frequency and duration of use/exposure

Covers use up to 8.0 h/day

#### Other conditions affecting workers exposure

Outdoor use

Assumes process temperature up to 30.0 °C

## 3.3. Exposure estimation and reference to its source

# 3.3.1. Environmental release and exposure: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC 8e)

Release route	Release rate	Release estimation method
Water	0 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

# 3.3.2. Worker exposure: Widespread use by professional workers (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.1E-3 mg/m³ (German model)	< 0.01



Route of exposure and type of effects	Exposure estimate	RCR
Dermal, systemic, long term	0.019 mg/kg bw/day (UK Pesticide Operator Exposure Model (POEM))	0.017
Combined, systemic, long term		0.022

# 3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ${\bf ES}$

10