Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sportak® 450 EC

Recommended use of the chemical and restrictions on use

Recommended use : Can be used as fungicide only.

Restrictions on use : Use as recommended by the label.

Manufacturer or supplier's details

Company : FMC Corporation

Address : 2929 Walnut Street

Philadelphia PA 19104

USA

Telephone : (215) 299-6000

E-mail address : SDS-Info@fmc.com

Emergency telephone : For leak, fire, spill or accident emergencies, call:

001-803-017-9114 (CHEMTREC)

1 703 / 741-5970 (CHEMTREC - International)

Medical emergency: 0800 140 1447

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Serious eye damage/eye irri-

tation

Category 2A

Specific target organ toxicity - :

single exposure

Category 3 (Respiratory system)

Specific target organ toxicity - :

repeated exposure

(Inhalation)

Category 2 (hearing organs)

Aspiration hazard : Category 1

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

GHS label elements

Hazard pictograms









Signal Word : DANGER

Hazard Statements : H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs (hearing organs) through

prolonged or repeated exposure if inhaled.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smokina.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
prochloraz (ISO)	67747-09-5	>= 30 -< 60
xylene	1330-20-7	>= 25 -< 30
ethylbenzene	100-41-4	>= 2,5 -< 10
Benzenesulfonic acid, mono-C11-13-branched	68953-96-8	>= 3 -< 10
alkyl derivs., calcium salts		
1-methoxy-2-propanol	107-98-2	< 10
2-methylpropan-1-ol	78-83-1	>= 1 -< 3

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

If experiencing any discomfort, immediately remove from exposure. Light cases: Keep person under surveillance. Get medical attention immediately if symptoms develop. Serious cases: Get medical attention immediately or call for an ambu-

lance.

In case of skin contact : Take off all contaminated clothing immediately.

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Wash contaminated clothing before re-use.

Wash off immediately with plenty of water for at least 15

minutes.

Get medical attention immediately if irritation develops and

persists.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed.

May be fatal if swallowed and enters airways.

Causes serious eye irritation. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Avoid inhalation, ingestion and contact with skin and eyes.

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Notes to physician : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry chemical, CO2, water spray or regular foam.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

High volume water jet

Do not spread spilled material with high-pressure water

streams.

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Carbon oxides

Nitrogen oxides (NOx) Chlorine compounds

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for fire-fighters

Firefighters should wear protective clothing and self-contained

breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapors accumulating to form explosive concentra-

tions. Vapors can accumulate in low areas.

Never return spills in original containers for re-use.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

For disposal considerations see section 13.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
xylene	1330-20-7	NAB	100 ppm 434 mg/m3	ID OEL		
		Further information: Not classified as carcinogenic				
		to humans. Not enough data to classify these				
		materials as c	materials as carcinogenic to humans or animals			
		PSD	150 ppm	ID OEL		
			651 mg/m3			
		Further information: Not classified as carcinogenic				
		to humans. Not enough data to classify these				
		materials as carcinogenic to humans or animals				
		TWA	20 ppm	ACGIH		
ethylbenzene	100-41-4	NAB	20 ppm	ID OEL		
		Further information: Confirmed animal carcinogen.				
		TWA	20 ppm	ACGIH		
1-methoxy-2-propanol	107-98-2	NAB	100 ppm	ID OEL		
		PSD	150 ppm	ID OEL		
		TWA	50 ppm	ACGIH		
		STEL	100 ppm	ACGIH		
2-methylpropan-1-ol	78-83-1	NAB	50 ppm	ID OEL		
			152 mg/m3			
		TWA	50 ppm	ACGIH		

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after	1.5 g/g creatinine	ACGIH BEI

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

				exposure ceases)		
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable per-

sonal respiratory protection and protective suit.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Plan first aid action before beginning work with this product.

Always have on hand a first-aid kit, together with proper in-

structions.

Ensure that eye flushing systems and safety showers are

located close to the working place. Wear suitable protective equipment.

In the context of professional plant protection use as recommended, the end user must refer to the label and the instruc-

tions for use.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : yellowish-brown

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Odor : aromatic

Odor Threshold : No data available

pH : 7-8

In a 1% aqueous dispersion

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 28 °C

Self-ignition : > 480 °C

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 0,98 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : dispersible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Oxidizing properties : Non-oxidizing

Particle size : No data available

10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Avoid formation of aerosol.

Incompatible materials : Avoid strong acids, bases, and oxidizers.

Hazardous decomposition

products

Nitrogen oxides (NOx)

Carbon oxides

Hydrogen chloride gas

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : LD50 (Rat, female): 2.263 mg/kg

Method: OECD Test Guideline 401

LD50 (Rat, male): 1.715 mg/kg Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat, male and female): > 4.100 mg/kg

Method: OECD Test Guideline 402

Components:

prochloraz (ISO):

Acute oral toxicity : LD50 (Rat, female): ca. 1.010 mg/kg

Method: OECD Test Guideline 425 Symptoms: Breathing difficulties

GLP: yes

Acute inhalation toxicity : LC50 (Rat, male and female): > 2,16 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Method: OECD Test Guideline 403 Symptoms: Breathing difficulties

GLP: yes

Remarks: no mortality

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg

Method: OECD Test Guideline 402

Symptoms: Irritation

GLP: yes

Assessment: The component/mixture is minimally toxic after

single contact with skin. Remarks: no mortality

xylene:

Acute oral toxicity : LD50 (Rat, male): 3.523 mg/kg

Method: Regulation (EC) No. 440/2008, Annex, B.1 bis

LD50 (Rat, female): > 4.000 mg/kg

Method: Regulation (EC) No. 440/2008, Annex, B.1 bis

Acute inhalation toxicity : LC50 (Rat, male and female): 27,6 mg/l, 6350 ppm

Exposure time: 4 h
Test atmosphere: vapor

Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 (Rabbit, male): > 4.200 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat, male and female): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit, male): 15.400 mg/kg

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Acute oral toxicity : LD0 (Rat, male and female): > 2.000 mg/kg

Method: OECD Test Guideline 401

Remarks: no mortality

Acute dermal toxicity : LD50 (Rat, male and female): > 1.000 - 1.600 mg/kg

Method: OECD Test Guideline 402

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rat, male): 3.739 mg/kg

LD50 Oral (Rat, female): 4.277 mg/kg

Acute inhalation toxicity : LC0 (Rat, male and female): > 25,8 mg/l, > 7000 ppm

Exposure time: 6 h

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Test atmosphere: vapor Remarks: no mortality

Acute dermal toxicity : LD50 Dermal (Rat, male and female): > 2.000 mg/kg

Remarks: no mortality

2-methylpropan-1-ol:

Acute oral toxicity : LD50 (Rat): 3.350 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 18,18 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): 2.460 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

Components:

prochloraz (ISO):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

xylene:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

ethylbenzene:

Species : Rabbit

Remarks : Moderate skin irritation

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rabbit Result : Skin irritation

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

1-methoxy-2-propanol:

Species : Rabbit

Result : No skin irritation

2-methylpropan-1-ol:

Species : Rabbit Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Remarks : May cause irreversible eye damage.

Components:

prochloraz (ISO):

Species : Rabbit

Result : Slight or no eye irritation
Assessment : Not classified as irritant
Method : OECD Test Guideline 405

GLP : yes

xylene:

Species : Rabbit

Result : Moderate eye irritation

ethylbenzene:

Species : Rabbit

Result : No eye irritation

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rabbit

Result : Irreversible effects on the eye

1-methoxy-2-propanol:

Species : Rabbit

Result : No eye irritation

2-methylpropan-1-ol:

Species : Rabbit

Result : Irreversible effects on the eye

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Test Type : Buehler Test Species : Guinea pig

Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

Components:

prochloraz (ISO):

Test Type : Local lymph node assay (LLNA)

Species : mice

Assessment : Not a skin sensitizer.

Method : OECD Test Guideline 429

Result : Not a skin sensitizer.

xylene:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitization.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Test Type : Maximization Test

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

1-methoxy-2-propanol:

Test Type : Maximization Test Routes of exposure : Intradermal Species : Guinea pig

Result : Does not cause skin sensitization.

2-methylpropan-1-ol:

Routes of exposure : Skin contact

Result : Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Components:

prochloraz (ISO):

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: mice (male and female)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

xylene:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Method: Regulation (EC) No. 440/2008, Annex, B.10

Result: negative

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Result: negative

Genotoxicity in vivo : Test Type: Rodent Dominant Lethal Assay

Species: Mouse (male)

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 478

Result: negative

ethylbenzene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Method: OECD Test Guideline 474

Result: negative

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Remarks: Based on data from similar materials

Test Type: reverse mutation assay

Method: Mutagenicity (Salmonella typhimurium - reverse mu-

tation assay) Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Application Route: Oral Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

1-methoxy-2-propanol:

Genotoxicity in vitro : Test Type: reverse mutation assay

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Result: negative

Test Type: gene mutation test

Test system: Chinese hamster fibroblasts

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

2-methylpropan-1-ol:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Not classified based on available information.

Components:

prochloraz (ISO):

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

xylene:

Species : Rat
Application Route : Oral
Exposure time : 103 weeks
Result : negative

ethylbenzene:

Species : Mouse, male and female

Application Route : Inhalation Exposure time : 104 weeks Result : positive

1-methoxy-2-propanol:

Species : Rat, male and female Application Route : inhalation (vapor)

Exposure time : 2 years

Dose : 300, 1000, 3000 ppm

300 ppm

Method : OECD Test Guideline 453

Result : negative

Species : Mouse, male and female

Application Route : inhalation (vapor)

Exposure time : 2 years

Dose : 300, 1000, 3000 ppm

1.000 ppm

Method : OECD Test Guideline 453

Result : negative

Carcinogenicity - Assess-

nent

Weight of evidence does not support classification as a car-

cinogen

Reproductive toxicity

Not classified based on available information.

Components:

prochloraz (ISO):

Reproductive toxicity - As-

sessment

No toxicity to reproduction

xylene:

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: inhalation (vapor)
General Toxicity F1: NOAEC: 2,171 mg/l

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Pre-natal

Species: Rat

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Application Route: inhalation (vapor)

Symptoms: Maternal effects.

Result: negative

Remarks: Based on data from similar materials

ethylbenzene:

Effects on fertility : Species: Rat, male and female

Application Route: Inhalation Method: OECD Test Guideline 415

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat, female

Application Route: Inhalation Method: OECD Test Guideline 414

Result: negative

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Effects on fertility : Test Type: Three-generation study

Species: Rat, male and female Application Route: Oral

Dose: 14, 70, 350 mg/kg bw d

General Toxicity Parent: NOAEL: 350 mg/kg body weight

General Toxicity F1: NOAEL: 350 mg/kg bw/day General Toxicity F2: NOAEL: 350 mg/kg bw/day

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: reproductive and developmental toxicity study

Species: Rat

Application Route: Oral

Dose: 0.2, 2.0, 300 and 600 mg/kg Duration of Single Treatment: 20 d

General Toxicity Maternal: LOAEL: 600 mg/kg body weight

Teratogenicity: LOAEL: 600 mg/kg bw/day

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

1-methoxy-2-propanol:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female Application Route: inhalation (vapor) Dose: 300, 1000, 3000 parts per million General Toxicity Parent: LOAEL: 1.000 General Toxicity F1: LOAEL: 3.000

General Toxicity F2: 3.000

Method: OECD Test Guideline 416

Result: negative

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Effects on fetal development : Test Type: reproductive and developmental toxicity study

Species: Rabbit

Application Route: Inhalation

Dose: 0, 500, 1500, 3000 parts per million Duration of Single Treatment: 29 d

General Toxicity Maternal: LOAEL: 3.000 part per million

Teratogenicity: NOAEL: 3.000 part per million

Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

2-methylpropan-1-ol:

Effects on fertility : Species: Rat

Application Route: Inhalation

Fertility: NOAEC Mating/Fertility: 7,5 mg/l

STOT-single exposure

May cause respiratory irritation.

Components:

xylene:

Assessment : May cause respiratory irritation.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

2-methylpropan-1-ol:

Assessment : May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

Components:

xylene:

Routes of exposure : Inhalation
Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

ethylbenzene:

Routes of exposure : Inhalation
Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Repeated dose toxicity

Components:

prochloraz (ISO):

Species : Rat, male and female LOAEL : 6 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Dose : 6, 25, 100 mg/kg bw/day Symptoms : increased liver weight

Species : Mouse, male and female

LOAEL : 25 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Dose : 6, 25, 100, 400 mg/kg bw/day

Symptoms : increased liver weight

Species : Dog, male and female

NOAEL : 2,5 mg/kg LOAEL : 7 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Dose : 1, 2.5, 7, 20 mg/kg bw/day Symptoms : increased liver weight

xylene:

Species : Rat

NOAEC : 3,515 mg/l Application Route : Inhalation Exposure time : 13 weeks

ethylbenzene:

Species : Rat, male and female

NOAEL : 75 mg/kg Application Route : Oral Exposure time : 28 days

Method : OECD Test Guideline 407

Species : Rat, male and female

NOAEL : 250 ppm LOAEL : 75 ppm

Application Route : inhalation (vapor)

Exposure time : 728 days

Method : OECD Test Guideline 453

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rat, male and female NOAEL : 40 mg/kg bw/day LOAEL : 115 mg/kg bw/day

Application Route : Oral - feed Exposure time : 6 months

Dose : 40, 115, 340, 1030 mg/kg bw d Remarks : Based on data from similar materials

1-methoxy-2-propanol:

Species : Rat, male

LOAEL : 2757 mg/kg bw/day

Application Route : Oral Exposure time : 35 d

Dose : 91.9,275.7,919,2757mg/kg

Species : Rat, male and female

NOEL : 300 ppm

Application Route : inhalation (vapor)

Exposure time : 2 years

Dose : 300, 1000, 3000ppm Method : OECD Test Guideline 453

Species : Rabbit, male

LOAEL : 3676 mg/kg bw/day

Application Route : Skin contact

Exposure time : 90d

Dose : 1838,3676, 6433, 9190mg/kg

2-methylpropan-1-ol:

Species : Rat

: 1450 mg/kg

Application Route : Oral

Species : Rat

7,5 mg/l

Application Route : Inhalation

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

prochloraz (ISO):

The substance does not have properties associated with aspiration hazard potential.

xylene:

May be fatal if swallowed and enters airways.

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

xylene:

General Information : Target Organs: inner ear

Symptoms: hearing loss

Target Organs: Central nervous system Symptoms: Drowsiness, Dizziness

ethylbenzene:

General Information : Target Organs: inner ear

Symptoms: hearing loss

Further information

Product:

Remarks : Solvents may degrease the skin.

Components:

prochloraz (ISO):

Remarks : Ingestion may cause gastrointestinal irritation, nausea, vomit-

ing and diarrhea.

Contact may cause slight irritation.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Components:

prochloraz (ISO):

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 1,2 mg/l

Exposure time: 96 h Test Type: static test

GLP: yes

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

LC50 (Lepomis macrochirus (Bluegill sunfish)): 2,2 mg/l

Exposure time: 96 h
Test Type: static test

GLP: yes

LC50 (Oncorhynchus mykiss (rainbow trout)): 1,5 mg/l

Exposure time: 96 h Test Type: static test

GLP: yes

Toxicity to daphnia and other : aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4,3 mg/l

Exposure time: 48 h
Test Type: static test

EC50 (Crassostrea virginica (atlantic oyster)): 0,69 - 1,3 mg/l

Exposure time: 96 h

Test Type: flow-through test

GLP: yes

LC50 (Mysidopsis bahia (opossum shrimp)): 0,86 mg/l

Exposure time: 48 h

GLP: yes

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 0,032

mg/

Exposure time: 72 h

ErC50 (Lemna gibba (duckweed)): 0,109 mg/l

Exposure time: 7 d

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0,0485 mg/l

Exposure time: 36 d

NOEC (Salmo gairdneri): 0,18 mg/l

End point: mortality Exposure time: 28 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0,0222 mg/l

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

: 1

Toxicity to terrestrial organ-

isms

LD50 (Apis mellifera (bees)): 51 µg/bee

End point: Acute contact toxicity

LD50 (Apis mellifera (bees)): 61 µg/bee

End point: Acute oral toxicity

xylene:

Sportak® 450 EC



SDS Number: Date of last issue: -Version Revision Date:

2024/10/17 50000536 1.3 Date of first issue: 2017/07/17

LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l Toxicity to fish

Exposure time: 96 h

Test Type: Static renewal test Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2

ma/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1,3 mg/l

Exposure time: 56 d

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): 0,96 mg/l

Exposure time: 7 d

Remarks: Based on data from similar materials

Toxicity to microorganisms NOEC (activated sludge): 16 mg/l

Exposure time: 28 h

Method: OECD Test Guideline 301F

Toxicity to soil dwelling or-

ganisms

NOEC (Eisenia fetida (earthworms)): 16 mg/kg

Exposure time: 14 d

Remarks: Based on data from similar materials

ethylbenzene:

Toxicity to fish LC50 (Menidia menidia (Atlantic silverside)): 5,1 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

EC50 (Ceriodaphnia dubia (water flea)): 3,2 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (algae)): 3,6 mg/l

Exposure time: 96 h

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

EC50 (Skeletonema costatum (marine diatom)): 7,7 mg/l

Exposure time: 96 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Fish): 0,25 - 3,4 mg/l

Method: QSAR

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): 0,96 mg/l

Exposure time: 7 d

Toxicity to microorganisms : Method: OECD Test Guideline 209

Toxicity to soil dwelling or-

ganisms

(Eisenia fetida (earthworms)): 0,047 mg/cm2

Exposure time: 48 d

Method: OECD Test Guideline 207

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 31,6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 62 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 29 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,5

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0,23 mg/l

Exposure time: 72 d

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1,18 mg/l

Exposure time: 21 d

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (activated sludge): 550 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to soil dwelling or-

ganisms

NOEC (Eisenia fetida (earthworms)): 250 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 207

Remarks: Based on data from similar materials

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

LC50 (Eisenia fetida (earthworms)): > 1.000 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 207

Remarks: Based on data from similar materials

Plant toxicity : EC50: 167 mg/kg

Exposure time: 21 d

Species: Sorghum bicolor (sorghum)

80 mg/kg

Exposure time: 14 d

Species: Avena sativa (oats)

Toxicity to terrestrial organ-

isms

EC10 (Hypoaspis aculeifer): 82 mg/kg

Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): >= 1.000 mg/l

Exposure time: 96 h
Test Type: semi-static test

LC50 (Pimephales promelas (fathead minnow)): 20.800 mg/l

Exposure time: 96 h Test Type: static test

LC50 (Leuciscus idus (Golden orfe)): 6.812 mg/l

Exposure time: 96 h Test Type: static test Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 21.100 - 25.900 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l

Exposure time: 7 d Test Type: static test

Toxicity to microorganisms : IC50 (activated sludge): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

2-methylpropan-1-ol:

Toxicity to fish : LC50 : 1.430 mg/l

Exposure time: 4 d

Toxicity to daphnia and other :

aquatic invertebrates

EC50: 1.100 mg/l Exposure time: 48 h

Toxicity to daphnia and other : NOEC: 20 mg/l

25 / 32

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Toxicity to microorganisms : EC50 (Anabaena flos-aquae (cyanobacterium)): 593 - 1.799

mg/l

Exposure time: 72 h

IC50 (Natural microorganism): 1.000 mg/l

Exposure time: 16 h

Persistence and degradability

Components:

prochloraz (ISO):

Biodegradability : Result: Not readily biodegradable.

xylene:

Biodegradability : aerobic

Inoculum: activated sludge, non-adapted

Concentration: 16 mg/l Result: Readily biodegradable.

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

aerobic

Inoculum: activated sludge, non-adapted

Concentration: 16 mg/l Result: Readily biodegradable.

Biodegradation: 94 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

aerobic

Inoculum: activated sludge, non-adapted

Concentration: 16,2 mg/l Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

ethylbenzene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 79 % Exposure time: 10 d

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

Biodegradability : Inoculum: activated sludge, non-adapted

Result: Not readily biodegradable.

Biodegradation: 2,9 % Exposure time: 28 d

Method: OECD Test Guideline 301E

Result: Inherently biodegradable. Biodegradation: > 35 - 45 %

Exposure time: 10 d

1-methoxy-2-propanol:

Biodegradability : Inoculum: activated sludge

Result: Readily biodegradable.

Method: OECD Test Guideline 301E

2-methylpropan-1-ol:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

prochloraz (ISO):

Bioaccumulation : Remarks: See section 9 for octanol-water partition coefficient.

The product may be accumulated in organisms.

Partition coefficient: n-

octanol/water

log Pow: 4,12 (25 °C)

xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): > 4,9

Exposure time: 7 d Concentration: 1,3 mg/l

Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

log Pow: 3,2 (20 °C)

pH: 7

Remarks: Based on data from similar materials

log Pow: 3,12 (20 °C)

pH: 7

Remarks: Based on data from similar materials

log Pow: 3,15 (20 °C)

pH: 7

Remarks: Based on data from similar materials

log Pow: 3,15 (20 °C)

pH: 7

Remarks: Based on data from similar materials

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

ethylbenzene:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 110

Partition coefficient: n- : Pow: 4.170 (20 °C)

octanol/water log Pow: 3,03 - 3,6 (20 °C)

pH: 7,84

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Method: QSAR

Partition coefficient: n-

octanol/water

log Pow: 4,595 (20 °C)

1-methoxy-2-propanol:

Partition coefficient: n-

: log Pow: < 1 (20 °C)

octanol/water

pH: 6,8

2-methylpropan-1-ol:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <=

4).

Partition coefficient: n-

octanol/water

Pow: 10 (25 °C)

Mobility in soil

Components:

prochloraz (ISO):

Distribution among environ-

mental compartments

Remarks: immobile

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(prochloraz, Xylene)

Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

(prochloraz, Xylene)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo :

aircraft)

Packing instruction (passen: 355

ger aircraft)

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

366

(prochloraz, Xylene)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Minister of Industry Regulation No. 23/M-IND/PER/4/2013 concerning the Revision of Minister of Industry Regulation No. 87/M-IND/PER/9/2009 concerning Globally Harmonized System of Classification and Labelling of Chemicals.

Regulation of the Minister of Health No. 472 of 1996 on the Safeguarding of Substances Hazardous to Health

Hazardous substances that must be registered : Not applicable

Government Regulation No. 74 of 2001 on the Management of Hazardous and Toxic Substances

Hazardous substances approved for use : Not applicable

Prohibited substances : Not applicable

Restricted substances : Not applicable

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains chemical substance(s) exempt from

CEPA DSL Inventory requirements. It is regulated as a pesticide subject to Pest Control Products Act (PCPA) requirements. Read the PCPA label, authorized under the Pest Control Products Act, prior to using or handling this pest control

product.

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

TECI: Not in compliance with the inventory

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

16. OTHER INFORMATION

Revision Date : 2024/10/17

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
ID OEL : Indonesia. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit ID OEL / NAB : Long term exposure limit ID OEL / PSD : Short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or

Sportak® 450 EC



Version Revision Date: SDS Number: Date of last issue: -

1.3 2024/10/17 50000536 Date of first issue: 2017/07/17

implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

ID / EN