SPORTAK EC 250



Version **Revision Date:** SDS Number: Date of last issue: 2021/04/19 2021/04/26 50000588 Date of first issue: 2021/04/19 1.1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name SPORTAK EC 250

Other means of identification Prochloraz 25% (w/w)

Recommended use of the chemical and restrictions on use

Recommended use Can be used as fungicide only

Restrictions on use Use as recommended by the label.

Manufacturer or supplier's details

Company FMC Taiwan Co., Ltd.

Address 3F, No. 179, Fuhuiyuan Blvd., Xitun Dist,

Taichung 40758

+886(4) 2254 2785 Telephone

Emergency telephone For leak, fire, spill or accident emergencies, call:

00801-14-8954 (CHEMTREC)

Medical emergency:

00886 2 28757525 (in case of chemical spill, fire or poisoning

accident)

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids Category 3

Acute toxicity (Oral) Category 4

Acute toxicity (Inhalation) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 2A

Skin sensitization Category 1

Carcinogenicity Category 2

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

Aspiration hazard : Category 1

Short-term (acute) aquatic

hazard

: Category 1

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms









Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H302 + H332 Harmful if swallowed or if inhaled. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical Name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 50 -< 70
prochloraz (ISO)	67747-09-5	>= 22.5 -< 27.5
Benzenesulfonic acid, mono-C11-13-branched	68953-96-8	>= 3 -< 10
alkyl derivs., calcium salts		
2-methylpropan-1-ol	78-83-1	>= 1 -< 3

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

First aid measures for different exposure routes

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

Harmful if swallowed or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Notes to physician : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Thermal decomposition can lead to release of irritating gases

and vapors.

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

SPORTAK EC 250



Version **Revision Date:** SDS Number: Date of last issue: 2021/04/19 2021/04/26 50000588 Date of first issue: 2021/04/19 1.1

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapors accumulating to form explosive concentra-

tions. Vapors can accumulate in low areas.

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

7. HANDLING AND STORAGE

Handling

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Keep away from open flames, hot surfaces and sources of

ignition.

Avoid formation of aerosol. Advice on safe handling

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Storage

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis	
		(Form of	ters / Permissible		
		exposure)	concentration		
Solvent naphtha (petroleum),	64742-94-5	TWA	200 mg/m3	ACGIH	
heavy arom.			(total hydrocarbon		
			vapor)		
2-methylpropan-1-ol	78-83-1	TWA	50 ppm	TW OEL	
			152 mg/m3		
	Further information: Type 2 organic solvent				
		STEL	75 ppm	TW OEL	
			190 mg/m3		
	Further information: Type 2 organic solvent				
		TWA	50 ppm	ACGIH	

Biological occupational exposure limits

Contains no substances with biological exposure indices.

Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable per-

sonal respiratory protection and protective suit.

Hand protection

Remarks : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber. The suitability for a specific workplace should be discussed with the producers of the

protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : Light yellow to yellow

Odor : aromatic

pH : 5.5 - 8.5

Flash point : 25 - 27 °C

Flammability (liquids) : Sustains combustion

Self-ignition : > 480 °C

Density : 0.98 g/cm3 (22.8 °C)

Viscosity

Viscosity, kinematic : 17.3 mm2/s (25 °C)

14.3 mm2/s (45 °C)

10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents

Hazardous decomposition

products

Stable under recommended storage conditions.

11. TOXICOLOGICAL INFORMATION

Symptoms of Overexposure : None known.

Acute toxicity

Harmful if swallowed or if inhaled.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Product:

Acute oral toxicity : LD50 (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.12 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Components:

Solvent naphtha (petroleum), heavy arom.:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): > 4.688 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

prochloraz (ISO):

Acute oral toxicity : LD50 (Rat): 1,023 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.16 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,100 mg/kg

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Acute oral toxicity : LD0 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 401

Remarks: no mortality

Acute dermal toxicity : LD50 (Rat, male and female): > 1,000 - 1,600 mg/kg

Method: OECD Test Guideline 402

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

2-methylpropan-1-ol:

Acute oral toxicity : LD50 (Rat): 3,350 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 18.18 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): 2,460 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : May cause skin irritation and/or dermatitis.

Components:

Solvent naphtha (petroleum), heavy arom.:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

prochloraz (ISO):

Method : OECD Test Guideline 404

Result : No skin irritation

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rabbit
Result : Skin irritation

2-methylpropan-1-ol:

Species : Rabbit Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit Result : Eye irritation

Remarks : May cause irreversible eye damage.

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

Components:

Solvent naphtha (petroleum), heavy arom.:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

prochloraz (ISO):

Result : slight irritation

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rabbit

Result : Irreversible effects on the eye

2-methylpropan-1-ol:

Species : Rabbit

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Test Type : Local lymph node assay (LLNA)

Species : mice

Method : OECD Test Guideline 429

Result : May cause sensitization by skin contact.

Components:

Solvent naphtha (petroleum), heavy arom.:

Test Type : Maximization Test

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.
Remarks : Based on data from similar materials

prochloraz (ISO):

Result : Not a skin sensitizer.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Test Type : Maximization Test

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

2-methylpropan-1-ol:

Routes of exposure : Skin contact

Result : Not a skin sensitizer.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), heavy arom.:

Genotoxicity in vitro : Test Type: reverse mutation assay

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Cytogenetic assay

Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials

prochloraz (ISO):

Germ cell mutagenicity -

Assessment

No genotoxic potential

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Test Type: reverse mutation assay

Method: Mutagenicity (Salmonella typhimurium - reverse mu-

tation assay) Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Application Route: Oral

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

2-methylpropan-1-ol:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Suspected of causing cancer.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Components:

Solvent naphtha (petroleum), heavy arom.:

Species : Mouse
Application Route : Dermal
Exposure time : 104 weeks
Result : negative

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

prochloraz (ISO):

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

Reproductive toxicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), heavy arom.:

Effects on fertility : Test Type: Fertility

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 415

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: reproductive and developmental toxicity study

Species: Rat

Application Route: Oral

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

prochloraz (ISO):

Reproductive toxicity - As-

sessment

No toxicity to reproduction

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Effects on fertility : Test Type: Three-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 14, 70, 350 mg/kg bw d

General Toxicity Parent: NOAEL: 350 mg/kg body weight

General Toxicity F1: NOAEL: 350 mg/kg bw/day General Toxicity F2: NOAEL: 350 mg/kg bw/day

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: reproductive and developmental toxicity study

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

Species: Rat

Application Route: Oral

Dose: 0.2, 2.0, 300 and 600 mg/kg Duration of Single Treatment: 20 d

General Toxicity Maternal: LOAEL: 600 mg/kg body weight

Teratogenicity: LOAEL: 600 mg/kg bw/day

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

2-methylpropan-1-ol:

Effects on fertility : Species: Rat

Application Route: Inhalation

Fertility: NOAEC Mating/Fertility: 7.5 mg/l

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Solvent naphtha (petroleum), heavy arom.:

Assessment : May cause drowsiness or dizziness.

prochloraz (ISO):

Remarks : No significant adverse effects were reported

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

2-methylpropan-1-ol:

Assessment : May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Components:

prochloraz (ISO):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

Solvent naphtha (petroleum), heavy arom.:

Species : Rat, male and female

SPORTAK EC 250



Version **Revision Date:** SDS Number: Date of last issue: 2021/04/19 2021/04/26 50000588 Date of first issue: 2021/04/19 1.1

NOAEL 300 mg/kg **Application Route** Oral - gavage Exposure time 90 day

Remarks Based on data from similar materials

Species Rat, male and female

NOAEL 0.8 - 0.9 mg/l **Application Route** inhalation (vapor) Exposure time 12 months

Symptoms Reduced body weight

prochloraz (ISO):

Species Rat LOAEL 60 mg/kg

Symptoms increased liver weight, Reduced body weight

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species Rat, male and female **NOAEL** 40 mg/kg bw/day LOAEL 115 mg/kg bw/day **Application Route** Oral - feed

Exposure time 6 months

Dose 40, 115, 340, 1030 mg/kg bw d Remarks Based on data from similar materials

2-methylpropan-1-ol:

Species Rat

1450 mg/kg

Application Route Oral

Species Rat

7.5 mg/l Inhalation Application Route

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:

Solvent naphtha (petroleum), heavy arom.:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

prochloraz (ISO):

The substance does not have properties associated with aspiration hazard potential.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Solvent naphtha (petroleum), heavy arom.:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3

mg/l

Exposure time: 24 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EL50 (Daphnia magna (Water flea)): 0.89 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : LL50 (Tetrahymena pyriformis): 677.9 mg/l

Exposure time: 72 h

Test Type: Growth inhibition

prochloraz (ISO):

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 1.2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.3 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 0.032

mg/l

Exposure time: 72 h

ErC50 (Lemna gibba (duckweed)): 0.109 mg/l

Exposure time: 7 d

M-Factor (Acute aquatic tox-

icity)

10

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.0485 mg/l

Exposure time: 36 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0222 mg/l

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

: 1

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 31.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 62 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 29 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.5

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.23 mg/l

Exposure time: 72 d

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1.18 mg/l

Exposure time: 21 d

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (activated sludge): 550 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to soil dwelling or-

ganisms

NOEC (Eisenia fetida (earthworms)): 250 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 207

Remarks: Based on data from similar materials

LC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 207

Remarks: Based on data from similar materials

Plant toxicity : EC50: 167 mg/kg

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Exposure time: 21 d

Species: Sorghum bicolor (sorghum)

80 mg/kg

Exposure time: 14 d

Species: Avena sativa (oats)

Toxicity to terrestrial organ-

isms

EC10 (Hypoaspis aculeifer): 82 mg/kg

Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

2-methylpropan-1-ol:

Toxicity to fish : LC50: 1,430 mg/l

Exposure time: 4 d

Toxicity to daphnia and other :

aquatic invertebrates

EC50: 1,100 mg/l Exposure time: 48 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 20 mg/l

Exposure time: 21 d

Toxicity to microorganisms : EC50 (Anabaena flos-aquae (cyanobacterium)): 593 - 1,799

mg/l

Exposure time: 72 h

IC50 (Natural microorganism): 1,000 mg/l

Exposure time: 16 h

Persistence and degradability

Components:

Solvent naphtha (petroleum), heavy arom.:

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 58.6 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

prochloraz (ISO):

Biodegradability : Result: Not readily biodegradable.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Biodegradability : Inoculum: activated sludge, non-adapted

Result: Not readily biodegradable.

Biodegradation: 2.9 % Exposure time: 28 d

Method: OECD Test Guideline 301E

Result: Inherently biodegradable.

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

Biodegradation: > 35 - 45 %

Exposure time: 10 d

2-methylpropan-1-ol:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

Solvent naphtha (petroleum), heavy arom.:

Partition coefficient: n-

octanol/water

: log Pow: 2.4 - 6.5

prochloraz (ISO):

Bioaccumulation : Remarks: See section 9 for octanol-water partition coefficient.

The product may be accumulated in organisms.

Partition coefficient: n-

octanol/water

log Pow: 4.12 (25 °C)

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Bioaccumulation : Bioconcentration factor (BCF): 3.16

Method: QSAR

Partition coefficient: n-

octanol/water

log Pow: 4.595 (20 °C)

2-methylpropan-1-ol:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <=

4).

Partition coefficient: n-

octanol/water

Pow: 10 (25 °C)

Mobility in soil

Components:

prochloraz (ISO):

Distribution among environ-

mental compartments

: Remarks: immobile

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Aromatic hydrocarbons, prochloraz)

Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

(Aromatic hydrocarbons, prochloraz)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen: 355

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Aromatic hydrocarbons, prochloraz)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SPORTAK EC 250



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2021/04/19

 1.1
 2021/04/26
 50000588
 Date of first issue: 2021/04/19

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Regulations on Occupational Safety and Health Facilities

Standards for the Storage, Cleanup, Handling and Disposal of Industrial Waste Regulations on Labelling and Hazard Communication of Hazardous Chemicals

Standards of Permissible Exposure Limits in Workplace

Establishment Standards and Safety Control Regulations for Manufacturing, Storing, Processing Public Hazardous Substances and Flammable Pressurized Gases Places: Quantity subject to control

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AICS : On the inventory, or in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

N-PROPYL-N-[2-(2,4,6-

TRICHLOROPHENOXY)ETHYL]IMIDAZOLE-1-

CARBOXAMIDE

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

16. OTHER INFORMATION

Responsible Department : FMC Corporation

Contact Person : Bee Huang

Revision Date : 2021/04/26

SPORTAK EC 250



Version Revision Date: SDS Number: Date of last issue: 2021/04/19
1.1 2021/04/26 50000588 Date of first issue: 2021/04/19

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

TW OEL : Standards of Permissible Exposure Limits in Workplace

ACGIH / TWA : 8-hour, time-weighted average TW OEL / TWA : 8-hour time weighted average

TW OEL / STEL : time weighted average for short term exposure

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

SPORTAK EC 250



Version Revision Date: 1.1 2021/04/26

SDS Number: 50000588

Date of last issue: 2021/04/19 Date of first issue: 2021/04/19

TW / EN