

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name MANGANESE 400

Other means of identification

Product code 50001131

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : A fertilizer with micronutrients for use in agriculture

Recommended restrictions
on use : Use as recommended by the label.
For professional users only.

1.3 Details of the supplier of the safety data sheet

1.3 Details of the supplier of the safety data sheet

Supplier Address FMC Agro Limited
Rectors Lane, Pentre
Flintshire
CH5 2DH
United Kingdom

Telephone: + 44 1244 537370
E-mail address: SDS-Info@fmc.com .

1.4 Emergency telephone number

For leak, fire, spill or accident emergencies, call:
England and Wales: 44-870-8200418 (CHEMTREC)

Medical emergency:
England and Wales: 111
Scotland: 84 54 24 2424

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758





MANGANESE 400

Version 1.3	Revision Date: 25.10.2023	SDS Number: 50001131	Date of last issue: - Date of first issue: 20.07.2018
----------------	------------------------------	-------------------------	--

Skin corrosion, Sub-category 1C	H314: Causes severe skin burns and eye damage.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :  

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H373 May cause damage to organs through prolonged or repeated exposure.

Supplemental Hazard Statements : EUH208 May produce an allergic reaction.

Precautionary statements : **Prevention:**
P260 Do not breathe mist or vapours.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Disposal:
P501 Dispose of contents and/or container in accordance with hazardous waste regulations.

Hazardous components which must be listed on the label:
manganese dinitrate
ethanediol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3 Revision Date: 25.10.2023 SDS Number: 50001131 Date of last issue: -
Date of first issue: 20.07.2018

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
manganese carbonate	598-62-9 209-942-9	Aquatic Chronic 2; H411	>= 30 - < 50
manganese dinitrate	10377-66-9 233-828-8 01-2119487993-17-0002	Ox. Sol. 3; H272 Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 STOT RE 2; H373 Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 1	>= 10 - < 20
sodium acrylate	7446-81-3 231-209-7	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2.5 - < 10
ethanediol	107-21-1 203-473-3 603-027-00-1	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 10 specific concentration limit Skin Sens. 1; H317 >= 0.05 %	>= 0.0025 - < 0.025

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|---|
| General advice | : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician. |
| In case of skin contact | : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|---|
| Risks | : Causes severe skin burns and eye damage.
May cause damage to organs through prolonged or repeated exposure.
May produce an allergic reaction. |
|-------|---|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|------------------------------|--|
| Suitable extinguishing media | : Dry chemical, CO ₂ , water spray or regular foam. |
|------------------------------|--|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Fire may produce irritating, corrosive and/or toxic gases. Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Never return spills in original containers for re-use.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.
For disposal considerations see section 13.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Keep away from combustible material.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Fertilizers

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
manganese carbonate	598-62-9	TWA (Inhalable)	0.2 mg/m ³ (Manganese)	GB EH40
		TWA (Respirable fraction)	0.05 mg/m ³ (Manganese)	GB EH40
		TWA (inhalable fraction)	0.2 mg/m ³ (Manganese)	2017/164/EU
Further information: Indicative				
		TWA (Respirable	0.05 mg/m ³	2017/164/EU

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3 Revision Date: 25.10.2023 SDS Number: 50001131 Date of last issue: -
Date of first issue: 20.07.2018

		fraction)	(Manganese)	
	Further information: Indicative			
manganese dini- trate	10377-66-9	TWA (Inhalable)	0.2 mg/m3 (Manganese)	GB EH40
		TWA (Respirable fraction)	0.05 mg/m3 (Manganese)	GB EH40
		TWA (inhalable fraction)	0.2 mg/m3 (Manganese)	2017/164/EU
	Further information: Indicative			
		TWA (Respirable fraction)	0.05 mg/m3 (Manganese)	2017/164/EU
	Further information: Indicative			
ethanediol	107-21-1	TWA (Vapour)	20 ppm 52 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub- stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA (particles)	10 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub- stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL (Vapour)	40 ppm 104 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub- stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	40 ppm 104 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 52 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
1,2-benzisothiazol- 3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
	Marine water	0.000403 mg/l
	Sewage treatment plant	1.03 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3	Revision Date: 25.10.2023	SDS Number: 50001131	Date of last issue: - Date of first issue: 20.07.2018
----------------	------------------------------	-------------------------	--

8.2 Exposure controls

Personal protective equipment

- | | | |
|-----------------------------|---|---|
| Eye/face protection | : | Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems. |
| Hand protection
Material | : | Wear chemical resistant gloves, such as barrier laminate, butyl rubber or nitrile rubber. |
| Remarks | : | The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Skin and body protection | : | Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Protective measures | : | Plan first aid action before beginning work with this product.
Always have on hand a first-aid kit, together with proper instructions.
Ensure that eye flushing systems and safety showers are located close to the working place.
Wear suitable protective equipment. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|---|---|-----------------------------------|
| Physical state | : | liquid |
| Form | : | liquid |
| Colour | : | beige |
| Odour | : | Barely perceptible |
| Odour Threshold | : | No data available |
| pH | : | 2.5 - 6.0
Concentration: 100 % |
| Melting point/freezing point | : | No data available |
| Initial boiling point and boiling range | : | No data available |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3	Revision Date: 25.10.2023	SDS Number: 50001131	Date of last issue: - Date of first issue: 20.07.2018
----------------	------------------------------	-------------------------	--

Flash point	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	1.70 - 1.75
Density	:	No data available
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	dispersible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	Non-oxidizing

9.2 Other information

Particle size	:	5 - 13 µm
Particle Size Distribution	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Avoid extreme temperatures

10.5 Incompatible materials

Materials to avoid : Avoid strong acids, bases, and oxidizers

10.6 Hazardous decomposition products

Toxic fumes

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008
Remarks: Estimated data

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

manganese carbonate:

Acute oral toxicity : LD0 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Remarks: no mortality

Acute inhalation toxicity : LC0 (Rat, male and female): > 5.35 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: no mortality
Based on data from similar materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

manganese dinitrate:

Acute oral toxicity : LD50 Oral (Rat, female): > 300 mg/kg
Method: OECD Test Guideline 420

ethanediol:

Acute inhalation toxicity : LC0 (Rat, male and female): > 2.5 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist
Remarks: no mortality

Acute dermal toxicity : LD50 (Mouse, male and female): > 3,500 mg/kg

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat, male and female): 490 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Product:

Assessment : Irritating to skin.
Result : Skin irritation
Remarks : May cause eye and skin irritation.

Components:

manganese carbonate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

manganese dinitrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

ethanediol:

Species : Rabbit
Result : No skin irritation

1,2-benzisothiazol-3(2H)-one:

Species : Rabbit
Exposure time : 72 h

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Result	:	Severe eye irritation
Remarks	:	May cause irreversible eye damage.

Components:

manganese carbonate:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

manganese dinitrate:

Species	:	Bovine cornea
Result	:	Irreversible effects on the eye

ethanediol:

Species	:	Rabbit
Result	:	No eye irritation

1,2-benzisothiazol-3(2H)-one:

Species	:	Bovine cornea
Method	:	OECD Test Guideline 437
Result	:	No eye irritation

Species	:	Rabbit
Method	:	EPA OPP 81-4
Result	:	Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks	:	Not expected to cause skin sensitisation
---------	---	--

Components:

manganese carbonate:

Test Type	:	Local lymph node test
-----------	---	-----------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.
Remarks : Based on data from similar materials

manganese dinitrate:

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.

ethanediol:

Test Type : Maximisation Test
Species : Guinea pig
Result : Does not cause skin sensitisation.

1,2-benzisothiazol-3(2H)-one:

Test Type : Maximisation Test
Species : Guinea pig
Method : OECD Test Guideline 406
Result : May cause sensitisation by skin contact.

Species : Guinea pig
Method : FIFRA 81.06
Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

manganese carbonate:

Genotoxicity in vitro : Test Type: reverse mutation assay
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (female)
Application Route: Oral

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3	Revision Date: 25.10.2023	SDS Number: 50001131	Date of last issue: - Date of first issue: 20.07.2018
----------------	------------------------------	-------------------------	--

Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

manganese dinitrate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: reverse mutation assay
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (female)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

ethanediol:

Genotoxicity in vitro : Test Type: reverse mutation assay
Method: OPPTS 870.5100
Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test
Species: Rat
Application Route: Oral
Result: negative

1,2-benzisothiazol-3(2H)-one:

Genotoxicity in vitro : Test Type: gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Method: OECD Test Guideline 473
Result: positive

Genotoxicity in vivo : Test Type: unscheduled DNA synthesis assay
Species: Rat (male)
Cell type: Liver cells
Application Route: Ingestion
Exposure time: 4 h
Method: OECD Test Guideline 486
Result: negative

Test Type: Micronucleus test
Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Based on available data, the classification criteria are not met.

Components:

manganese dinitrate:

Species : Rat, male
Application Route : Oral
Exposure time : 103 weeks
Dose : 60, 200, 615 mg/kg body weight
: 615 mg/kg body weight
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

ethanediol:

Species : Mouse
Application Route : Oral
Exposure time : 24 month(s)
Result : negative

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:

manganese carbonate:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: inhalation (dust/mist/fume)
Dose: 0, .005, .01, .02 mg/L

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3	Revision Date: 25.10.2023	SDS Number: 50001131	Date of last issue: - Date of first issue: 20.07.2018
----------------	------------------------------	-------------------------	--

General Toxicity - Parent: NOEL: 0.02 mg/l
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Species: Rat
Application Route: inhalation (dust/mist/fume)
Duration of Single Treatment: 15 d
General Toxicity Maternal: NOAEL: 0.025 mg/L
Developmental Toxicity: LOAEL: 0.025 mg/L
Embryo-foetal toxicity: NOAEL: 0.025 mg/L
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

manganese dinitrate:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: inhalation (dust/mist/fume)
Dose: 0, 5, 10, 20 µg/L
General Toxicity - Parent: NOEC: 0.020 mg/l
General Toxicity F1: NOAEC: 0.020 mg/l
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Species: Rat
Application Route: inhalation (dust/mist/fume)
General Toxicity Maternal: NOAEL: 0.005 mg/L
Embryo-foetal toxicity: NOAEL: 0.015 mg/L
Method: OECD Test Guideline 414

1,2-benzisothiazol-3(2H)-one:

Effects on fertility : Species: Rat, male
Application Route: Ingestion
General Toxicity - Parent: NOAEL: 18.5 mg/kg body weight
General Toxicity F1: NOAEL: 48 mg/kg body weight
Fertility: NOAEL: 112 mg/kg bw/day
Symptoms: No effects on reproduction parameters
Method: OPPTS 870.3800
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

STOT - single exposure

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Components:

manganese carbonate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

manganese dinitrate:

Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

ethanediol:

Exposure routes : Oral
Target Organs : Kidney
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

1,2-benzisothiazol-3(2H)-one:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

manganese carbonate:

Species : Rabbit, male
LOAEC : 0.0039 mg/l
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 4 - 6 weeks
Dose : 0, .001, .0039 mg/L
Remarks : Based on data from similar materials

manganese dinitrate:

Species : Rat, male
NOAEL : 1700 mg/kg bw/day
Application Route : Oral
Exposure time : 13weeks
Dose : 110 to 1700 mg/kg

Species : Rat, male and female
NOAEL : 20 µg/L air
Application Route : inhalation (dust/mist/fume)
Dose : 5, 10, 20 µg/L air
Method : OPPTS 870.3800

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

ethanediol:

Species	: Rat
NOAEL	: 150 mg/kg
Application Route	: Oral
Exposure time	: 12 months

Species	: Dog
NOAEL	: > 2,200 - < 4,400 mg/kg
Application Route	: Dermal
Exposure time	: 4 weeks
Method	: OECD Test Guideline 410

1,2-benzisothiazol-3(2H)-one:

Species	: Rat, male and female
NOAEL	: 15 mg/kg
Application Route	: Ingestion
Exposure time	: 28 d
Method	: OECD Test Guideline 407
Symptoms	: Irritation

Species	: Rat, male and female
NOAEL	: 69 mg/kg
Application Route	: Ingestion
Exposure time	: 90 d
Symptoms	: Irritation, Reduced body weight

Aspiration toxicity

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks	: No data available
---------	---------------------

SECTION 12: Ecological information

12.1 Toxicity

Components:

manganese carbonate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 3.17 mg/l Exposure time: 96 h Test Type: flow-through test Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 3.6 mg/l Exposure time: 48 h Method: OECD Test Guideline 202

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 2.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.69 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (activated sludge): 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: 0.55 mg/l
Exposure time: 65 d
Species: Salvelinus fontinalis (Brook trout)
Test Type: flow-through test
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1.3 mg/l
Exposure time: 8 d
Species: Ceriodaphnia dubia (water flea)
Test Type: static test
Remarks: Based on data from similar materials

manganese dinitrate:

Toxicity to fish : LC50 (Fish): 55.26 - 67.71 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : LOEC (Lemna minor (duckweed)): 64.94 mg/l
Exposure time: 7 d
Method: OECD Test Guideline 221
Remarks: Based on data from similar materials

EC10 (Lemna minor (duckweed)): 23.37 mg/l
Exposure time: 7 d
Method: OECD Test Guideline 221
Remarks: Based on data from similar materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version 1.3	Revision Date: 25.10.2023	SDS Number: 50001131	Date of last issue: - Date of first issue: 20.07.2018
----------------	------------------------------	-------------------------	--

Toxicity to microorganisms : NOEC (activated sludge): 560 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : see user defined free text: 2.9 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.02 mg/l
Exposure time: 20 d
Species: Daphnia magna (Water flea)
Test Type: static test

M-Factor (Chronic aquatic toxicity) : 1

sodium acrylate:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

ethanediol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 72,860 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : IC50 (Pseudokirchneriella subcapitata (green algae)): 10,940 mg/l
Exposure time: 96 h

Toxicity to microorganisms : (activated sludge): > 1,995 mg/l
Exposure time: 30 min
Method: ISO 8192

Toxicity to fish (Chronic toxicity) : 1,500 mg/l
Exposure time: 28 d
Species: Menidia peninsulae (tidewater silverside)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : 33,911 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 16.7

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Oncorhynchus mykiss (rainbow trout)): 2.15 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.9 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.070 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.04 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : EC50 (activated sludge): 24 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

EC50 (activated sludge): 12.8 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

12.2 Persistence and degradability

Components:

ethanediol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301A

1,2-benzisothiazol-3(2H)-one:

Biodegradability : Result: rapidly biodegradable
Method: OECD Test Guideline 301C

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

12.3 Bioaccumulative potential

Components:

ethanediol:

Partition coefficient: n-octanol/water : log Pow: -1.36

1,2-benzisothiazol-3(2H)-one:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Exposure time: 56 d
Bioconcentration factor (BCF): 6.62
Method: OECD Test Guideline 305
Remarks: This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Partition coefficient: n-octanol/water : log Pow: 0.7 (20 °C)
pH: 7

log Pow: 0.99 (20 °C)
pH: 5

12.4 Mobility in soil

Components:

1,2-benzisothiazol-3(2H)-one:

Distribution among environmental compartments : Koc: 9.33 ml/g, log Koc: 0.97
Method: OECD Test Guideline 121
Remarks: Highly mobile in soils

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1760
ADR	: UN 1760
RID	: UN 1760
IMDG	: UN 1760
IATA	: UN 1760

14.2 UN proper shipping name

ADN	: CORROSIVE LIQUID, N.O.S. (manganese dinitrate)
ADR	: CORROSIVE LIQUID, N.O.S. (manganese dinitrate)
RID	: CORROSIVE LIQUID, N.O.S. (manganese dinitrate)
IMDG	: CORROSIVE LIQUID, N.O.S. (manganese dinitrate)
IATA	: Corrosive liquid, n.o.s. (manganese dinitrate)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 8	
ADR	: 8	
RID	: 8	

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

IMDG : 8

IATA : 8

14.4 Packing group

ADN

Packing group : III
Classification Code : C9
Hazard Identification Number : 80
Labels : 8

ADR

Packing group : III
Classification Code : C9
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

RID

Packing group : III
Classification Code : C9
Hazard Identification Number : 80
Labels : 8

IMDG

Packing group : III
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo aircraft) : 856
Packing instruction (LQ) : Y841
Packing group : III
Labels : Corrosive

IATA (Passenger)

Packing instruction (passenger aircraft) : 852
Packing instruction (LQ) : Y841
Packing group : III
Labels : Corrosive

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3 ethanediol (Number on list 3)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	P8	OXIDIZING LIQUIDS AND SOLIDS
	E2	ENVIRONMENTAL HAZARDS
	E2	
	E1	

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

The components of this product are reported in the following inventories:

TCSI	:	Not in compliance with the inventory
TSCA	:	Product contains substance(s) not listed on TSCA inventory.
AIIC	:	Not in compliance with the inventory
DSL	:	This product contains the following components that are not on the Canadian DSL nor NDSL. JETT 200 CLASSIC 500G/L
ENCS	:	Not in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory
NZIoC	:	Not in compliance with the inventory
TECI	:	Not in compliance with the inventory

15.2 Chemical safety assessment

A chemical safety assessment is not required for this product (mixture).

SECTION 16: Other information

Full text of H-Statements

H272	:	May intensify fire; oxidizer.
H302	:	Harmful if swallowed.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H373	:	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Ox. Sol.	: Oxidizing solids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MANGANESE 400

Version	Revision Date:	SDS Number:	Date of last issue: -
1.3	25.10.2023	50001131	Date of first issue: 20.07.2018

Classification of the mixture:

Skin Corr. 1C

H314

STOT RE 2

H373

Classification procedure:

Calculation method

Calculation method

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

Prepared by

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.

© 2021-2023 FMC Corporation. All Rights Reserved.

GB / 6N