MULTIPLE PRO Spektrum Universal



Version 1.4 Revision Date: 08.04.2025

SDS Number: 50001215

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name MULTIPLE PRO

Spektrum Universal

Other means of identification

Product code 50001215

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

stance/Mixture

: A fertilizer for use in agriculture

Recommended restrictions

on use

Use as recommended by the label.

1.3 Details of the supplier of the safety data sheet

Supplier Address FMC Ukraine LLC

8 Illinska Street 04070 Kyiv Ukraine

Telephone: Website: fmc.com.ua

E-mail address: SDS-Info@fmc.com, info@fmc.com.ua.

1.4 Emergency telephone number

For leak, fire, spill or accident emergencies, call:

Ukraine: 380-947101374 (CHEMTREC)

Medical emergency:

All other countries: +1 651 / 632-6793 (Collect)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.

Short-term (acute) aquatic hazard, Cate-

gory 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Cat- H410: Very toxic to aquatic life with long lasting

MULTIPLE PRO Spektrum Universal



Version 1.4 Revision Date: 08.04.2025

SDS Number: 50001215

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

egory 1

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor. P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

dicopper oxide

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

MULTIPLE PRO Spektrum Universal



Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
manganese carbonate	598-62-9 209-942-9		>= 30 - < 50
dicopper oxide	1317-39-1 215-270-7 029-002-00-X	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 3 - < 10
ethanediol	107-21-1 203-473-3 603-027-00-1	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 2,5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Avoid inhalation, ingestion and contact with skin and eyes. If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Take off all contaminated clothing immediately.

Wash contaminated clothing before re-use.

Wash off immediately with plenty of water for at least 15

minutes.

Get medical attention if irritation develops and persists.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

MULTIPLE PRO Spektrum Universal



Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing

media

Do not spread spilled material with high-pressure water

streams.

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Fire may produce irritating, corrosive and/or toxic gases.

Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Firefighters should wear protective clothing and self-contained

breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Never return spills in original containers for re-use.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

MULTIPLE PRO Spektrum Universal



Version 1.4

Revision Date: 08.04.2025

SDS Number: 50001215

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

equipment may intervene.

For disposal considerations see section 13.

6.2 Environmental precautions

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. To maintain product quality, DO NOT ALLOW TO FREEZE.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological

safety standards.





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Recommended storage tem- : > 5 °C

perature

Further information on stor-

age stability

No decomposition if stored and applied as directed.

Do not freeze.

7.3 Specific end use(s)

Specific use(s) : Fertilizers

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
manganese car-	598-62-9	TWA (inhalable	0,2 mg/m3	2017/164/EU
bonate		fraction)	(Manganese)	
	Further information: Indicative			
		TWA (Respirable	0,05 mg/m3	2017/164/EU
		fraction)	(Manganese)	
	Further information: Indicative			
ethanediol	107-21-1	MAC (aerosol	5 mg/m3	UA OEL
		and vapour)		
	Further information: Danger class 3			
		TWA	20 ppm	2000/39/EC
			52 mg/m3	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			ce through the
		STEL	40 ppm	2000/39/EC
			104 mg/m3	
	Further information: Identifies the possibility of significant uptake through the			
	skin, Indicative			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
dicopper oxide	Consumers	Oral	Long-term systemic effects	0,041 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	0,082 mg/kg bw/day
manganese car- bonate	Workers	Inhalation	Long-term systemic effects	0,2 mg/m3
	Workers	Dermal	Long-term systemic effects	0,004 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,043 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0021 mg/kg bw/day





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

ethanediol	Workers	Inhalation	Long-term local effects	35 mg/m3
	Workers	Dermal	Long-term systemic effects	106 mg/kg
	Consumers	Inhalation	Long-term local effects	7 mg/m3
	Consumers	Dermal	Long-term systemic effects	53 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
dicopper oxide	Fresh water	0,0078 mg/l
	Marine water	0,0052 mg/l
	Sewage treatment plant	0,230 mg/l
	Fresh water sediment	87 mg/kg dry
		weight (d.w.)
	Marine sediment	676 mg/kg dry
		weight (d.w.)
	Soil	65 mg/kg dry
		weight (d.w.)
manganese carbonate	Fresh water	0,0084 mg/l
	Intermittent use/release	0,011 mg/l
	Marine water	840 ng/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	8,18 mg/kg dry
		weight (d.w.)
	Marine sediment	0,810 mg/kg dry
		weight (d.w.)
	Soil	8,15 mg/kg dry
		weight (d.w.)
ethanediol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	37 mg/kg dry
		weight (d.w.)
	Marine sediment	3,7 mg/kg dry
		weight (d.w.)
	Soil	1,53 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

Protective measures : Plan first aid action before beginning work with this product.

Always have on hand a first-aid kit, together with proper in-

structions.

Ensure that eye flushing systems and safety showers are

located close to the working place. Wear suitable protective equipment.

In the context of professional plant protection use as recommended, the end user must refer to the label and the instruc-

tions for use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Form : suspension
Colour : red brown
Odour : Faint odour
Odour Threshold : No data available

pH : 8 - 11

Concentration: 100 %

Melting point/freezing point

Initial boiling point and boiling

No data available

range No data available
Flash point : No data available
Upper explosion limit / Upper : No data available

flammability limit

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available Relative vapour density : No data available Relative density : 1,68 - 1,72

Density : No data available
Bulk density : No data available

Solubility(ies)

Water solubility : dispersible Solubility in other solvents : No data available

Partition coefficient: n- : No data available





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.04.2025

 1.4
 08.04.2025
 50001215
 Date of first issue: 18.09.2020

octanol/water

Auto-ignition temperature : No data available Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 1.800 - 4.500 mPa,s Viscosity, kinematic : No data available

Explosive properties

No data available

Oxidizing properties : Non-oxidizing

9.2 Other information

Particle size : No data available Particle Size Distribution : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : None reasonably foreseeable. No decomposition if stored and

applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Avoid extreme temperatures

Direct sources of heat. Protect from frost.

10.5 Incompatible materials

Materials to avoid : Avoid strong acids, bases, and oxidizers

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

MULTIPLE PRO Spektrum Universal



Version 1.4

Revision Date: 08.04.2025

SDS Number: 50001215

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

Method: Calculation method

Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

manganese carbonate:

Acute oral toxicity : LD0 (Rat, female): > 2.000 mg/kg

Method: OECD Test Guideline 420

Remarks: no mortality

Acute inhalation toxicity : LC0 (Rat, male and female): > 5,35 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: no mortality

Based on data from similar materials

dicopper oxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 (Rat, male and female): 1.340 mg/kg

Symptoms: Fatality, Gastrointestinal tract damage

Acute inhalation toxicity : Acute toxicity estimate: 3,34 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LC50 (Rat, male and female): 3,34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Symptoms: respiratory depression, Bruising and haemorrhage

formation, Fatality, ataxia, lethargy

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg

Method: OECD Test Guideline 402

Remarks: no mortality

ethanediol:

Acute inhalation toxicity : LC0 (Rat, male and female): > 2,5 mg/l

Exposure time: 6 h

Test atmosphere: dust/mist Remarks: no mortality





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Acute dermal toxicity : LD50 (Mouse, male and female): > 3.500 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

manganese carbonate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

dicopper oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

ethanediol:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : No data available

Components:

manganese carbonate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

dicopper oxide:

Species : Rabbit

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

ethanediol:

Species : Rabbit

Result : No eye irritation

MULTIPLE PRO Spektrum Universal



Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

manganese carbonate:

Test Type : Local lymph node test

Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.
Remarks : Based on data from similar materials

dicopper oxide:

Test Type : Maximisation Test

Exposure routes : Intradermal Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

ethanediol:

Test Type : Maximisation Test

Species : Guinea pig

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

manganese carbonate:

Genotoxicity in vitro : Test Type: reverse mutation assay

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (female)
Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

dicopper oxide:

Genotoxicity in vitro : Test Type: reverse mutation assay

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Application Route: Oral

Result: negative

Test Type: unscheduled DNA synthesis assay

Species: Rat (male) Application Route: Oral

Result: negative

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

ethanediol:

Genotoxicity in vitro : Test Type: reverse mutation assay

Method: OPPTS 870.5100

Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test

Species: Rat

Application Route: Oral Result: negative

Carcinogenicity

Based on available data, the classification criteria are not met.

Components:

ethanediol:

Species : Mouse Application Route : Oral

Exposure time : 24 month(s)
Result : negative

MULTIPLE PRO Spektrum Universal



Version 1.4

Revision Date: 08.04.2025

SDS Number: 50001215

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:

manganese carbonate:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: inhalation (dust/mist/fume)

Dose: 0, .005, .01, .02 mg/L

General Toxicity - Parent: NOEL: 0,02 mg/l

Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Species: Rat

Application Route: inhalation (dust/mist/fume)

Duration of Single Treatment: 15 d

General Toxicity Maternal: NOAEL: 0,025 mg/L Developmental Toxicity: LOAEL: 0,025 mg/L Embryo-foetal toxicity: NOAEL: 0,025 mg/L

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

dicopper oxide:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 1.53, 7.7,15.2, 23.6mg/kg/bwd

General Toxicity - Parent: LOAEL: 23,6 mg/kg bw/day General Toxicity F1: LOAEL: 23,6 mg/kg bw/day General Toxicity F2: LOAEL: 23,6 mg/kg bw/day

Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Species: Rabbit, female Application Route: Oral

Dose: 0, 6, 9, 18 mg Cu/mL Duration of Single Treatment: 28 d

General Toxicity Maternal: LOAEL: 9 mg/kg bw/day Developmental Toxicity: LOAEL: 9 mg/kg bw/day

Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

: Weight of evidence does not support classification for repro-

ductive toxicity





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

STOT - single exposure

Based on available data, the classification criteria are not met.

Components:

manganese carbonate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Components:

dicopper oxide:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

ethanediol:

Exposure routes : Oral Target Organs : Kidney

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Repeated dose toxicity

Components:

manganese carbonate:

Species : Rabbit, male
LOAEC : 0,0039 mg/l
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 4 - 6 weeks

Dose : 0, .001, .0039 mg/L

Remarks : Based on data from similar materials

dicopper oxide:

Species : Mouse, male and female

NOAEL : 1000 ppm LOAEL : 2000 ppm Application Route : Oral Exposure time : 92d

Dose : 0,1000,2000,4000,8000,16000 ppm

Method : Regulation (EC) No. 440/2008, Annex, B.26

Species : Rat, male and female

NOAEL : 1000 ppm LOAEL : 2000 ppm Application Route : Oral Exposure time : 92d





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Dose : 0, 500, 1000, 2000, 4000,8000 ppm

Method : Regulation (EC) No. 440/2008, Annex, B.26

Species : Rat, male and female

NOAEL : > 0,002 mg/l

Application Route : inhalation (dust/mist/fume)

Test atmosphere : dust/mist Exposure time : 28d

Dose : 0.2, 0.4, 0.8, 2.0 mg/m3
Method : OECD Test Guideline 412

ethanediol:

Species : Rat
NOAEL : 150 mg/kg
Application Route : Oral
Exposure time : 12 Months

Species : Dog

NOAEL : > 2.200 - < 4.400 mg/kg

Application Route : Dermal Exposure time : 4 Weeks

Method : OECD Test Guideline 410

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

manganese carbonate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3,17 mg/l

Exposure time: 96 h

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 3,6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 2,2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,69

MULTIPLE PRO Spektrum Universal



Version 1.4

Revision Date: 08.04.2025

SDS Number: 50001215

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms

NOEC (activated sludge): 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

EC50 (activated sludge): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,55 mg/l Exposure time: 65 d

Species: Salvelinus fontinalis (Brook trout)

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 1,3 mg/l Exposure time: 8 d

Species: Ceriodaphnia dubia (water flea)

Test Type: static test

Remarks: Based on data from similar materials

dicopper oxide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0,0384 mg/l

Exposure time: 96 h

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 0,0098 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Raphidocelis subcapitata (freshwater green alga)):

0,032 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Phaeodactylum tricornutum): 0,0029 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

100

Toxicity to microorganisms : NOEC (activated sludge): 0,23 - 0,45 mg/l

Exposure time: 30 d

Test Type: Respiration inhibition

MULTIPLE PRO Spektrum Universal



Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,0022 mg/l

Exposure time: 60 d

Species: Oncorhynchus mykiss (rainbow trout)

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,004 mg/l Exposure time: 7 d

Species: Ceriodaphnia dubia (water flea)

Test Type: semi-static test

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

10

Toxicity to terrestrial organ-

isms

LD50: 1.400 mg/kg Exposure time: 14 d

Species: Colinus virginianus (Bobwhite quail)

Ecotoxicology Assessment

Acute aquatic toxicity Very toxic to aquatic life.

Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

ethanediol:

LC50 (Pimephales promelas (fathead minnow)): > 72.860 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

IC50 (Pseudokirchneriella subcapitata (green algae)): 10.940

ma/l

Exposure time: 96 h

Toxicity to microorganisms (activated sludge): > 1.995 mg/l

> Exposure time: 30 min Method: ISO 8192

Toxicity to fish (Chronic tox-

icity)

1.500 mg/l

Exposure time: 28 d

Species: Menidia peninsulae (tidewater silverside)

Toxicity to daphnia and other :

33.911 mg/l

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Species: Daphnia magna (Water flea)

MULTIPLE PRO Spektrum Universal



Version Revision Date: SDS Number: Dat 1.4 08.04.2025 50001215 Dat

Date of last issue: 04.04.2025 Date of first issue: 18.09.2020

12.2 Persistence and degradability

Components:

ethanediol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301A

12.3 Bioaccumulative potential

Components:

dicopper oxide:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

ethanediol:

Partition coefficient: n-

octanol/water

log Pow: -1,36

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

 ADR
 : UN 3082

 IMDG
 : UN 3082

 IATA
 : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Dicopper oxide)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Dicopper oxide)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(Dicopper oxide)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

IMDG

Packing group : III Labels : 9

EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passen- : 964

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : Not in compliance with the inventory





Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TECI: Not in compliance with the inventory

15.2 Chemical safety assessment

A chemical safety assessment is not required for this product (mixture).

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

STOT RE : Specific target organ toxicity - repeated exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

UA OEL : Ukraine OEL - Order on Approval of the Hygienic Regulations

of Chemicals in the Air of the Working Zone

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

UA OEL / MAC : Maximum allowable concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International

MULTIPLE PRO Spektrum Universal



Version Revision Date: SDS Number: Date of last issue: 04.04.2025 1.4 08.04.2025 50001215 Date of first issue: 18.09.2020

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

Classification of the mixture: Classification procedure:

Eye Dam. 1 H318 Calculation method
Aquatic Acute 1 H400 Calculation method
Aquatic Chronic 1 H410 Calculation method

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

Prepared by

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.
© 2021-2025 FMC Corporation. All Rights Reserved.

UA / 6N