according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SHIBAOKE 250 EC

Other means of identification : Prochloraz 250 g/L EC

### Recommended use of the chemical and restrictions on use

Recommended use : Can be used as fungicide only.

Restrictions on use : Use as recommended by the label.

#### Manufacturer or supplier's details

Company : FMC (Suzhou) Crop care co., ltd

Address : 99 Jiepu Road, Suzhou Industrial Park, Jiang Su, China

215126 China

Telephone : 0512-62863988

Telefax : 0512-62863900

E-mail address : SDS-Info@fmc.com

Emergency telephone : For leak, fire, spill or accident emergencies, call:

0086-0532 8388 9090 (National Registration Center for Chemi-

cals)

Medical emergency: 86 532 8388 9090

#### 2. HAZARDS IDENTIFICATION

# **Emergency Overview**

Appearance : liquid

Color : Light yellow to yellow

Odor : aromatic

Combustible liquid. Harmful if swallowed or if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### **GHS Classification**

Flammable liquids : Category 4

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2A

Skin sensitization : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity - :

single exposure

Category 3 (Narcotic effects)

Aspiration hazard : Category 1

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 2

### **GHS** label elements

Hazard pictograms







Signal Word : DANGER

Hazard Statements : H227 Combustible liquid.

H302 + H332 Harmful if swallowed or if inhaled. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Physical and chemical hazards

Combustible liquid.

#### **Health hazards**

Harmful if swallowed. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

### **Environmental hazards**

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### Other hazards which do not result in classification

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
prochloraz (ISO)	67747-09-5	>= 20 -< 30
Solvent naphtha (petroleum), heavy arom.;	64742-94-5	>= 50 -< 70
Kerosine — unspecified		
Benzenesulfonic acid, mono-C11-13-branched	68953-96-8	>= 3 -< 10
alkyl derivs., calcium salts		
2-methylpropan-1-ol	78-83-1	>= 1 -< 3

#### 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Notes to physician : Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry chemical

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Carbon dioxide (CO2)

Water spray Regular foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Fire may produce irritating, corrosive and/or toxic gases.

Carbon oxides

Nitrogen oxides (NOx) Hydrogen cyanide Chlorine compounds

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for fire-fighters

Firefighters should wear protective clothing and self-contained

breathing apparatus.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Evacuate personnel to safe areas.

Use personal protective equipment. If it can be safely done, stop the leak.

Do not touch or walk through the spilled material.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

### 7. HANDLING AND STORAGE

### Handling

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of

ignition.

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Avoidance of contact : Strong acids

Strong bases

Strong oxidizing agents

**Storage** 

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
2-methylpropan-1-ol	78-83-1	TWA	50 ppm	ACGIH

## Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable per-

sonal respiratory protection and protective suit.

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Form : liquid

Color : Light yellow to yellow

Odor : aromatic

pH : 5.5 - 8.5

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 62.5 °C

Method: ASTM D 93

Flammability (liquids) : Sustains combustion

Self-ignition : > 480 °C

Density : 0.98 g/cm3 (22.8 °C)

Partition coefficient: n-

octanol/water

: Not applicable

Viscosity

Viscosity, kinematic : 17.3 mm2/s (25 °C)

14.3 mm2/s (45 °C)

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Explosive properties : Not explosive

Oxidizing properties : Non-oxidizing

#### 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents

Hazardous decomposition

products

: Stable under recommended storage conditions.

## 11. TOXICOLOGICAL INFORMATION

#### **Acute toxicity**

Harmful if swallowed or if inhaled.

## **Product:**

Acute oral toxicity : LD50 (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.12 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

#### **Components:**

prochloraz (ISO):

Acute oral toxicity : LD50 (Rat, female): ca. 1,010 mg/kg

Method: OECD Test Guideline 425 Symptoms: Breathing difficulties

GLP: yes

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Acute inhalation toxicity : LC50 (Rat, male and female): > 2.16 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403 Symptoms: Breathing difficulties

GLP: yes

Remarks: no mortality

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Symptoms: Irritation

GLP: yes

Assessment: The component/mixture is minimally toxic after

single contact with skin. Remarks: no mortality

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Acute oral toxicity : LD0 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 401

Remarks: no mortality

Acute dermal toxicity : LD50 (Rat, male and female): > 1,000 - 1,600 mg/kg

Method: OECD Test Guideline 402

2-methylpropan-1-ol:

Acute oral toxicity : LD50 (Rat): 3,350 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 18.18 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): 2,460 mg/kg

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

#### Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : May cause skin irritation and/or dermatitis.

**Components:** 

prochloraz (ISO):

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rabbit Result : Skin irritation

2-methylpropan-1-ol:

Species : Rabbit Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Species : Rabbit Result : Eye irritation

Remarks : May cause irreversible eye damage.

**Components:** 

prochloraz (ISO):

Species : Rabbit

Result : Slight or no eye irritation
Assessment : Not classified as irritant
Method : OECD Test Guideline 405

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

GLP : yes

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rabbit

Result : Irreversible effects on the eye

2-methylpropan-1-ol:

Species : Rabbit

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

**Product:** 

Test Type : Local lymph node assay (LLNA)

Species : mice

Method : OECD Test Guideline 429

Result : May cause sensitization by skin contact.

Remarks : Causes sensitization.

**Components:** 

prochloraz (ISO):

Test Type : Local lymph node assay (LLNA)

Species : mice

Assessment : Not a skin sensitizer.

Method : OECD Test Guideline 429

Result : Not a skin sensitizer.

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Test Type : Buehler Test Species : Guinea pig

Result : Does not cause skin sensitization.
Remarks : Based on data from similar materials

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Test Type : Maximization Test

Species : Guinea pig

Method : OECD Test Guideline 406

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Result : Does not cause skin sensitization.

2-methylpropan-1-ol:

Routes of exposure : Skin contact

Result : Not a skin sensitizer.

Germ cell mutagenicity

Not classified due to lack of data.

**Components:** 

prochloraz (ISO):

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative GLP: yes

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: mice (male and female)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Genotoxicity in vitro : Test Type: reverse mutation assay

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: sister chromatid exchange assay

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Test Type: reverse mutation assay

Method: Mutagenicity (Salmonella typhimurium - reverse mu-

tation assay)

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male and female)

Application Route: Oral

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

2-methylpropan-1-ol:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Result: negative

Carcinogenicity

Suspected of causing cancer.

**Components:** 

prochloraz (ISO):

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Mouse
Application Route : Dermal
Exposure time : 104 weeks
Result : negative

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified due to lack of data.

**Components:** 

prochloraz (ISO):

Reproductive toxicity - As-

sessment

No toxicity to reproduction

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Effects on fertility : Test Type: Fertility

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 415

Result: negative

Remarks: Based on data from similar materials

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Effects on fetal development : Test Type: reproductive and developmental toxicity study

Species: Rat

Application Route: Oral

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Effects on fertility : Test Type: Three-generation study

Species: Rat, male and female

Application Route: Oral Dose: 14, 70, 350 mg/kg bw d

General Toxicity Parent: NOAEL: 350 mg/kg body weight

General Toxicity F1: NOAEL: 350 mg/kg bw/day General Toxicity F2: NOAEL: 350 mg/kg bw/day

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: reproductive and developmental toxicity study

Species: Rat

Application Route: Oral

Dose: 0.2, 2.0, 300 and 600 mg/kg Duration of Single Treatment: 20 d

General Toxicity Maternal: LOAEL: 600 mg/kg body weight

Teratogenicity: LOAEL: 600 mg/kg bw/day

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

2-methylpropan-1-ol:

Effects on fertility : Species: Rat

Application Route: Inhalation

Fertility: NOAEC Mating/Fertility: 7.5 mg/l

STOT-single exposure

May cause drowsiness or dizziness.

**Components:** 

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Assessment : May cause drowsiness or dizziness.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

2-methylpropan-1-ol:

Assessment : May cause respiratory irritation.

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

May cause drowsiness or dizziness.

#### STOT-repeated exposure

Not classified due to lack of data.

#### Repeated dose toxicity

### **Components:**

### prochloraz (ISO):

Species : Rat, male and female LOAEL : 6 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Dose : 6, 25, 100 mg/kg bw/day Symptoms : increased liver weight

Species : Mouse, male and female

LOAEL : 25 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Dose : 6, 25, 100, 400 mg/kg bw/day

Symptoms : increased liver weight

Species : Dog, male and female

NOAEL : 2.5 mg/kg LOAEL : 7 mg/kg bw/day

Application Route : Oral Exposure time : 90 d

Dose : 1, 2.5, 7, 20 mg/kg bw/day Symptoms : increased liver weight

## Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rat, male and female

NOAEL : 750 mg/kg
Application Route : Oral - gavage
Exposure time : 90 day

Remarks : Based on data from similar materials

Species : Rat, male and female

NOAEL : 1 mg/l LOAEL : 0.5 mg/l

Application Route : inhalation (vapor)

Exposure time : 90 day

Symptoms : Alpha-2u-globulin nephropathy

## Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Species : Rat, male and female NOAEL : 40 mg/kg bw/day LOAEL : 115 mg/kg bw/day

Application Route : Oral - feed Exposure time : 6 months

Dose : 40, 115, 340, 1030 mg/kg bw d

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Remarks : Based on data from similar materials

2-methylpropan-1-ol:

Species : Rat

: 1450 mg/kg

Application Route : Oral

Species : Rat

: 7.5 mg/l

Application Route : Inhalation

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### **Product:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### **Components:**

#### prochloraz (ISO):

The substance does not have properties associated with aspiration hazard potential.

### Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Further information**

**Product:** 

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

### **Components:**

prochloraz (ISO):

Remarks : Ingestion may cause gastrointestinal irritation, nausea, vomit-

ing and diarrhea.

Contact may cause slight irritation.

#### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### Components:

## prochloraz (ISO):

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 1.2 mg/l

Exposure time: 96 h Test Type: static test

GLP: yes

LC50 (Lepomis macrochirus (Bluegill sunfish)): 2.2 mg/l

Exposure time: 96 h Test Type: static test

GLP: yes

LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l

Exposure time: 96 h Test Type: static test

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.3 mg/l

Exposure time: 48 h Test Type: static test

EC50 (Crassostrea virginica (atlantic oyster)): 0.69 - 1.3 mg/l

Exposure time: 96 h

Test Type: flow-through test

GLP: yes

LC50 (Mysidopsis bahia (opossum shrimp)): 0.86 mg/l

Exposure time: 48 h

GLP: yes

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 0.032

mg/l

Exposure time: 72 h

ErC50 (Lemna gibba (duckweed)): 0.109 mg/l

Exposure time: 7 d

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.0485 mg/l

Exposure time: 36 d

NOEC (Salmo gairdneri): 0.18 mg/l

End point: mortality Exposure time: 28 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0222 mg/l

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

: 1

Toxicity to terrestrial organ-

isms

LD50 (Apis mellifera (bees)): 51 µg/bee

End point: Acute contact toxicity

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

LD50 (Apis mellifera (bees)): 61 µg/bee

End point: Acute oral toxicity

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: water accommodated fractions (WAF)

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: water accommodated fractions (WAF)

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: water accommodated fractions (WAF)

Toxicity to microorganisms : LL50 (Tetrahymena pyriformis): 677.9 mg/l

Exposure time: 72 h

Test Type: Growth inhibition

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 31.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 62 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 29 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.5

mq/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.23 mg/l

Exposure time: 72 d

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1.18 mg/l

Exposure time: 21 d

Test Type: flow-through test

Remarks: Based on data from similar materials

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Toxicity to microorganisms : EC50 (activated sludge): 550 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to soil dwelling or-

ganisms

NOEC (Eisenia fetida (earthworms)): 250 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 207

Remarks: Based on data from similar materials

LC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg

Exposure time: 14 d

Method: OECD Test Guideline 207

Remarks: Based on data from similar materials

Plant toxicity : EC50: 167 mg/kg

Exposure time: 21 d

Species: Sorghum bicolor (sorghum)

80 mg/kg

Exposure time: 14 d

Species: Avena sativa (oats)

Toxicity to terrestrial organ-

isms

EC10 (Hypoaspis aculeifer): 82 mg/kg

Exposure time: 21 d

Remarks: Information given is based on data obtained from

similar substances.

2-methylpropan-1-ol:

Toxicity to fish : LC50 : 1,430 mg/l

Exposure time: 4 d

Toxicity to daphnia and other :

aquatic invertebrates

EC50: 1,100 mg/l

Exposure time: 48 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 20 mg/l

Exposure time: 21 d

Toxicity to microorganisms : E

EC50 (Anabaena flos-aquae (cyanobacterium)): 593 - 1,799

mg/l

Exposure time: 72 h

IC50 (Natural microorganism): 1,000 mg/l

Exposure time: 16 h

Persistence and degradability

**Components:** 

prochloraz (ISO):

Biodegradability : Result: Not readily biodegradable.

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 58.6 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Biodegradability : Inoculum: activated sludge, non-adapted

Result: Not readily biodegradable.

Biodegradation: 2.9 % Exposure time: 28 d

Method: OECD Test Guideline 301E

Result: Inherently biodegradable. Biodegradation: > 35 - 45 %

Exposure time: 10 d

2-methylpropan-1-ol:

Biodegradability : Result: Readily biodegradable.

**Bioaccumulative potential** 

**Components:** 

prochloraz (ISO):

Bioaccumulation : Remarks: See section 9 for octanol-water partition coefficient.

The product may be accumulated in organisms.

Partition coefficient: n-

octanol/water

log Pow: 4.12 (25 °C)

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Partition coefficient: n- : log Pow: 1.99 - 18.02 octanol/water : Method: QSAR

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts:

Bioaccumulation : Bioconcentration factor (BCF): 3.16

Method: QSAR

Partition coefficient: n-

octanol/water

: log Pow: 4.595 (20 °C)

2-methylpropan-1-ol:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <=

4).

Partition coefficient: n-

octanol/water

Pow: 10 (25 °C)

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

### Mobility in soil

## **Components:**

prochloraz (ISO):

Distribution among environ-

mental compartments

Remarks: immobile

### Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

#### 13. DISPOSAL CONSIDERATIONS

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### 14. TRANSPORT INFORMATION

### International Regulations

**UNRTDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(prochloraz)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(prochloraz)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

aircraft)

Packing instruction (passen- : 964

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(prochloraz)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

GB 6944/12268

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(prochloraz)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : yes

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 15. REGULATORY INFORMATION

## National regulatory information

### Law on the Prevention and Control of Occupational Diseases

### **Yangtze River Protection Law**

This product does not contain any dangerous chemicals prohibited for inland river transport.

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

according to GB/T 16483 and GB/T 17519



# SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

N-PROPYL-N-[2-(2,4,6-

TRICHLOROPHENOXY)ETHYL]IMIDAZOLE-1-

**CARBOXAMIDE** 

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

TECI: Not in compliance with the inventory

#### 16. OTHER INFORMATION

Revision Date : 2024/06/14

Date format : yyyy/mm/dd

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No

according to GB/T 16483 and GB/T 17519



## SHIBAOKE 250 EC

Version Revision Date: SDS Number: Date of last issue: -

3.1 2024/06/14 50000588 Date of first issue: 2018/06/05

1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### **Disclaimer**

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

CN / EN