

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Other means of identification

Product code 50000965

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Herbicide

Recommended restrictions on use : Use as recommended by the label.

1.3 Manufacturer or supplier's details

Supplier Address FMC Ukraine LLC
8 Illinska Street
04070 Kyiv
Ukraine

Telephone: +380443648258, Website: fmc.com.ua
E-mail address: SDS-Info@fmc.com, info@fmc.com.ua .

1.4 Emergency telephone number

For leak, fire, spill or accident emergencies, call:
Ukraine: 380-947101374 (CHEMTREC)

Medical emergency:
All other countries: +1 651 / 632-6793 (Collect)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Specific target organ toxicity - repeated exposure, Category 2 H373: May cause damage to organs through prolonged or repeated exposure.

Short-term (acute) aquatic hazard, Category 1 H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Category 1 H410: Very toxic to aquatic life with long lasting effects.

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Category 1

effects.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal word : Warning

Hazard statements : H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.

Response:
P314 Get medical advice/ attention if you feel unwell.
P391 Collect spillage.

Disposal:
P501 Dispose of contents/container as hazardous waste in accordance with local regulations.

Hazardous components which must be listed on the label:
tribenuron-methyl (ISO)

Additional Labelling

EUH208 Contains tribenuron-methyl (ISO). May produce an allergic reaction.

EUH401 To avoid risks to human health and the environment, comply with the instructions for use.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version 1.0 Revision Date: 23.09.2024 SDS Number: 50000965 Date of last issue: -
Date of first issue: 23.09.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
tribenuron-methyl (ISO)	101200-48-0 401-190-1 607-177-00-9	Skin Sens. 1; H317 STOT RE 2; H373 (Thyroid, Nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 70 - < 90
kaolin	1332-58-7 310-194-1		>= 1 - < 10
Alkyl-naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	68425-94-5	Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 2,5 - < 10
Lignosulfonic acid, ethoxylated, sodium salts	68611-14-3	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system)	>= 3 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
Show this safety data sheet to the doctor in attendance.
Move out of dangerous area.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
Avoid inhalation, ingestion and contact with skin and eyes.
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- If inhaled : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
If experiencing any discomfort, immediately remove from exposure. Light cases: Keep person under surveillance. Get medical attention immediately if symptoms develop. Serious cases: Get medical attention immediately or call for an ambulance.

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

lance.

- | | | |
|-------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In case of skin contact | : | If on clothes, remove clothes.
If on skin, rinse well with water.
Wash off with soap and plenty of water.
Get medical attention immediately if irritation develops and persists. |
| In case of eye contact | : | If eye irritation persists, consult a specialist.
Keep eye wide open while rinsing.
Protect unharmed eye.
Remove contact lenses.
Flush eyes with water as a precaution. |
| If swallowed | : | Take victim immediately to hospital.
If symptoms persist, call a physician.
Never give anything by mouth to an unconscious person.
Do not give milk or alcoholic beverages.
Keep respiratory tract clear.
Do not induce vomiting without medical advice. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|--------------------------------------------------------------------|
| Risks | : | May cause damage to organs through prolonged or repeated exposure. |
|-------|---|--------------------------------------------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- | | | |
|--------------------------------|---|------------------------------------------------------------------|
| Suitable extinguishing media | : | Dry chemical, CO2, water spray or regular foam. |
| Unsuitable extinguishing media | : | Do not spread spilled material with high-pressure water streams. |

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|------------------------------------------------------------------------------------------------------------------------|
| Specific hazards during fire-fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | Fire may produce irritating, corrosive and/or toxic gases.
Nitrogen oxides (NOx)
Sulphur oxides
Carbon oxides |

5.3 Advice for firefighters

- | | | |
|-----------------------------------------------|---|--------------------------------------------------------------------------------------|
| Special protective equipment for firefighters | : | Firefighters should wear protective clothing and self-contained breathing apparatus. |
|-----------------------------------------------|---|--------------------------------------------------------------------------------------|

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Do not touch or walk through the spilled material.
If it can be safely done, stop the leak.
Ensure adequate ventilation.
Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Never return spills in original containers for re-use.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.
Provide sufficient air exchange and/or exhaust in work rooms.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Do not breathe vapours/dust.
Avoid formation of respirable particles.

Advice on protection against fire and explosion : Provide appropriate exhaust ventilation at places where dust is formed. Avoid dust formation.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version 1.0 Revision Date: 23.09.2024 SDS Number: 50000965 Date of last issue: -
Date of first issue: 23.09.2024

Hygiene measures : Wash hands before breaks and at the end of workday. When using do not smoke. When using do not eat or drink.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place.

Further information on storage conditions : Store in closed, labelled containers. The storage room should be constructed of incombustible material, closed, dry, ventilated and with impermeable floor, without access of unauthorised persons or children. The room should only be used for storage of chemicals. Food, drink, feed and seed should not be present. A hand wash station should be available.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Registered pesticide to be used in accordance with a label approved by country-specific regulatory authorities.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles
Eye wash bottle with pure water

Hand protection
Material : Wear chemical resistant gloves, such as barrier laminate, butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Dust impervious protective suit

Respiratory protection : In case of dust exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Plan first aid action before beginning work with this product. Always have on hand a first-aid kit, together with proper instructions. Wear suitable protective equipment. When using do not eat, drink or smoke.

In the context of professional plant protection use as recommended, the end user must refer to the label and the instructions for use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: solid
Form	: granules
Colour	: light brown
Odour	: mild, sweet
pH	: 6,0 - 7,0
	Concentration: 1 % (1% solution in water)
Flash point	: not determined
Flammability (solid, gas)	: Not highly flammable
Density	: No data available
Bulk density	: 530 - 630 kg/m3
Solubility(ies)	
Water solubility	: dispersible
Solubility in other solvents	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The product is not oxidizing.

9.2 Other information

Particle size	: No data available
Particle Size Distribution	: No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : Avoid extreme temperatures
Protect from frost, heat and sunlight.
Heating of the mixture may evolve harmful and irritant vapours.

10.5 Incompatible materials

Materials to avoid : Avoid strong acids, bases, and oxidizers

10.6 Hazardous decomposition products

Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : LD50 (Rat, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Remarks: (Data on the product itself)
Information source: Internal study report

Acute inhalation toxicity : LC50 (Rat): > 6,0 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Remarks: (Data on the product itself)
Information source: Internal study report

Components:

tribenuron-methyl (ISO):

Acute oral toxicity : LD50: > 5.000 mg/kg
Method: OECD Test Guideline 425

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Acute inhalation toxicity : LC50 (Rat): > 5,14 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 402

kaolin:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

LD50: > 2.000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50: 5,07 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

LD50: > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Alkyl-naphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Lignosulfonic acid, ethoxylated, sodium salts:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species	: Rabbit
Assessment	: Not classified as irritant
Method	: OECD Test Guideline 404
Result	: No skin irritation
GLP	: yes
Remarks	: (Data on the product itself) Information source: Internal study report

Components:

tribenuron-methyl (ISO):

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Species : Rabbit
Assessment : Not classified as irritant
Method : OECD Test Guideline 404
Remarks : May cause mild irritation.
Based on available data, the classification criteria are not met.

kaolin:

Method : OECD Test Guideline 404
Result : No skin irritation

Alkyl naphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Remarks : No data available

Lignosulfonic acid, ethoxylated, sodium salts:

Result : Skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Assessment : Not classified as irritant
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes
Remarks : (Data on the product itself)
Information source: Internal study report

Components:

tribenuron-methyl (ISO):

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Remarks : May cause mild irritation.
Based on available data, the classification criteria are not met.

kaolin:

Method : OECD Test Guideline 405
Result : No eye irritation

Alkyl naphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Result : Eye irritation

Lignosulfonic acid, ethoxylated, sodium salts:

Result : Moderate eye irritation

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Respiratory or skin sensitisation**Skin sensitisation**

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Test Type	: Modified Buehler Test
Species	: Guinea pig
Assessment	: Did not cause sensitisation on laboratory animals.
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.
GLP	: yes
Remarks	: (Data on the product itself) Information source: Internal study report

Components:**tribenuron-methyl (ISO):**

Test Type	: Maximisation Test
Species	: Guinea pig
Assessment	: May cause sensitisation by skin contact.
Method	: OECD Test Guideline 406
Result	: Causes skin sensitization.

kaolin:

Method	: OECD Test Guideline 429
Result	: Does not cause skin sensitisation.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:**tribenuron-methyl (ISO):**

Germ cell mutagenicity- Assessment	: Did not show mutagenic effects in animal experiments.
------------------------------------	---------------------------------------------------------

kaolin:

Genotoxicity in vitro	: Test Type: Ames test Method: OECD Test Guideline 471 Result: negative
-----------------------	-------------------------------------------------------------------------------

Genotoxicity in vivo	: Remarks: No data available
----------------------	------------------------------

Carcinogenicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Components:

tribenuron-methyl (ISO):

Remarks : No significant adverse effects were reported

Carcinogenicity - Assessment : Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:

tribenuron-methyl (ISO):

Reproductive toxicity - Assessment : No toxicity to reproduction
Animal testing did not show any effects on foetal development., Did not show teratogenic effects in animal experiments.

kaolin:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Based on available data, the classification criteria are not met.

Components:

tribenuron-methyl (ISO):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

kaolin:

Remarks : No significant adverse effects were reported

Lignosulfonic acid, ethoxylated, sodium salts:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

tribenuron-methyl (ISO):

Target Organs : Thyroid, Nervous system

Assessment : May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

kaolin:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

tribenuron-methyl (ISO):

Species	: Rabbit
LOAEL	: 80 mg/kg
Target Organs	: Thyroid, Nervous system
Assessment	: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.
Remarks	: Increased mortality or reduced survival

kaolin:

Remarks : No data available

Aspiration toxicity

Based on available data, the classification criteria are not met.

Components:

tribenuron-methyl (ISO):

The substance does not have properties associated with aspiration hazard potential.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 156 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 156 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (microalgae)): 0,067 mg/l Exposure time: 72 h EC50 (Lemna gibba (duckweed)): 0,033 mg/l Exposure time: 14 d

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Components:**tribenuron-methyl (ISO):**

- | | | |
|------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 738 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Crustaceans): > 320 mg/l
Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): > 894 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | EC50 (Pseudokirchneriella subcapitata (green algae)): 0,0208 mg/l
Exposure time: 120 h

EC50 (Lemna gibba (duckweed)): 0,00424 mg/l
Exposure time: 14 d |
| M-Factor (Acute aquatic toxicity) | : | 100 |
| Toxicity to fish (Chronic toxicity) | : | NOEC: 114 mg/l
Exposure time: 21 d
Species: Cyprinodon variegatus (sheepshead minnow)
Method: OECD Test Guideline 211

NOEC: 560 mg/l
Exposure time: 21 d
Species: Oncorhynchus mykiss (rainbow trout) |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC: 41 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea) |
| M-Factor (Chronic aquatic toxicity) | : | 100 |
| Toxicity to soil dwelling organisms | : | NOEC: 3,2 mg/kg
Exposure time: 56 d
Species: Eisenia fetida (earthworms) |
| Toxicity to terrestrial organisms | : | LD50: > 2.250 mg/kg
Species: Colinus virginianus (Bobwhite quail)

LD50: > 5.620 ppm
Species: Colinus virginianus (Bobwhite quail)
Remarks: Dietary

LD50: > 5.620 ppm
Species: Anas platyrhynchos (Mallard duck)
Remarks: Dietary

LD50: > 98.4 µg/bee |

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Exposure time: 48 h
End point: Acute contact toxicity
Species: Apis mellifera (bees)

LD50: > 9.1 µg/bee
Exposure time: 48 h
End point: Acute oral toxicity
Species: Apis mellifera (bees)

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

kaolin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms :
Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: No data available

Alkyl-naphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Toxicity to fish : LC50 (Zebra fish): > 10 - 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

EC10 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: > 10 - 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

tribenuron-methyl (ISO):

Biodegradability : Biodegradation: 29,4 %
Exposure time: 28 d

kaolin:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Alkyl-naphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Lignosulfonic acid, ethoxylated, sodium salts:

Biodegradability : Result: Not readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data is available on the product itself.

Components:

tribenuron-methyl (ISO):

Bioaccumulation : Bioconcentration factor (BCF): < 1
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: -0,38

kaolin:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n- : Remarks: Not applicable

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

octanol/water

12.4 Mobility in soil**Components:****tribenuron-methyl (ISO):**

Distribution among environmental compartments : Remarks: Under normal conditions the active ingredient/s is/are of high to intermediate mobility in soil. There is a potential for leaching to groundwater.

kaolin:

Distribution among environmental compartments : Remarks: Low mobility in soil

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Do not re-use empty containers.
Packaging that is not properly emptied must be disposed of as the unused product.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 3077
IMDG	:	UN 3077
IATA	:	UN 3077

14.2 UN proper shipping name

ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Tribenuron-methyl)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Tribenuron-methyl)
IATA	:	Environmentally hazardous substance, solid, n.o.s. (Tribenuron-methyl)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	:	9
IMDG	:	9
IATA	:	9

14.4 Packing group

ADR	
Packing group	: III
Classification Code	: M7
Hazard Identification Number	: 90
Labels	: 9
Tunnel restriction code	: (-)
IMDG	
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Remarks	: Environmentally hazardous substances/Marine Pollutants in single or combination packaging containing a net quantity per single or inner packaging of 5 kg or less for solids, or having a net quantity per single or inner packaging of 5 L or less for liquids may be transported as non-dangerous goods as provided in special provision A197 of the IATA and section 2.10.2.7 of IMDG code.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

IATA (Cargo)

Packing instruction (cargo aircraft)	:	956
Packing instruction (LQ)	:	Y956
Packing group	:	III
Labels	:	Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft)	:	956
Packing instruction (LQ)	:	Y956
Packing group	:	III
Labels	:	Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous	:	yes
---------------------------	---	-----

IMDG

Marine pollutant	:	yes
------------------	---	-----

IATA (Passenger)

Environmentally hazardous	:	yes
---------------------------	---	-----

IATA (Cargo)

Environmentally hazardous	:	yes
---------------------------	---	-----

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The components of this product are reported in the following inventories:

TCSI	:	Not in compliance with the inventory
TSCA	:	Product contains substance(s) not listed on TSCA inventory.
AIIC	:	Not in compliance with the inventory
DSL	:	This product contains the following components that are not on the Canadian DSL nor NDSL.

METHYL 2-[4-METHOXY-6-METHYL-1,3,5-TRIAZIN-2-

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

YL(METHYL)CARBAMOYLSULFAMOYL]BENZOATE

ENCS	:	Not in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory
NZIoC	:	Not in compliance with the inventory
TECI	:	Not in compliance with the inventory

15.2 Chemical safety assessment

A chemical safety assessment is not required for this product (mixture).

SECTION 16: Other information**Full text of H-Statements**

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2004/37/EC / TWA	:	Long term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergen-

FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

cy Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : see user defined free text

Classification of the mixture:

STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Calculation method
Based on product data or assessment
Calculation method

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

Prepared by

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.

© 2021-2024 FMC Corporation. All Rights Reserved.

SAFETY DATA SHEET



FLUENCE® 75, WG (ФЛЮЕНС®75, ВГ)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.09.2024	50000965	Date of first issue: 23.09.2024

UA / 6N