According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name FYFANON 500 g/L EC

Other means of identification

Product code 50000605

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- Insecticide

stance/Mixture

Recommended restrictions

on use

Use as recommended by the label.

1.3 Details of the supplier of the safety data sheet

<u>Supplier Address</u> FMC Agricultural Solutions A/S

Thyborønvej 78

DK-7673 HARBOØRE

Denmark

Telephone: +45 9690 9690 Telefax: +45 9690 9691

E-mail address: SDS-Info@fmc.com

**1.4 Emergency telephone number** For leak, fire, spill or accident emergencies, call:

Denmark: 45-69918573 (CHEMTREC)

Medical emergency:

Denmark: +45 82 12 12 12

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Short-term (acute) aquatic hazard, Cate-

gory 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Cat-

egory 1

H410: Very toxic to aquatic life with long lasting

effects.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or

repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe mist or vapours.P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391 Collect spillage.

### Hazardous components which must be listed on the label:

xylene

ethylbenzene

Solvent naphtha (petroleum), heavy arom.

**Additional Labelling** 

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

EUH208 Contains malathion (ISO) [containing ≤ 0,03 % isomalathion]. May produce an

allergic reaction.

EUH401 To avoid risks to human health and the environment, comply with instructions of use.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
malathion (ISO) [containing ≤ 0,03 % isomalathion]	121-75-5 204-497-7 015-041-00-X	Acute Tox. 4; H302 Skin Sens. 1; H317 Carc. 1B; H350 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 30 - < 50
		M-Factor (Acute aquatic toxicity): 1.000 M-Factor (Chronic aquatic toxicity): 1.000	
xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3;	>= 30 - < 50

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



# FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

	1	H412	
		Acute toxicity esti- mate	
		Acute dermal toxicity: 1.100 mg/kg	
ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2,5 - < 10
		Acute toxicity esti- mate	
		Acute inhalation toxicity (vapour): 17,8 mg/l	
Solvent naphtha (petroleum), heavy arom.	64742-94-5 265-198-5 649-424-00-3	Asp. Tox. 1; H304 Aquatic Chronic 2; H411 STOT SE 3; H336 EUH066	>= 1 - < 2,5
calcium bis(dodecylbenzenesulphonate), branched	70528-83-5 274-654-2	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 1 - < 3
		Acute toxicity esti- mate	
		Acute oral toxicity: 3.333 mg/kg Acute dermal toxicity: 1.470 mg/kg	
toluene	108-88-3 203-625-9 601-021-00-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 0,25 - < 1

For explanation of abbreviations see section 16.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

Remove to fresh air immediately. Get medical attention imme-

diately.

In case of skin contact : If on skin, rinse well with water.

Wash off immediately with plenty of water for at least 15

minutes.

If skin irritation persists, call a physician.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Malathion is a cholinesterase inhibitor affecting the central and

peripheral nervous systems producing respiratory depression.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Thermal decomposition can lead to release of irritating gases

and vapours.

Oxides of phosphorus

Carbon oxides Sulphur oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Dike runoff from fire control activities for later disposal.

Prevent fire extinguishing water from contaminating surface

water or the ground water system.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Never return spills in original containers for re-use.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe

label precautions. Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : Do not store near acids.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Registered pesticide to be used in accordance with a label

approved by country-specific regulatory authorities.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
malathion (ISO)	121-75-5	of exposure)	5 mg/m3	DK OEL
[containing ≤ 0,03	121-75-5	GV	5 1119/1113	DK OEL
% isomalathion]				
Further information	Means that th	e substance can be	absorbed through the skin.	
xylene	1330-20-7	TWA	50 ppm	2000/39/EC
			221 mg/m3	
Further information	Identifies the	possibility of significa	ant uptake through the skin, I	
		STEL	100 ppm	2000/39/EC
			442 mg/m3	
ı	1	1	1	1
		GV	25 ppm	DK OEL
E district	NA (l ( t)		109 mg/m3	O I Para Para f
Further information			absorbed through the skin.,	Juiding list of
ethylbenzene	organic solve	TWA	100 ppm	2000/39/EC
etriyiberizerie	100-41-4	IVVA	100 ppm 442 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
	10011111001110	STEL	200 ppm	2000/39/EC
			884 mg/m3	
		GV	50 ppm	DK OEL
			217 mg/m3	
Further information	Means that the substance can be absorbed through the skin., Means that the			
	substance is included in the list of substances considered carcinogenic., Guiding list of organic solvents., The substance has an EC-limit value			
toluene	108-88-3	TWA		2006/15/EC
toluene	100-00-3	IVVA	50 ppm 192 mg/m3	2006/15/EC
Further information	Indicative Ide	l Intifies the nossibility	of significant uptake through	the skin
1 ditiloi illioilliation	maicative, rac	STEL	100 ppm	2006/15/EC
		0122	384 mg/m3	2000/10/20
		GV	25 ppm	DK OEL
			94 mg/m3	
Further information	Means that the substance can be absorbed through the skin., Guiding list of			
	organic solvents., The substance has an EC-limit value			

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Dermal	Long-term systemic effects	212 mg/kg
	Consumers	Inhalation	Long-term systemic effects	66,3 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	65,3 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	125 mg/m3
	Consumers	Dermal	Long-term systemic effects	12,5 mg/kg
ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Workers	Inhalation	Long-term local ef- fects	293 mg/m3
	Workers	Skin contact	Long-term systemic effects	180 mg/kg
toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
	Workers	Inhalation	Acute systemic effects	384 mg/m3
	Workers	Inhalation	Long-term local ef- fects	192 mg/m3
	Workers	Inhalation	Acute local effects	384 mg/m3
	Workers	Dermal	Long-term systemic effects	384 mg/m3
	Consumers	Inhalation	Long-term systemic effects	56,5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	226 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	56,5 mg/m3
	Consumers	Inhalation	Acute local effects	226 mg/m3
	Consumers	Dermal	Long-term systemic effects	226 mg/kg
	Consumers	Oral	Long-term systemic effects	

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

malathion (ISO) [containing ≤ 0,03 % isomalathion]	Fresh water	1,2
xylene	Fresh water	0,327 mg/l
	Intermittent use (freshwater)	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
ethylbenzene	Fresh water	0,1 mg/l
	Marine water	0,01 - 0,1 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water sediment	13,7 mg/kg dry weight (d.w.)
	Marine sediment	1,37 mg/kg dry weight (d.w.)
	Intermittent use/release	0,100 mg/l
toluene	Fresh water	0,68 mg/l

#### 8.2 Exposure controls

### Personal protective equipment

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

Protective measures : Plan first aid action before beginning work with this product.

Always have on hand a first-aid kit, together with proper in-

structions.

Personal protective equipment comprising: suitable protective

gloves, safety goggles and protective clothing

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance

at the specific workplace.

Ensure that eye flushing systems and safety showers are

located close to the working place.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

light yellow

Odour : slight

aromatic

Odour Threshold : No data available

Melting point/freezing point : < 0 °C

Initial boiling point and boiling

range

No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : ca. 30 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 4,3 (22 °C)

Concentration: 10 g/l

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 2,9 mm2/s (22 °C)

Solubility(ies)

Water solubility : emulsifiable

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : No data available

Density : 1.028 g/l

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Relative vapour density : No data available

Particle characteristics

Particle size : No data available

Particle Size Distribution : No data available

Shape : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Flammability (liquids) : Sustains combustion

**SECTION 10: Stability and reactivity** 

**10.1 Reactivity** No decomposition if stored and applied as directed.

**10.2 Chemical stability** No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

See subsection 5.2.

**SECTION 11: Toxicological information** 

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Not classified based on available information.

**Product:** 

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Remarks: Based on data from similar materials

### **Components:**

### malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Acute oral toxicity : LD50 (Rat): 1.857 mg/kg

Method: OECD Test Guideline 401

Assessment: The component/mixture is moderately toxic after

single ingestion.

Remarks: Based on data from similar materials

LD50 (Rat): > 5.000 mg/kg Method: FIFRA 81.01

Acute inhalation toxicity : LC50 (Rat): > 5,02 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: EPA OPP 81 - 3

Assessment: The component/mixture is minimally toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: FIFRA 81.02

Assessment: The substance or mixture has no acute dermal

toxicity

xylene:

Acute oral toxicity : LD50 (Rat, male): 3.523 mg/kg

Method: Regulation (EC) No. 440/2008, Annex, B.1 bis

LD50 (Rat, female): > 4.000 mg/kg

Method: Regulation (EC) No. 440/2008, Annex, B.1 bis

Acute inhalation toxicity : LC50 (Rat, male and female): 27,6 mg/l, 6350 ppm

Exposure time: 4 h
Test atmosphere: vapour

Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Method: Converted acute toxicity point estimate

LD50 (Rabbit, male): > 4.200 mg/kg

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat, male and female): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute toxicity estimate: 17,8 mg/l

Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : LD50 (Rabbit, male): 15.400 mg/kg

Solvent naphtha (petroleum), heavy arom.:

Acute oral toxicity : LD50 (Rat, male and female): > 5.000 mg/kg

Method: OECD Test Guideline 420

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,688 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

calcium bis(dodecylbenzenesulphonate), branched:

Acute oral toxicity : Acute toxicity estimate: 3.333 mg/kg

Acute dermal toxicity : Acute toxicity estimate: 1.470 mg/kg

toluene:

Acute oral toxicity : LD50 (Rat): 5.580 mg/kg

Acute inhalation toxicity : LC50 (Rat, male): 25,7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

LC50 (Rat, female): 30 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : (Rabbit): 12.267 mg/kg

Skin corrosion/irritation

Causes skin irritation.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

**Product:** 

Result : slight irritation

Remarks : May cause skin irritation in susceptible persons.

**Components:** 

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Method : FIFRA 81.05
Result : slight irritation

xylene:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

ethylbenzene:

Species : Rabbit

Remarks : Moderate skin irritation

Solvent naphtha (petroleum), heavy arom.:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

calcium bis(dodecylbenzenesulphonate), branched:

Result : Skin irritation

toluene:

Species : Rabbit

Assessment : Repeated exposure may cause skin dryness or cracking.

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Result : slight irritation

Remarks : Based on data from similar materials

Remarks : May cause substantial but temporary eye damage.

Components:

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Method : FIFRA 81.04

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Result : slight irritation

xylene:

Species : Rabbit

Result : Moderate eye irritation

ethylbenzene:

Species : Rabbit

Result : No eye irritation

Solvent naphtha (petroleum), heavy arom.:

Species : Rabbit

Result : No eye irritation

calcium bis(dodecylbenzenesulphonate), branched:

Result : Irreversible effects on the eye

toluene:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

**Product:** 

Assessment : Not a skin sensitizer.

Result : Does not cause skin sensitisation.

**Components:** 

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Test Type : Buehler Test Method : FIFRA 81.06

Result : Does not cause skin sensitisation.

Test Type : Local lymph node assay (LLNA)
Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

Test Type : Magnussen-Kligman test
Method : OECD Test Guideline 406

Result : May cause sensitisation by skin contact.
Remarks : Based on data from similar materials

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

xylene:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

Solvent naphtha (petroleum), heavy arom.:

Test Type : Maximisation Test Species : Guinea pig

Result : Not a skin sensitizer.

toluene:

Test Type : Maximisation Test

Species : Guinea pig

Result : Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

**Product:** 

Germ cell mutagenicity- As-

: Weight of evidence does not support classification as a germ

sessment cell mutagen.

**Components:** 

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Remarks: Based on data from similar materials

Test Type: unscheduled DNA synthesis assay

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: chromosome aberration assay

Species: Rat Result: negative

Remarks: Based on data from similar materials

Test Type: unscheduled DNA synthesis assay

Species: Rat Result: negative

Remarks: Based on data from similar materials

xylene:

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Method: Regulation (EC) No. 440/2008, Annex, B.10

Result: negative

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Result: negative

Genotoxicity in vivo : Test Type: Rodent Dominant Lethal Assay

Species: Mouse (male)

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 478

Result: negative

ethylbenzene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Method: OECD Test Guideline 474

Result: negative

Solvent naphtha (petroleum), heavy arom.:

Genotoxicity in vitro : Test Type: reverse mutation assay

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Bone marrow chromosome aberration

Species: Rat

Application Route: inhalation (vapour)

Result: negative

toluene:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Rat Result: negative

Carcinogenicity

Not classified based on available information.

Product:

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

### **Components:**

### malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Species : Rat
Application Route : Ingestion
Exposure time : 24 month(s)
NOAEL : 6.000 ppm
Result : positive

Remarks : Probably carcinogenic to humans (IARC 2A)

Carcinogenicity - Assess-

ment

Possible human carcinogen

xylene:

Species : Rat
Application Route : Oral
Exposure time : 103 weeks
Result : negative

ethylbenzene:

Species : Mouse, male and female

Application Route : Inhalation
Exposure time : 104 weeks
Result : positive

#### Solvent naphtha (petroleum), heavy arom.:

Species : Rat, male and female
Application Route : inhalation (vapour)
Exposure time : 12 month(s)

NOAEC : 1,8 mg/l Result : negative

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Not classifiable as a human carcinogen.

#### Reproductive toxicity

Not classified based on available information.

**Product:** 

Reproductive toxicity - As-

Weight of evidence does not support classification for repro-

sessment

ductive toxicity

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

#### **Components:**

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

General Toxicity F1: NOAEL: 132 - 152 mg/kg bw/day

Symptoms: Reduced offspring weight gain

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

General Toxicity Maternal: NOAEL: 400 mg/kg bw/day

Teratogenicity: NOAEL: 800 mg/kg bw/day

Result: No teratogenic effects

Test Type: Embryo-foetal development

Species: Rabbit

General Toxicity Maternal: NOAEL: 25 mg/kg bw/day

Teratogenicity: NOAEL: 25 mg/kg bw/day

Result: No teratogenic effects

Reproductive toxicity - As-

sessment

Animal testing showed no reproductive toxicity.

xylene:

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: inhalation (vapour)
General Toxicity F1: NOAEC: 2,171 mg/l

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Pre-natal

Species: Rat

Application Route: inhalation (vapour)

Symptoms: Maternal effects

Result: negative

Remarks: Based on data from similar materials

ethylbenzene:

Effects on fertility : Species: Rat, male and female

Application Route: Inhalation Method: OECD Test Guideline 415

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat, female

Application Route: Inhalation Method: OECD Test Guideline 414

Result: negative

toluene:

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Effects on foetal develop-

ment

: Species: Rat

Application Route: Inhalation Result: Teratogenic effects

Remarks: Adverse developmental effects were observed

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, and/or on development, based on animal experiments.

### STOT - single exposure

Not classified based on available information.

**Product:** 

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

**Components:** 

xylene:

Assessment : May cause respiratory irritation.

toluene:

Assessment : May cause drowsiness or dizziness.

#### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Components:** 

xylene:

Exposure routes : Inhalation
Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

ethylbenzene:

Exposure routes : Inhalation
Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

toluene:

Exposure routes : Inhalation Target Organs : inner ear

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

#### Repeated dose toxicity

### **Components:**

### malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Species : Rat

LOAEL : 34,4 mg/kg Application Route : Oral - feed Exposure time : 90 d

Target Organs : Nervous system

Symptoms : cholinesterase inhibition

xylene:

Species : Rat
NOAEC : 3,515 mg/l
Application Route : Inhalation
Exposure time : 13 weeks

ethylbenzene:

Species : Rat, male and female

NOAEL : 75 mg/kg Application Route : Oral Exposure time : 28 days

Method : OECD Test Guideline 407

Species : Rat, male and female

NOAEL : 250 ppm LOAEL : 75 ppm

Application Route : inhalation (vapour)

Exposure time : 728 days

Method : OECD Test Guideline 453

## Solvent naphtha (petroleum), heavy arom.:

Species : Rat, male and female

NOAEC : 0,9 - 1,8 mg/l
Application Route : inhalation (vapour)

Exposure time : 12 months

toluene:

Species : Rat NOAEL : 625 mg/kg Application Route : Oral

Symptoms : central nervous system effects

Species : Rat
NOAEL : 0,098 mg/l
Application Route : Inhalation
Test atmosphere : vapour

Species : Rat

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

LOAEL : 2,261 mg/l
Application Route : Inhalation
Test atmosphere : vapour

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### **Product:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Components:**

### malathion (ISO) [containing ≤ 0,03 % isomalathion]:

The substance does not have properties associated with aspiration hazard potential.

#### xylene:

May be fatal if swallowed and enters airways.

### ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Solvent naphtha (petroleum), heavy arom.:

May be fatal if swallowed and enters airways.

### toluene:

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **Experience with human exposure**

### **Components:**

xylene:

General Information : Target Organs: inner ear

Symptoms: hearing loss

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version **Revision Date:** SDS Number: Date of last issue: -

01.06.2022 50000605 Date of first issue: 01.06.2022 1.0

> Target Organs: Central nervous system Symptoms: Drowsiness, Dizziness

ethylbenzene:

**General Information** Target Organs: inner ear

Symptoms: hearing loss

Solvent naphtha (petroleum), heavy arom.:

Skin contact Symptoms: Repeated exposure may cause skin dryness or

cracking.

**Neurological effects** 

Components:

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Remarks : No neurotoxicity observed in animal studies

**Further information** 

**Product:** 

Remarks Solvents may degrease the skin.

**SECTION 12: Ecological information** 

12.1 Toxicity

**Product:** 

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Components:** 

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,18 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.72 µg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: IC50 (Selenastrum capricornutum (green algae)): 4,06 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox- : 1.000

icity)

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version **Revision Date:** SDS Number: Date of last issue: -

01.06.2022 50000605 Date of first issue: 01.06.2022 1.0

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,021 mg/l Exposure time: 37 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC: 0,006 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic

toxicity)

1.000

Toxicity to soil dwelling or-

ganisms

613 mg/kg

Exposure time: 14 d

Species: Eisenia fetida (earthworms)

Toxicity to terrestrial organ-

isms

LC50: 3.497 mg/kg

Exposure time: 5 d

Species: Colinus virginianus (Bobwhite quail)

LD50: 1.485 mg/kg

Species: Anas platyrhynchos (Mallard duck)

LD50: 0.38 µg/bee

Species: Apis mellifera (bees)

xylene:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l

Exposure time: 96 h

Test Type: Static renewal test Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44

ma/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (activated sludge): 16 mg/l Toxicity to microorganisms

Exposure time: 28 h

Method: OECD Test Guideline 301F

Toxicity to fish (Chronic tox-

icity)

NOEC: > 1,3 mg/l Exposure time: 56 d

25 / 36

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Species: Oncorhynchus mykiss (rainbow trout)

Test Type: flow-through test

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,96 mg/l Exposure time: 7 d

Species: Ceriodaphnia dubia (water flea) Remarks: Based on data from similar materials

Toxicity to soil dwelling or-

ganisms

NOEC: 16 mg/kg Exposure time: 14 d

Species: Eisenia fetida (earthworms)

Remarks: Based on data from similar materials

ethylbenzene:

Toxicity to fish : LC50 (Menidia menidia (Atlantic silverside)): 5,1 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

EC50 (Ceriodaphnia dubia (water flea)): 3,2 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (algae)): 3,6 mg/l

Exposure time: 96 h

EC50 (Skeletonema costatum (marine diatom)): 7,7 mg/l

Exposure time: 96 h

Toxicity to microorganisms

Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,25 - 3,4 mg/l

Species: Fish Method: QSAR

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,96 mg/l Exposure time: 7 d

Species: Ceriodaphnia dubia (water flea)

Toxicity to soil dwelling or-

ganisms

0,047 mg/cm2 Exposure time: 48 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 207

Solvent naphtha (petroleum), heavy arom.:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

Exposure time: 96 h

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 1,4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3

mg/l

Exposure time: 24 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : LL50 (Tetrahymena pyriformis): 677,9 mg/l

Exposure time: 72 h

Test Type: Growth inhibition

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EL50: 0,89 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

calcium bis(dodecylbenzenesulphonate), branched:

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (algae): > 1 - 10 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

toluene:

Toxicity to fish : LC50 (Fish): 5,5 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50: 3,78 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 134 mg/l

Exposure time: 3 h

Toxicity to fish (Chronic tox-

icity)

NOEC: 1,4 mg/l

Species: Oncorhynchus kisutch (coho salmon)

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,74 mg/l Exposure time: 7 d

Species: Ceriodaphnia sp.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

### 12.2 Persistence and degradability

#### **Components:**

#### malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Biodegradability : Result: Not readily biodegradable.

xylene:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 16 mg/l

Result: Readily biodegradable.

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 16 mg/l Result: Readily biodegradable.

Biodegradation: 94 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 16,2 mg/l Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

ethylbenzene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 79 % Exposure time: 10 d

Solvent naphtha (petroleum), heavy arom.:

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 58,6 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

calcium bis(dodecylbenzenesulphonate), branched:

Biodegradability : Result: Readily biodegradable.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version **Revision Date:** SDS Number: Date of last issue: -

01.06.2022 50000605 Date of first issue: 01.06.2022 1.0

toluene:

Biodegradability : Result: Readily biodegradable.

### 12.3 Bioaccumulative potential

#### **Components:**

malathion (ISO) [containing ≤ 0,03 % isomalathion]:

Bioaccumulation Species: Fish

> Bioconcentration factor (BCF): 95 Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2,75

xylene:

Bioaccumulation Species: Oncorhynchus mykiss (rainbow trout)

> Exposure time: 7 d Concentration: 1,3 mg/l

Bioconcentration factor (BCF): > 4,9

Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

log Pow: 3,2 (20 °C)

pH: 7

Remarks: Based on data from similar materials

log Pow: 3,12 (20 °C)

pH: 7

Remarks: Based on data from similar materials

log Pow: 3,15 (20 °C)

pH: 7

Remarks: Based on data from similar materials

log Pow: 3,15 (20 °C)

pH: 7

Remarks: Based on data from similar materials

ethylbenzene:

Bioaccumulation Species: Fish

Bioconcentration factor (BCF): 110

Partition coefficient: n-

Pow: 4.170 (20 °C) octanol/water

log Pow: 3,03 - 3,6 (20 °C)

pH: 7,84

Solvent naphtha (petroleum), heavy arom.:

log Pow: 3,72 Partition coefficient: noctanol/water Method: QSAR

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

## calcium bis(dodecylbenzenesulphonate), branched:

Bioaccumulation : Bioconcentration factor (BCF): 1

Remarks: Bioaccumulation is unlikely.

toluene:

Bioaccumulation : Bioconcentration factor (BCF): 90

Partition coefficient: n-

octanol/water

: log Pow: 2,73 (20 °C)

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Waste, residues, etc. must be collected, stored and disposed

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

of in tightly closed container labeled: "Contains a substance that is covered by the Danish health and safety regulation in

terms of cancer risk."

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1993
ADR : UN 1993
RID : UN 1993
IMDG : UN 1993
IATA : UN 1993

### 14.2 UN proper shipping name

**ADN** : FLAMMABLE LIQUID, N.O.S.

(Xylene, Malathion)

**ADR** : FLAMMABLE LIQUID, N.O.S.

(Xylene, Malathion)

RID : FLAMMABLE LIQUID, N.O.S.

(Xylene, Malathion)

**IMDG** : FLAMMABLE LIQUID, N.O.S.

(Xylene, Malathion)

IATA : Flammable liquid, n.o.s.

(Xylene, Malathion)

## 14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

### 14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

**ADR** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

**RID** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

**IMDG** 

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

**ADR** 

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 3

toluene (Number on list 48)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

malathion (ISO) [containing ≤ 0,03

% isomalathion]

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

E1 ENVIRONMENTAL HAZARDS

### Other regulations:

When evaluating a workplace, measures must be taken to ensure that employees are not exposed to conditions that may pose a risk during pregnancy or breastfeeding (cf. The Danish Working Environment Authority's Executive Order on The Performance of Work)

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

The substance/mixture is subject to the provisions of BEK nr. 1795 of 18/12/2015 (as amended) "Executive order on Measures to Protect Workers from the Risks related to Exposure to Carcinogenic Substances and

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified ethylbenzene malathion (ISO) [containing ≤ 0,03

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

Materials at Work". The work with this substance/mixture % isomalathion]

may pose a cancer risk.

### The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

TECI: Not in compliance with the inventory

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

Chemical Safety Assessments (CSA) under REACH are carried out at the substance level when the substance is registered thru ECHA. It includes exposure scenarios for all the identified uses of the substance. Chemical Safety Assessments are not performed on mixtures.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H319

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H350 : May cause cancer.

Causes serious eve irritation.

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



## FYFANON 500 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
4 0	04.00.000		

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

H361d : Suspected of damaging the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2006/15/EC : Europe. Indicative occupational exposure limit values

DK OEL : Denmark. Occupational Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2006/15/EC / TWA : Limit Value - eight hours 2006/15/EC / STEL : Short term exposure limit DK OEL / GV : Long term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

According to Commission Regulation (EU) 2020/878 of amending Regulation (EC) No 1907/2006



Classification procedure:

## FYFANON 500 g/L EC

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.06.2022 50000605 Date of first issue: 01.06.2022

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### **Further information**

Classification of the mixture:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT RE 2	H373	Calculation method
A T - 4	11004	December of the conservation

Asp. Tox. 1 H304 Based on product data or assessment
Aquatic Acute 1 H400 Based on product data or assessment
Aquatic Chronic 1 H410 Based on product data or assessment

#### Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

### **Prepared by**

**FMC** Corporation

FMC Logo - Trademark of FMC Corporation

© 2021 FMC Corporation. All Rights Reserved.

**DK / 6N**