

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: SKD-S2 Aerosol

Product Code: Not available.

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Non-Destructive Testing.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Magnaflux
155 Harlem Avenue,
Glenview, Illinois
60025

Telephone Number: 847-657-5300

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: CHEMTREC 800-424-9300

Date of Preparation: November 25, 2013 **Version #:** 1.2

Section 2: HAZARD(S) IDENTIFICATION


2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Flammable Aerosol 1
Gases Under Pressure - Compressed Gas
Eye irritation 2A
Specific target organ toxicity - Single exposure 3
Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:



Signal Word:

Danger

Hazard Statement:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to lungs through prolonged or repeated exposure.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, including under lids. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Inhalation: May cause respiratory tract irritation. May cause drowsiness or dizziness.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Water, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

Skin Protection:

Hand Protection: Chemical-resistant gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

General Health and Safety Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White liquid.
Color:	White.
Odor:	Alcohol.
Odor Threshold:	Not available.
Physical State:	Gas/Pressurized Liquid.
pH:	Neutral.
Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	~ 55 °C (~ 132 °F)
Flash Point:	Not applicable.
Evaporation Rate:	0.4 (Ether = 1)
Flammability:	Flammable.
Lower Flammability/Explosive Limit:	2 %
Upper Flammability/Explosive Limit:	15 %
Vapor Pressure:	65 psi @ 24 °C (75 °F)
Vapor Density:	3
Relative Density/Specific Gravity:	0.87
Solubility:	Partial.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.

Ceramic materials and wares, chemicals	Not available.	Not available.	Oral > 2000 mg/kg, rat Dermal > 2500 mg/kg, rabbit
Talc	1,000 mg/m ³	Not available.	Not available.

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
> 5 mg/L 4h, rat	> 2000 mg/kg, rat	> 2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Isopropanol	G-A4, I-3
Petroleum gases, liquefied, sweetened	Not listed.
Acetone	G-A4
Ceramic materials and wares, chemicals	Not listed.
Talc	G-A4, I-3

* See Section 15 for more information.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory Sensitization: Based on available data, the classification criteria are not met.

Skin Sensitization: Based on available data, the classification criteria are not met.

STOT-Single Exposure: May cause drowsiness or dizziness.

Chronic Health Effects:

Carcinogenicity: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met.

Teratogenicity: Based on available data, the classification criteria are not met.

Embryotoxicity: Based on available data, the classification criteria are not met.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Causes damage to lungs through prolonged or repeated exposure.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Toxicologically Synergistic Materials: Not available.

Other Information: Not available.

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Isopropanol	Not listed.	Not listed.	Not listed.	313
Petroleum gases, liquefied, sweetened	Not listed.	Not listed.	Not listed.	Not listed.
Acetone	Not listed.	Not listed.	5,000	Not listed.
Ceramic materials and wares, chemicals	Not listed.	Not listed.	Not listed.	Not listed.
Talc	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations:

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer.

Global Inventories:

Ingredient	Canada DSL/NDL	USA TSCA
Isopropanol	DSL	Yes.
Petroleum gases, liquefied, sweetened	DSL	Yes.
Acetone	DSL	Yes.
Ceramic materials and wares, chemicals	DSL	Yes.
Talc	DSL	Yes.

NFPA-National Fire Protection Association:

Health:	2
Fire:	4
Reactivity:	0

HMIS-Hazardous Materials Identification System:

Health:	2*
Fire:	4
Physical Hazard:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.