

## SAFETY DATA SHEET

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name Valvoline™ NON-DETERGENT SAE 30 MOTOR OIL

Product code VV265

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance: liquid, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

#### Potential Health Effects

##### **Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

##### **Eye contact**

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

##### **Skin contact**

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

##### **Ingestion**

## SAFETY DATA SHEET

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

### Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

### Target Organs

No data

### Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

### Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=80-<90%
RESIDUAL OILS (PETROLEUM), SOLVENT-	64742-62-7	>=10-<15%

**SAFETY DATA SHEET**

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

DEWAXED		
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	>=1.5-<5%
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7	>=1.5-<5%
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	>=1-<1.5%

**4. FIRST AID MEASURES****Eyes**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

**Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation**

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

**Notes to physician**

**Hazards:** Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum

## SAFETY DATA SHEET

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

**Treatment:** No information available.

### 5. FIREFIGHTING MEASURES

#### **Suitable extinguishing media**

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Water spray

#### **Hazardous combustion products**

carbon dioxide and carbon monoxide, Hydrocarbons

#### **Precautions for fire-fighting**

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

#### **NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

### 6. ACCIDENTAL RELEASE MEASURES

#### **Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

#### **Environmental precautions**

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

#### **Methods for cleaning up**

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

## SAFETY DATA SHEET

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

### Other information

Comply with all applicable federal, state, and local regulations.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

### Storage

Store in a cool, dry, ventilated area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

HYDROTREATED LIGHT PARAFFINIC DISTILLATE		64742-55-8	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)		64742-70-7	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

## SAFETY DATA SHEET

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

### Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

### Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).

### Respiratory protection

Respiratory protection is not required under normal conditions of use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Colour	amber
Boiling point/boiling range	424.99 °F / 218.33 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas
Flash point	> 390 °F / > 199 °C Cleveland open cup
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V) Calculated Explosive Limit
Vapour pressure	1.333 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Relative vapour density	(<)1 AIR=1
Density	0.8890 g/cm3 @ 60.01 °F / 15.56 °C
	7.39 lb/gal @ 60.1 °F / 15.6 °C
Water solubility	negligible

## SAFETY DATA SHEET

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to avoid

excessive heat

#### Incompatible products

Strong oxidizing agents

#### Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons, Aldehydes, oxides of sulfur, nitrogen and phosphorus

#### Hazardous reactions

Product will not undergo hazardous polymerization.

### 11. TOXICOLOGICAL INFORMATION

#### Acute oral toxicity

Acute oral toxicity - : no data available  
Product

#### Acute oral toxicity - Components

HEAVY PARAFFINIC : LD 50: > 15 g/kg Species: Rat  
DISTILLATE

CATALYTIC DE : LD 50: > 2,000 mg/kg Species: Rat Remarks: Information  
WAXED HEAVY given is based on data obtained from similar substances.  
PARAFFINIC OIL  
(PETROLEUM)

HYDROTREATED : LD 50: > 15 g/kg Species: Rat  
HEAVY PARAFFINIC  
BASE OIL

## SAFETY DATA SHEET

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

### Acute inhalation toxicity

Acute inhalation toxicity - : no data available  
Product

### Acute dermal toxicity

Acute dermal toxicity - : no data available  
Product

### Acute dermal toxicity - Components

HEAVY PARAFFINIC : LD 50: > 5 g/kg Species: Rabbit  
DISTILLATE

CATALYTIC DE : LD 50: > 2,000 mg/kg Species: Rabbit Remarks:  
WAXED HEAVY Information given is based on data obtained from similar  
PARAFFINIC OIL substances.  
(PETROLEUM)

HYDROTREATED : LD 50: > 5 g/kg Species: Rabbit  
HEAVY PARAFFINIC  
BASE OIL

### Acute toxicity (other routes of administration)

Acute toxicity (other : no data available  
routes of administration)

## 12. ECOLOGICAL INFORMATION

### Biodegradability

Biodegradability - Product : no data available

### Bioaccumulation

Bioaccumulation - Product : no data available

### Ecotoxicity effects

#### Toxicity to fish

Toxicity to fish - Product : no data available



## SAFETY DATA SHEET

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

### Toxicity to daphnia and other aquatic invertebrates.

Toxicity to daphnia and : no data available  
other aquatic invertebrates.  
- Product

### Toxicity to algae

Toxicity to algae - : no data available  
Product

### Toxicity to bacteria

Toxicity to bacteria - : no data available  
Product

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
--------------	----------------------	------------------	-----------------------	------------------	------------------------------------

### U.S. DOT - ROAD

Not dangerous goods

### U.S. DOT - RAIL

## SAFETY DATA SHEET

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

Not dangerous goods
---------------------

### U.S. DOT - INLAND WATERWAYS

Not dangerous goods
---------------------

### TRANSPORT CANADA - ROAD

Not dangerous goods
---------------------

### TRANSPORT CANADA - RAIL

Not dangerous goods
---------------------

### TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods
---------------------

### INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods
---------------------

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods
---------------------

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods
---------------------

### MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods
---------------------

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## 15. REGULATORY INFORMATION

### California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.	
--	--

# SAFETY DATA SHEET

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

## SARA Hazard Classification

### SARA 311/312 Classification

No SARA Hazards

## SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE	64742-54-7
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0

### Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE	64742-54-7
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0

## Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	1	1

**SAFETY DATA SHEET**

Revision Date: 02/23/2012

Print Date: 4/5/2012

MSDS Number: R0169702

Version: 3.1

Valvoline™ NON-DETERGENT SAE 30  
MOTOR OIL  
VV265

	HMIS	NFPA
Physical hazards	0	
Instability		0
Specific Hazard	--	--

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).