Material Safety Data Sheet

Print Date 31-Mar-2011 **Revision Date** 31-Mar-2011 **Revision Number** 1

1. PRODUCT AND COMPANY IDENTIFICATION

Common name	THINNER NO. 63
Product code	F041-0063
Trade name	THINNER CLEAR
Product Class	PAINT THINNER
Manufacturer	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency telephone	800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes	Moderately irritating to the eyes.
Skin	Irritating to skin.
Inhalation	Irritating to respiratory system.
Ingestion	May be harmful if swallowed. Do not induce vomiting: may contain petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis.

Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Skin disorders. Respiratory disorders.

Interactive effects Use of alcoholic beverages may enhance toxic effects.

Potential environmental effects See Section 12 for additional Ecological Information

Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
HEXYL ACETATE	88230-35-7	60 - 100
METHYL N-AMYL KETONE	110-43-0	5 - 10
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - 5

4. FIRST AID MEASURES

Eye contact: Rinse thoroughly with plenty of water for at least 15 minutes.

Skin contact: Wash off immediately with soap and plenty of water.

Ingestion: If swallowed, do not induce vomiting. Get medical attention immediately.

Inhalation: Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties Combustible material.

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO2) - Foam - Dry chemical

Hazardous decomposition products Oxides of carbon, hydrocarbons.

Specific hazards arising from the chemical
Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for firefighters
Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Other information Not applicable

7. HANDLING AND STORAGE

Handling
Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage
Close container after each use. Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
HEXYL ACETATE				TWA: 50 ppm TWA; 294 mg/m^3 TWA	
METHYL N-AMYL KETONE	: 50 ppm TWA	: 100 ppm TWA; 465 mg/m^3 TWA	TWA: 50 ppm TWAEV; 233 mg/m^3 TWAEV	TWA: 25 ppm TWA; 115 mg/m^3 TWA	: 50 ppm TWA; 235 mg/m^3 TWA : 100 ppm STEL; 465 mg/m^3 STEL

Engineering measures Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection Lightweight protective clothing, Apron, Impervious gloves
Eye/face protection Safety glasses with side-shields
Respiratory protection **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	57°C / 134.0°F
Boiling range	113 - 176°C / 235.0 - 349.0°F
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	.87915 g/cm3
Density	7.31585 lbs/gal
Volatile organic compounds (VOC) content	6.413 lbs/gal
Volatile by weight	87.6590 %
Volatile by volume	88.3522 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	**Conditions to avoid**	Heat, flames and sparks.
Incompatible products	Strong oxidizing agents. Acids. Alkalines.	**Possibility of hazardous reactions**	None under normal processing

11. TOXICOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL N-AMYL KETONE	1670 mg/kg (Rat)	12600 µL/kg (Rabbit)	
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	6500 mg/kg (Rat)	14500 mg/kg (Rabbit)	73.7 mg/L (Rat) 4 h

Irritation No information available
Corrosivity No information available
Sensitization No information available

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutegenicity No information available
Reproductive effects No information available
Developmental effects No information available
Teratogenicity No information available
Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

.

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
METHYL N-AMYL KETONE		LC50 126-137 mg/L Pimephales promelas 96 h		
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE		LC50 50-70 mg/L Brachydanio rerio 96 h LC50= 77 mg/L Pimephales promelas 96 h		LC50 = 665 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name PAINT & RELATED MATERIAL-(NMFC 149980 SUB2)

15. REGULATORY INFORMATION

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Does not Comply
AICS	Does not Comply

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):
Component
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE

United States of America Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - 5	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	no
Acute Health Hazard	yes
Fire Hazard	yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

CERCLA

United States of America State Regulations

California Prop. 65
This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL N-AMYL KETONE	X	X	X		X
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE		X	X	X	

Other international regulations

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification
B3 Combustible liquid
D2B Toxic materials

Legend
NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date	31-Mar-2011
Revision Note	No information available

HMIS (Hazardous Material Information System) **Health** 2 **Flammability** 2 **Reactivity** 1

Disclaimer
For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.
To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS