# PROBRANDS

## SAFETY DATA SHEET

#### 1. Identification

Product identifier LPS® PreSolve (Aerosol)

Other means of identification

Part Number 01420

**Recommended use** A solvent degreasing agent designed for removing tar, adhesives, grease, oil and other residues

from metal and other hard surfaces.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company name ITW Pro Brands

**Address** 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

#### 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin

irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause

drowsiness or dizziness. May be fatal if swallowed and enters airways.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Wear eye/face protection. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work

clothing must not be allowed out of the workplace. Wear protective gloves.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep

comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Material name: LPS® PreSolve (Aerosol)

SDS US

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a Storage

well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None known.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light		64742-47-8	60 - 70
3-Methoxy-3-methyl-1-butanol (MMB)		56539-66-3	10 - 20
d-limonene		5989-27-5	10 - 20
Carbon Dioxide		124-38-9	1 - 3

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while Skin contact

removing contaminated clothing and shoes. Get medical attention if irritation develops and

persists.

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Eye contact

Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Only induce vomiting at the instruction of Ingestion

medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs,

drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and

Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath,

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

In the case of accident or if you feel unwell, seek medical advice immediately (show the label General information where possible). Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves.

are reversible if exposure is stopped.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not

breathe fumes.

Extremely flammable aerosol.

#### Accidental release measures

Personal precautions, protective equipment and emergency procedures Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
US. ACGIH Threshold Lin	nit Values		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
US. NIOSH: Pocket Guide	e to Chemical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
ogical limit values	No biological exposure limits noted for the ing	P 1/ )	

## Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection

**Hand protection** Chemical resistant gloves are recommended.

Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves. Other

Respiratory protection No personal respiratory protective equipment normally required. Use a positive-pressure

air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate

protection.

Not applicable. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Gas. Physical state Aerosol. **Form** 

Color Clear, Off-white.

Odor Orange

**Odor threshold** Not established Not applicable Not established Melting point/freezing point Initial boiling point and boiling > 302 °F (> 150 °C)

range

Flash point 104.0 °F (40.0 °C) Tag Closed Cup

0.7%

6%

**Evaporation rate** > 0.1 BuAc Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure < 5 mm Hg @ 20°C

> 1 (air = 1)Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) < 15 %

**Partition coefficient** Not established

(n-octanol/water)

> 392 °F (> 200 °C) **Auto-ignition temperature Decomposition temperature** Not established **Viscosity** < 3 cSt @ 25°C

Other information

Heat of combustion > 30 kJ/g100 % Percent volatile

Specific gravity 0.82 - 0.86 @ 20°C VOC 97.2 % per U.S. State and Federal Consumer Product Regulations

CARB

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Risk of ignition. Chemical stability

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

#### 11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness.

Skin contact Causes skin irritation. May cause sensitization by skin contact.

Eye contact Causes eye irritation.

Ingestion May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. May cause allergic skin reaction.

Components **Species Test Results** 

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

**Acute** Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapor

LC50 Rat > 4.5 mg/l, 4 Hours

d-limonene (CAS 5989-27-5)

**Acute** 

Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

d-limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Material name: LPS® PreSolve (Aerosol)

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. **Aspiration hazard** Prolonged exposure may cause chronic effects. **Chronic effects** 

#### 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

**Species Test Results** Components

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

2.9 mg/l, 96 hours

d-limonene (CAS 5989-27-5)

**Aquatic** 

EC50 Crustacea Water flea (Daphnia pulex) 69.6 mg/l, 48 hours

LC50 Fish Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours

Persistence and degradability Not inherently biodegradable.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

4.232 d-limonene

Mobility in soil Readily absorbed into soil.

Other adverse effects None known.

#### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

D003: Waste Reactive material

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

#### 14. Transport information

DOT

**UN number** UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

2.1

Subsidiary risk Label(s) 2.1

Not available. Packing group

**Environmental hazards** 

**Class** 

Marine pollutant No

Special precautions for user Not available.

N82 Special provisions Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

**UN** number UN1950 UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

Environmental hazards No.

Special precautions for user Not available.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN number UN1950

**UN proper shipping name** Aerosols, flammable, MARINE POLLUTANT **Transport hazard class(es)** 

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

**Environmental hazards** 

Marine pollutant Yes
EmS F-D, S-U
Special precautions for user Not available.

Transport in bulk according to
Annex II of MARPOL 73/78 and

the IBC Code

#### DOT



IATA; IMDG



#### Marine pollutant



#### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Yes

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### 16. Other information, including date of preparation or last revision

 Issue date
 09-15-2015

 Revision date
 05-18-2017

Version # 04

01420 Version #: 04 Revision date: 05-18-2017 Issue date: 09-15-2015

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **Revision information**

Hazard(s) identification: Hazard statement Hazard(s) identification: Response Hazard(s) identification: GHS Symbols

Hazard(s) identification: Supplemental information

Toxicological information: Acute toxicity Toxicological information: Aspiration hazard Toxicological information: Ingestion

Regulatory Information: Risk Phrases - Labeling

GHS: Classification

SDS US

01420 Version #: 04 Revision date: 05-18-2017 Issue date: 09-15-2015