Don Forda B172783

Safety Data Sheet

Revision Date 01-20-2016 Revision Number 11

DAUBERT CHEMICAL COMPANY. INC.

SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier

3009 TECTYL® 506

Details of the supplier of the safety

data sheet

Daubert Chemical Company

4700 S. Central Avenue Chicago, IL 60638

708-496-7350

Emergency telephone number

Relevant identified uses of the substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols





GHS Classification

Hazard Statements

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2B

Flammable Liquid Category 3

Specific Target Organ Systemic Toxicity (STOT) -

Single Exposure Category 3

Warning

Flammable liquid and vapour. Causes skin and eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Signal Word

Keep away from heat/sparks/open flames/hot

surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof equipment. Use only non-sparking tools.

Take precautionary measures against static

discharge.


Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

TECTYL® 506

Page 1 of 7



Safety Data Sheet

Revision Date 01-20-2016 Revision Number 11 **SECTION 5 Firefighting measures** Extinguishing media Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. Fire and/or Explosion Hazards Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Fire Fighting Methods and Protection Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire. **Hazardous Combustion Products** Carbon dioxide, Carbon monoxide, Sulfur compounds, Hydrocarbons **SECTION 6 Accidental release measures** Personal precautions, protective Exposure to the spilled material may be irritating or harmful. Follow equipment and emergency procedures personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Methods and materials for containment Prevent the spread of any spill to minimize harm to human health and and cleaning up the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. **SECTION 7 Handling and storage** Precautions for safe handling Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Conditions for safe storage, including any Store in a cool dry place. Isolate from incompatible materials. incompatibilities Keep container closed when not in use. Keep away from heat, sparks, and flame.

Strong oxidizing agents, Strong acids

Page 3 of 7

TECTYL® 506

Incompatible materials

<u> </u>	<u>.</u>	<u>.</u>	 <u> </u>

Safety Data Sheet

Revision Date 01-20-2016 Revision Number 11

Decomposition Temperature

No data available

Viscosity

80 cSt @ 40°C

Volatiles, % by weight

VOC, lb/gal

3.21

VOC, grams/liter

385.0

VOC minus exempt solvents & water, 3.21

lb/gal

SECTION 10 Stability and reactivity

Chemical stability

Stable under normal conditions. Hazardous polymerization

will not occur.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

Contamination. Elevated temperatures.

Incompatible materials

Strong oxidizing agents, Strong acids

Hazardous decomposition products

Under normal conditions of use & storage, decomposition and

hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Likely Routes of Entry

Inhalation, Skin contact, Eye contact

Target Organs Potentially Affected by Exposure

Central Nervous System, Respiratory Tract, Skin, Eyes,

Kidneys, Liver, Nervous System

Chemical Interactions That Change Toxicity

Medical Conditions Aggravated

No chemical interaction known to affect toxicity.

Skin contact may aggravate existing skin disease, Respiratory

disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Other possible symptoms include; wheezing and coughing due to pulmonary

edema (fluid build-up in lungs).

Skin Contact Eye Contact

Can cause minor skin irritation, defatting, and dermatitis.

Can cause moderate irritation, tearing and reddening, but not likely to permanently injure

Ingestion Irritation

Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical

pneumonitis which can be fatal.

Ingestion Toxicity

Harmful if swallowed.

Long-Term (Chronic) Health Effects

Carcinogenicity

Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Inhalation

Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Skin Contact

Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Ingestion

Under normal industrial usage conditions, ingestion is highly unlikely.

Page 5 of 7 TECTYL® 506

_ 					
		· ···	- · · · · · · · · · · · · · · · · ·		
	<u> </u>	<u></u>		<u> </u>	·

Safety Data Sheet

Revision Date 01-20-2016 Revision Number 11

Chemical Name No CERCLA-listed chemicals in this product.	CAS#	Regulation CERCLA	Percent
No 313-listed chemicals in this product.	- Artista	SARA 313	
No SARA 302 EHS-listed chemicals in this product.	•	SARA EHS	

SECTION 16 Other information

Revision 01-20-2016

Date

Disclaimer

Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage. Reviewed

Version

Approved: J. Kump Comments

TECTYL® 506 Page 7 of 7

					•		
-							
÷							
		· ·	· · · · · · · · · · · · · · · · · · ·	· · ·		· · · · · · · · · · · · · · · · · · ·	· · · · · · ·
# 							
· · · · · · · · · · · · · · · · · · ·							<u></u>
	<u> </u>						