

Material Safety Data Sheet

Print Date 30-Mar-2011 Revision Date 30-Mar-2011 Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Common nameNO. 56 THINNERProduct codeF041-0056Trade nameTHINNER CLEARProduct ClassPAINT THINNER

ManufacturerTnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372Emergency telephone800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

COMBUSTIBLE LIQUID AND VAPOR. HARMFUL IF INHALED. HARMFUL OR FATAL IF SWALLOWED.

MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes Moderately irritating to the eyes.

Skin Irritating to skin.

Inhalation Irritating to respiratory system.

Ingestion May be harmful if swallowed. Do not induce vomiting: may contain petroleum distillates

and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis.

Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Skin disorders. Respiratory disorders.

Interactive effects

Use of alcoholic beverages may enhance toxic effects.

Potential environmental effects

See Section 12 for additional Ecological Information

Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
P-CHLOROBENZOTRIFLUORIDE	98-56-6	60 - 100
METHYL N-AMYL KETONE	110-43-0	10 - 30

4. FIRST AID MEASURES

Eye contact: Rinse thoroughly with plenty of water for at least 15 minutes.

Skin contact: Wash off immediately with soap and plenty of water.

Ingestion: If swallowed, do not induce vomiting. Get medical attention immediately.

Inhalation: Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties Combustible material.

environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO2) -

Foam - Dry chemical

Hazardous decomposition products Oxides of carbon, hydrocarbons. Chlorine. Fluorine.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all

sources of ignition.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary

sewer system.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated

absorbent, container and unused contents in accordance with local, state and federal

regulations.

Other information Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
P-	TWA: 2.5 mg/m ³		TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	
CHLOROBENZOTRIFLUORI	G			G	
DE					
METHYL N-AMYL KETONE	: 50 ppm TWA	: 100 ppm TWA; 465	TWA: 50 ppm TWAEV;	TWA: 25 ppm TWA;	: 50 ppm TWA; 235
		mg/m³ TWA	233 mg/m³ TWAEV	115 mg/m³ TWA	mg/m ³ TWA: 100 ppm
					STEL: 465 ma/m ³ STEL

Engineering measures Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection Eye/face protection Respiratory protection Lightweight protective clothing, Apron, Impervious gloves

Safety glasses with side-shields

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or

dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application.

Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point 42°C / 107.0°F

Boiling range 139 - 154°C / 282.0 - 309.0°F
Upper explosion limit No information available
Lower explosion limit No information available
Evaporation rate No information available
Vapor pressure No information available
Vapor density No information available

Specific Gravity

1.17154 g/cm3

Density

9.74899 lbs/gal

Volatile organic compounds (VOC) content

4.203 lbs/gal

Volatile by weight 4.203 lbs/ga 89.0780 %
Volatile by volume 86.2624 %

10. STABILITY AND REACTIVITY

Chemical stability Stable. Conditions to avoid Heat, flames and sparks.

Incompatible products Strong oxidizing agents. Possibility of hazardous None under normal processing

reactions

11. TOXICOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
P-CHLOROBENZOTRIFLUORIDE	13 g/kg (Rat)	2 mg/kg (Rabbit)	33 mg/L (Rat) 4 h	
METHYL N-AMYL KETONE	1670 mg/kg (Rat)	12600 µL/kg (Rabbit)		

IrritationNo information availableCorrosivityNo information availableSensitizationNo information available

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

MutegenicityNo information availableReproductive effectsNo information availableDevelopmental effectsNo information availableTeratogenicityNo information available

Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.

Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

.

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
P-			EC50 = 11.1 mg/L 5 min EC50	EC50 = 3.68 mg/L 48 h
CHLOROBENZOTRIFLUORI			= 13.4 mg/L 15 min EC50 =	-
DE			14.3 mg/L 30 min	
METHYL N-AMYL KETONE		LC50 126-137 mg/L	-	
		Pimephales promelas 96 h		

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert

absorbent. Dispose of contaminated absorbent, container and unused contents in accordance

with local, state and federal regulations.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other

modes of Transportation.

Proper shipping name UN1263,PAINT RELATED MATERIAL,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

EINECS/ELINCS Does not Comply

CHINA Complies

ENCS Does not Comply

KECL Complies

PICCS Does not Comply AICS Does not Comply

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61): United States of America Federal Regulations

SARA 313

SARA 311/312 Hazardous Categorization

Chronic Health HazardnoAcute Health HazardyesFire HazardyesSudden Release of Pressure HazardnoReactive Hazardno

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
P-CHLOROBENZOTRIFLUORIDE		X		

CERCLA

United States of America State Regulations

California Prop. 65

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Otate Night-to-Milow						
Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island	
P-		X	X		X	
CHLOROBENZOTRIFLUORI						
DE						
METHYL N-AMYL KETONE	X	X	X		X	

Other international regulations

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification

B3 Combustible liquid D2B Toxic materials



Leaend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date 30-Mar-2011

Revision Note No information available

HMIS (Hazardous Material Health 2 Flammability 2 Reactivity 1

Information System)

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS