



Material Safety Data Sheet

Print Date 11-Apr-2011

Revision Date 11-Apr-2011

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Common name THINNER NO.26
Product code F041-0026
Trade name THINNER CLEAR
Product Class PAINT THINNER
Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency telephone 800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes Moderately irritating to the eyes.
Skin Irritating to skin.
Inhalation Irritating to respiratory system.
Ingestion May be harmful if swallowed. Do not induce vomiting: may contain petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis.

Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions No information available

Interactive effects No information available

Potential environmental effects See Section 12 for additional Ecological Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
-----------	--------	----------

3. COMPOSITION/INFORMATION ON INGREDIENTS

ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	2807-30-9	30 - 60
--	-----------	---------

4. FIRST AID MEASURES

Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin contact:	Wash off immediately with soap and plenty of water.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation:	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties	Combustible material.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous decomposition products	Oxides of carbon, hydrocarbons.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)				TWA: 25 ppm TWA; 110 mg/m ³ TWA Skin	

Engineering measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face protection

Safety glasses with side-shields

Respiratory protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	57°C / 135.0°F
Method	Pensky Martens - Closed Cup
Boiling range	100 - 154°C / 212.0 - 310.0°F
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	.96406 g/cm ³
Density	8.02245 lbs/gal
Volatile organic compounds (VOC) content	7.600 lbs/gal
Volatile by weight	100.0000 %
Volatile by volume	100.0000 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to avoid	Heat, flames and sparks.
Incompatible products	Strong oxidizing agents.	Possibility of hazardous reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
-----------	-----------	-------------	-----------------

11. TOXICOLOGICAL INFORMATION

ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	3089 mg/kg (Rat)	960 µL/kg (Rabbit)	
--	--------------------	----------------------	--

Irritation No information available
Corrosivity No information available
Sensitization No information available

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenicity No information available
Reproductive effects No information available
Developmental effects No information available
Teratogenicity No information available
Target Organ Effects No information available
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION**Ecotoxicity**

.

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name PAINT & RELATED MATERIAL-(NMFC 149980 SUB2)

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Complies
AICS	Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component

ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)

United States of America Federal Regulations**SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	2807-30-9	30 - 60	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	yes
Acute Health Hazard	yes
Fire Hazard	yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

CERCLA**United States of America State Regulations****California Prop. 65**

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)		X	X	X	

Other international regulations**Canada**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification

B3 Combustible liquid

D2B Toxic materials

**Legend**

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION**Revision Date** 11-Apr-2011**Revision Note** No information available

HMIS (Hazardous Material
Information System)

Health 2

Flammability 2

Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS