

## Silver-Copper-Tin-Zinc Alloys

## Material Safety Data Sheet

## 1. Product and Company Identification

## Suppliers and Manufacturers

Lucas-Milhaupt, Inc.  
5656 South Pennsylvania Avenue  
Cudahy, WI 53110 USA  
Telephone: 414-769-6000  
www.lucasmilhaupt.com

Lucas-Milhaupt Toronto  
290 Carlingview Drive  
Rexdale, ON M9W 5G1 Canada  
Telephone: 416-675-1860  
www.lucasmilhaupt.com

## Emergency Phone Number

Chemtrec: 800-424-9300

Issue Date: 12/11/2012

Product Name: Silver-Copper-Tin-Zinc Alloys

MSDS Number: 93

Product Codes: 15-801; 28-685; 32-255; 32-340; 32-380; 32-402; 32-452  
32-550; 32-560; 32-565; 39-565; 40-057.

## 2. Composition/Information on Ingredients

Ingredient Name	CAS Number	%
Copper	7440-50-8	4-41
Silver	7440-22-4	24-81
Tin	7440-31-5	1-26
Zinc	7440-66-6	1-35

## 3. Hazards Identification

## Primary Routes(s) of Entry

Ingestion; inhalation.

## Eye Hazards

Eye contact with these products in finely-divided forms may cause irritation, conjunctivitis, ulceration of the cornea, and/or argyria, a blue-gray discoloration of the eyes, skin, mucous membranes, and respiratory tract.

## Skin Hazards

Skin contact with these products, particularly in finely-divided forms, may cause irritation, argyria, discoloration, and/or contact dermatitis.

## Ingestion Hazards

-----  
Ingestion of these products in finely-divided forms may cause nausea, vomiting, and gastrointestinal irritation.

#### Inhalation Hazards

-----

Inhalation of the components of these products is not known to present a significant risk to health when used according to instructions and with appropriate protective measures (see Section #8). Inhalation of component elements has been reported to cause one or more of the following symptoms and effects upon excessively high or prolonged exposure:

COPPER: Acute exposure may cause respiratory tract irritation, fever, muscle ache, chills, cough, weakness, and a metallic taste. Chronic exposure may damage the liver, kidney, spleen, pancreas, and brain.

SILVER: Chronic exposure via inhalation may cause argyria.

TIN: Exposure to tin dust or fume by inhalation may cause stannosis (a benign pneumoconiosis), shortness of breath, and respiratory tract irritation.

ZINC: Acute exposure to zinc oxide may cause respiratory tract irritation and "metal fume fever", which is characterized by a metallic taste, cough, dry throat, chills, fever, tightness of chest, headache, nausea, shortness of breath, vomiting, and fatigue.

#### 4. First Aid Measures

-----

##### Eye

---

Flush affected areas with water for at least fifteen minutes. Seek medical assistance if necessary.

##### Skin

----

Remove contaminated clothing. Wash affected area with large quantities of water for at least five minutes. Seek medical attention if necessary. Launder or dry-clean clothing before reuse.

##### Ingestion

-----

If subject is conscious, induce vomiting. If unconscious or convulsive, seek immediate medical attention.

##### Inhalation

-----

If signs and symptoms of toxicity are observed, remove subject from area, administer oxygen, and seek medical attention. Keep the subject warm and at rest. Perform artificial respiration if breathing has stopped.

##### Note to Physician

-----

None of the components are acutely toxic by ingestion, nor are they absorbed through the skin. Extensive or prolonged skin contact may cause dermatitis

and/or argyria.

## 5. Fire Fighting Measures

Flash Point: Not Applicable (N/Appl.)

Autoignition Point: N/Appl.

Flammability Class: N/Appl.

Lower Explosive Limit: N/Appl.

Upper Explosive Limit: N/Appl.

## Fire and Explosion Hazards

In finely-divided form, the products may ignite when exposed to flame or by reaction with incompatible materials (see Section #10). If present in a fire or explosion, they may emit fumes of the constituent metals or metal oxides.

## Extinguishing Media

Use dry chemical. Do not use water.

## Fire Fighting Instructions

If fighting a fire in which this product is present, wear a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode.

## 6. Accidental Release Measures

If a finely-divided form of product is spilled, clean up spillage so as to minimize dispersion of dust. Wet sweeping or vacuuming using HEPA filtration is recommended.

## 7. Handling and Storage

### Handling Precautions

No special handling precautions are required.

### Storage Precautions

Store away from incompatible materials (see Section #10).

### Work/Hygienic Practices

To minimize ingestion, wash hands and face before eating, drinking, applying cosmetics, or using tobacco.

## 8. Exposure Controls/Personal Protection

### Engineering Controls

Use appropriate ventilation (e.g., dilution, local exhaust) adequate to

maintain concentrations of all components and their byproducts to within their applicable standards.

#### Eye/Face Protection

Wear eye protection adequate to prevent eye contact with finely-divided forms of product and eye injury if products are used with a flame. Plastic-frame spectacles with side shields and filter lenses (shade #3/#4) are recommended.

#### Skin Protection

Wear appropriate protective gloves and clothing to prevent skin injury if these products are used with a flame and/or for prolonged or repeated contact with finely-divided forms of product. Avoid flammable fabrics.

#### Respiratory Protection

If an exposure level exceeds an applicable exposure standard, use a NIOSH-approved respirator having a configuration (type of facepiece, filter media, assigned protection factor, etc.) appropriate to the concentration of the contaminant(s) generated. For guidance on selection and use of respirators, consult American National Standard Z88.2 (ANSI, New York, NY 10036 USA).

#### Ingredient(s) - Exposure Limits

##### Copper

ACGIH TLVs: 0.2 mg/m<sup>3</sup> TWA (fume); 1 mg/m<sup>3</sup> TWA (dusts and mists)

OSHA PELs: 0.1 mg/m<sup>3</sup> TWA (fume); 1 mg/m<sup>3</sup> TWA (dusts and mists)

##### Silver

ACGIH TLV: 0.1 mg/m<sup>3</sup> TWA (metal)

OSHA PEL: 0.01 mg/m<sup>3</sup> TWA

##### Tin

ACGIH TLV: 2 mg/m<sup>3</sup> TWA (as Sn)

OSHA PEL: 2 mg/m<sup>3</sup> TWA (as Sn)

##### Zinc

ACGIH TLVs (as ZnO): 2 mg/m<sup>3</sup> TWA; 10 mg/m<sup>3</sup> STEL (respirable fractions)

OSHA PEL: 5 mg/m<sup>3</sup> TWA (as ZnO fume)

#### 9. Physical and Chemical Properties

Appearance: white to light-yellow metals, various forms

Odor: no odor

Chemical type: alloy

Physical state: solid

Melting point: 1145-1270F./620-690C.

Specific gravity: 8.7-9.4

Solubility (H<sub>2</sub>O): insoluble

Other commonly-reported physical properties (odor threshold, evaporation rate, vapor pressure, vapor density, freezing point, viscosity, oil-water partition coefficient, percent volatiles, percent VOCs) are not applicable to these products.

#### 10. Stability and Reactivity

Stability: stable

Hazardous Polymerization: will not occur

#### Conditions to Avoid

Silver and copper can form unstable acetylides in contact with acetylene gas.

#### Incompatible Materials

Strong oxidizers; ammonia; azides; nitric acid; ethylene imine; chlorine trifluoride; bromine trifluoride; sulfuric acid; inorganic and organic peroxides; peroxyformic acid; oxalic acid; tartaric acid; 1-bromo-2-propyne; permonosulfuric acid; bromates, chlorates, and iodates of alkali and alkali earth metals; halogens; carbon disulfide; hydrazine mononitrate; selenium; hydroxylamine; tellurium; cupric nitrate; sulfur.

#### Hazardous Decomposition Products

Heating to elevated temperatures may liberate metal/metal oxide fumes.

### 11. Toxicological Information

#### Carcinogenicity

These products contain no chemicals classified as potential or demonstrated carcinogens by IARC, NTP, or OSHA.

#### Conditions Aggravated by Overexposure

Pre-existing pulmonary diseases (e.g., bronchitis, emphysema) may be aggravated by inhalation overexposure, particularly as fume. Chronic overexposure by inhalation and/or ingestion may aggravate pre-existing diseases of the liver, kidneys, gastrointestinal system, and nervous system.

#### Ingredient(s) - Toxicological Data

##### Copper

LD50: No data available

LC50: No data available

##### Silver

LD50: >2,000 mg/kg (oral/rat)

LC50: No data available

##### Tin

LD50: No data available

LC50: No data available

##### Zinc

LD50: No data available

LC50: No data available

### 12. Ecological Information

In their intended manner of use, these products should not be released into the environment, and adverse effects on ecosystems are not anticipated under recommended conditions of use, storage, and disposal.

### 13. Disposal Considerations

-----  
Dispose of unused or unusable product in accordance with applicable Federal, State/Provincial, and local regulations.

#### 14. Transport Information

-----

These products are not Hazardous Substances or Dangerous Goods per USDOT, TDG (Canada), IATA, or IMO regulations.

#### 15. Regulatory Information

-----

##### TSCA Information

-----

All components of these products are listed in the EPA's TSCA inventory.

##### SARA Hazard Classes

-----

Acute Health Hazard; Chronic Health Hazard

##### Ingredient(s) - U.S. Regulatory Information

-----

These products contain these ingredients in concentrations greater than 1% (for carcinogens 0.1%) regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

1. Copper (CASRN 7440-50-8)
2. Silver (CASRN 7440-22-4)

##### Canadian Regulatory Information

-----

All components of these products are listed on either the Domestic Substances List (DSL) or the Nondomestic Substances List (NDSL).

WHMIS Class(es) and Division(s): D2B

Component(s) on Ingredients Disclosure List:

1. Copper, elemental (CASRN 7440-50-8)
2. Silver, elemental (CASRN 7440-22-4)
3. Tin, elemental (CASRN 7440-31-5)

#### 16. Other Information

-----

##### HMIS Ratings

-----

Health - 1\*      Flammability - 1      Physical Hazard - 1      PPE - see Note

Note: Lucas-Milhaupt, Inc. and Lucas-Milhaupt Toronto recommend use of safety glasses and protective gloves (Personal Protection Index "B") as standard PPE. HMIS recommends that its ratings be used only in conjunction with a fully implemented HMIS program, and that specific PPE codes be created by the user, who is familiar with the actual conditions under which the product is used. We cannot anticipate every condition of the product's use, and it is the user's responsibility to evaluate the hazards pertinent to its specific operations, and to determine the specific PPE required.

## NFPA Ratings

Health - 1 Flammability - 1 Reactivity - 1

## Revision Information

This MSDS supersedes a previous MSDS dated 6/01/2010.

## Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Lucas Milhaupt, Inc.

Lucas-Milhaupt Toronto