



# Material Safety Data Sheet

**CHEMTREC Transportation Emergency Phone:**  
**800-424-9300**  
**Pittsburgh Poison Control Center Health**  
**Emergency No.: 412-681-6669**

NOTE: The CHEMTREC Transportation Emergency Phone is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals

## 1. Identification

**Product Name:** BITUMASTIC 300 M PART B **Revision Date:** 7/15/2013

**Identification Number:** 0165B5NL **Supersedes Date:** 6/14/2011

**Product Use/Class:** Coal Tar Epoxy - FOR INDUSTRIAL USE ONLY

**Manufacturer:** Carboline Company  
 2150 Schuetz Road  
 St. Louis, MO 63146  
 800-848-4645

**Preparer:** Regulatory Department

## 2. Hazard Identification

**EMERGENCY OVERVIEW:** WARNING! May cause allergic skin reaction. May cause sensitization by skin contact. May be harmful if swallowed. Irritating to eyes and skin.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** May cause eye irritation.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin irritation. May cause allergic skin reaction. May cause sensitization by skin contact.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Vapours may be irritating to eyes, nose, throat, and lungs.

**EFFECTS OF OVEREXPOSURE - INGESTION:** May be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** May cause sensitization by skin contact.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION:** No information available.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

## 3. Composition/Information On Ingredients

### Hazardous Ingredients

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
EPOXY RESIN	25068-38-6	100.0	N/E	N/E	N/E	N/E

## 4. First-aid Measures

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

## 5. Fire-fighting Measures

Flash Point, °F:	490F (254C)	Lower Explosive Limit, %:	N/A
(Setaflash)		Upper Explosive Limit, %:	N/A
Extinguishing Media:	Carbon Dioxide, Dry Chemical, Foam, Water Fog		

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None known.

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate personnel to safe areas. The product is not flammable. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus.

## 6. Accidental Release Measures

**PERSONAL SAFETY MEASURES/ENVIRONMENTAL MEASURES/METHOD OF CLEANING/CONTAINMENT:** Wear personal protective equipment. For personal protection see section 8. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not allow material to contaminate ground water system. Prevent product from entering drains.

## 7. Handling and Storage

**INSTRUCTIONS FOR SAFE HANDLING :** Avoid breathing vapors, mist or gas. Do not get in eyes, on skin, or on clothing. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 8. Exposure Controls/Personal Protection

**ENGINEERING CONTROLS:** Use only in an area equipped with explosion proof exhaust ventilation. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

**RESPIRATORY PROTECTION:** Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.

**SKIN PROTECTION:** Lightweight protective clothing. Impervious gloves. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Request information on glove permeation properties from the glove supplier.

**EYE PROTECTION:** Safety glasses with side-shields

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

**9. Physical and Chemical Properties**

<b>Boiling Range:</b>	N/A	<b>Vapor Density:</b>	Heavier than Air
<b>Odor:</b>	Mild Odor	<b>Odor Threshold:</b>	N/D
<b>Appearance:</b>	Viscous Clear to Amber Liquid	<b>Evaporation Rate:</b>	Slower Than Ether
<b>Solubility in Water:</b>	N/D	<b>Specific Gravity:</b>	1.16
<b>Freeze Point:</b>	N/D	<b>pH:</b>	N/D
<b>Physical State:</b>	Liquid	<b>Vapor Pressure:</b>	No Information

(See section 16 for abbreviation legend)

**10. Stability and Reactivity**

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**MATERIALS TO AVOID:** Strong oxidizing agents

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

**HAZARDOUS POLYMERIZATION:** Hazardous polymerisation does not occur.

**STABILITY:** Stable under normal conditions.

**11. Toxicological Information**

Chemical Name	CAS-No.	LD50	LC50
EPOXY RESIN	25068-38-6	30000 mg/kg, rat, oral	>20 mL/kg skin, sensitizer

**12. Ecological Information**

**ECOLOGICAL INFORMATION:** No information available.

**13. Disposal Information**

**DISPOSAL INFORMATION:** Dispose of in accordance with local regulations.

**14. Transport Information**

<b>DOT Proper Shipping Name:</b>	Not Regulated	<b>Packing Group:</b>	N/A
<b>DOT Technical Name:</b>	N/A	<b>Hazard Subclass:</b>	N/A
<b>DOT Hazard Class:</b>	None	<b>Resp. Guide Page:</b>	N/A
<b>DOT UN/NA Number:</b>	N/A		
<b>Additional Notes:</b>	This product is considered a Marine Pollutant when transported by vessel.		

**15. Regulatory Information**

## U.S. Federal Regulations:

### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## U.S. State Regulations:

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

### Pennsylvania Right-To-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

### CALIFORNIA PROPOSITION 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

## International Regulations:

### CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS Class: D2B

**16. Other Information****HMIS Ratings:**

**Health:** 2      **Flammability:** 1      **Reactivity:** 0      **Personal Protection:** X

**VOLATILE ORGANIC COMPOUNDS, GR/LTR MIXED (UNTHINNED): 222**

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.