# MATERIAL SAFETY DATA SHEET

**Identity:** Visionaid Rainbow II

Company Product Code: LCL211B, LCL211BR, LCL211E, LCL2112, LCL211C,

1LC1776DU, LC5000D, 1LC3000D, LC382D, 1LCT200, 1LCT100

**Sizes:** 3.8L (128 fl. oz.), 473 ml (16 fl. oz.), 103 ml (3.5 fl. oz.), 59 ml (2 fl. oz.)

Product Use: Lens Cleaner

| Supplier: H. L. Bouton Co. 11 Kendrick Rd. Wareham, Ma. 02571 | Information Phone 1-800-426-1881 (business hours) Fax 1-508-295-3521  Emergency Phone 1-800-268-9017 (Poison Information Center) |
|---|--|
| Date Prepared March 25, 2008                                  | ,  |

| Date Prepared | March 25, 2008   |
|---------------|------------------|
| Prepared by   | H. L. Bouton Co. |

| Section II Material Identification and Information  |                |       |      |       |       |
|---|----------------|-------|------|-------|-------|
| Components (Chemical Names & Common Names) (Hazardous Components 1 % or greater, Carcinogens 0.1% or greater) | CAS #'s        | %     | OSHA | ACGIH | OTHER |
| Isopropanol   | 67-63-0        | 10    |      |       |       |
| Sodium Dodecyl Sulphate   | 151-21-3       | 2.5   |      |       |       |
| Hydrogen Hydroxide  | 7732-18-5      | 87.5  |      |       |       |
| Pylaklor Turquoise Blue S-400   | N/A<br>mixture | .0036 |      |       |       |

| Section III Physical / Chemical Characteristics |   |  |  |  |  |
|---|---|--|--|--|--|
| Physical State: Liquid                          | Specific Gravity (H2O=1) 1.00             |  |  |  |  |
| PH Factor: N/A                                  | Freezing point: -6°C (21°F)               |  |  |  |  |
| Boiling Point: 93°C (200°F)                     | Melting Point: -6°C (21°F)                |  |  |  |  |
| Vapor Pressure 20 mmHg at 20°(68°F)             | Evaporation Rate: 0.99                    |  |  |  |  |
| Vapor Density 1                                 | Water Reactive: None                      |  |  |  |  |
| Solubility in Water: 100%                       | Specific Gravity (Relative Density): 0.98 |  |  |  |  |
| Percent Volatile: 10%                           |   |  |  |  |  |

Appearance and Odor: Clear blue solution. Slight alcoholic odor

| 11  |                                |
|---|--------------------------------|
| Section IV Fire and Explosion Da                | ata                            |
| Flash Point (Method Used): 82° C (180°F)        | Auto-Ignition Temperature: N/A |
| Flammability Classification                     |                                |
| (29 CFR 1910.1200): Combustible Liquid          |                                |
| Flammability Limits in Air Lower: 2.5-12.0      | LEL: N/A                       |
| (Isopropanol)                                   |                                |
| Autoflammability and Autoignition Temperature:  |                                |
| 456°C (852°F) (Isopropanol)                     |                                |
| Extinguisher Media: Carbon Dioxide, Water, Foam |                                |

Special Fire Fighting Procedures: None Unusual Fire and Explosion Hazards: None

**Extinguishing Media** 

Suitable Extinguishing Media: Alcohol foam, dry chemical, carbon dioxide, water fog.

Stability
Unstable: No
Stable: Yes
Conditions to Avoid: High temperatures, flame and other ignition sources

Incompatibility (Materials to Avoid): Strong Oxides of carbon

Hazardous Decomposition Products: Oxides of carbon (Coχ).

Significance of change in physical appearance: Under severely cold temperatures product may begin to turn cloudy which may degrade its

functionality.

Conditions Of Reactivity: Do not heat above 80°C (176°F).

## Section VI Health Hazard Data-Potential Acute Health Affects

### **INHALATION**

Single Exposure Severity, Target Organs and Type of Effect: High levels may cause headache, nausea, dizziness.

Repeated Exposure Severity, Target Organs and Type of Effect: No longterm effects expected.

### **INGESTION**

Single Exposure Severity, Target Organs and Type of Effect: Mildly toxic by ingestion. May cause nausea, headache and vomiting.

### SKIN ABSORPTION

Single Exposure Severity, Target Organs and Type of Effect: No effects expected.

#### **Section VII - Health Hazard Data**

Eye Contact: Flush with plenty of water for at least fifteen minutes. If irritation persists, consult a physician.

Repeated Exposure Severity, Target Organs and Type of Effect: Corneal thickening leading to scarring from repeated eye contact.

Skin Contact: May cause mild irritations, drying out of skin. Wash thoroughly with soap and water.

Inhalation: Move to fresh air. If dizziness persists, consult physician.

Ingestion: May cause stomach discomfort if ingested. Seek medical advice.

### **Section VIII – Control and Protective Measures**

Respiratory Protection (Specify Type): None

Hygiene recommendations to prevent continued exposure: Use normal good industrial hygiene Practices

Protection Gloves: None Eye Protection: Safety Glasses

Ventilation to be used: N/A Local Exhaust: N/A Special: N/A

Mechanical (General): N/A Other: N/A

Other Protective Clothing and Equipment: Not required.

Hygienic Work Practices: Always read label before use.

### Section IX- Precautions for Safe Handling and Use/Leak Procedures

Steps to be taken if Material is Spilled or Released: Mop up using large amounts of water. Flush Down sanitary sewer.

| Waste Disposal Methods: In acco       | rdance with municipal, provincial and federal regulations.              |  |  |  |  |
|---------------------------------------|---|--|--|--|--|
|                                       | g and storage: Keep away from excessive heat.                           |  |  |  |  |
|                                       | Hazards: Keep from freezing. Read label before using.                   |  |  |  |  |
|                                       | ammability: 1 Reactivity: 0 Personal Protection: b                      |  |  |  |  |
|                                       | immability: 1 Reactivity: 0 Special: 0                                  |  |  |  |  |
| Training. Treatm. 1 The               | CANADIAN REGULATIONS  |  |  |  |  |
| WHMIS Class: B3 – Combustible         |   |  |  |  |  |
| WHMIS Class: D2B- Toxic: Eye          | •   |  |  |  |  |
|                                       | FIRE FIGHTING MEASURES  |  |  |  |  |
|                                       | FLAMMABLE PROPERTIES  |  |  |  |  |
| Flammability Classification (29 C     | FR 1910.1200): Combustible liquid.                                      |  |  |  |  |
| Flash Point and Method: 82° C (1      | 180°F)  |  |  |  |  |
| Flammable Limits in Air- 2.5% -1      | 2.0% (Isopropanol)  |  |  |  |  |
| AutoFlammability and Autoignition     | on Temperature: 456°C (852°F) (Isopropanol)                             |  |  |  |  |
| •                                     | EXTINGUISHING MEDIA   |  |  |  |  |
| Suitable Extinguishing Media: Ale     | cohol foam, dry chemical, carbon dioxide, water fog.                    |  |  |  |  |
|                                       | ACCIDENTAL RELEASE MEASURES   |  |  |  |  |
| Containment Technique:                | Prevent from entering waterways and storm sewers.                       |  |  |  |  |
| Clean-Up Technique:                   | Contain spill. Cover spill with inert absorbent (absorball,             |  |  |  |  |
| vermiculate). Using non-sparking      | g tools, shovel or sweep up into a clean container. Remove from area.   |  |  |  |  |
| spill area with water.                |   |  |  |  |  |
| Evacuation Procedures:                | Follow normal Emergency Response Plan (ERP).                            |  |  |  |  |
|                                       | HANDLING AND STORAGE  |  |  |  |  |
|                                       | HANDLING  |  |  |  |  |
| Handling Practices:                   | Use grounding wires if transferring large quantities. Keep              |  |  |  |  |
|                                       | away from oxidizers, heat and other ignition sources. Do not            |  |  |  |  |
|                                       | allow to freeze.  |  |  |  |  |
|                                       | STORAGE   |  |  |  |  |
| Conditions For Safe Storage:          | Keep away from oxidizers, heat and other ignition sources.              |  |  |  |  |
|                                       | Do not store in direct sunlight. Store in cool, dry well-               |  |  |  |  |
| Vantilation Deguinements              | ventiliated area. Do not allow to freeze.                               |  |  |  |  |
| Ventilation Requirements For Storage: | None required.  |  |  |  |  |
| Storage Temperature                   | None required.  |  |  |  |  |
| Range:                                | Below 40°C (104°F)  |  |  |  |  |
| Storage Humidity Range:               | Not applicable  |  |  |  |  |
| Quantity Limits for Safe Storage:     | **  |  |  |  |  |
|                                       | or Packaging or Containers: Not applicable                              |  |  |  |  |
| Transport Information: Not regu       |   |  |  |  |  |
| NOTE                                  |   |  |  |  |  |
|                                       | ce Hazardous Materials Information System training is required for      |  |  |  |  |
| <b>O</b> 1                            | n Canadian workplaces. U.S. OSHA requirements for handling              |  |  |  |  |
|                                       | lace for handling and using this product in the United States.          |  |  |  |  |
|                                       | ions: Cleaning of clear surfaces. Check for compatibility with material |  |  |  |  |
| to be cleaned prior to use.           | ions. Croaming of creat surfaces. Check for compationity with material  |  |  |  |  |
| to be cleaned prior to use.           |   |  |  |  |  |

**DISCLAIMER:** This information is furnished without warranty, representation, or license of any kind, except that it is accurate to the best of H. L. Bouton Co., Inc.'s knowledge, or obtained from sources believed to be accurate. H. L. Bouton Co.,Inc. does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests and investigations. Before using the product, please read and understand the label and the Material Safety Data Sheet.