

#### **MATERIAL SAFETY DATA SHEET**

PRODUCT: TBF 9-50 PAGE: 01

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION .....

Manufactured By: Supplied By: Path Silicones, Inc. Path Silicones, Inc.

PO Box 430, Wallace St. Ext. PO Box 430, Wallace St. Ext. Elmwood Park, NJ 07407 Elmwood Park, NJ 07407

Emergency Phone: (201) 796-0833

Chemical Family/Use: Silicone Fluid Formula: Silicone Fluid

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

TLV OSHA PEL

Product Composition/ Approx. ACGIH CAS Reg No. Wgt. % TWA\_ STEL \_TWA STEL UNITS

A. HAZARDOUS Not a hazardous material as defined by OSHA Hazard Com-None Found

munication Standard.

B. NON-HAZARDOUS Dimethylpolysiloxane

> 100 NE 63148-62-9 NE NE NE NE

#### 3. HAZARDS IDENTIFICATION

# POTENTIAL HEALTH EFFECTS

Ingestion: None known. Skin Contact: None known. Inhalation: None known.

Eye Contact: May cause mild eye irritation.

**Medical Conditions** 

Aggravated:

None known.

Subchronic(Target

Organ) Effects:

None known.

**Chronic Effects/** 

Carcinogenicity: This product or one of its ingredients present 0.1% or

more is NOT listed as a carcinogen or suspected

carcinogen by NTP, IARC, or OSHA.

**Principle Routes** 

of Exposure: None known.

IBF 9-50	Path Silicones, in	c. Page 2		
4. FIRST AID MEASURES				
Ingestion: Skin: Inhalation: Eyes: Note to Phys	No first aid should be r No first aid should be r In case of contact, imm of water for at least 15 if irritation persists.			
5. FIRE FIGHTING MEASURES				
Meth Igniti Flam Flam Sens Sens Extir	n Point: nod: on Temp. nmable limits in air - lower (%) nmable limits in air - upper (%) sitivity to mechanical impact (Y/N) sitivity to static discharge: nguishing media: cial Firefighting Procedures:	>535°F, >302°C COC ND NA NA No Sensitivity to static discharge is not expected. Foam, dry chemical or carbon dioxide. A self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.		
6.	ACCIDENTAL RELEASE	MEASURES		
	f material is released or spilled: ak. Scrape up with cardboard, rag or disposal.	gs or absorbent material. Place in		
7. HANDLING AND STORAGE				

# Precautions to be taken in handling and storage:

Store in clean and cool area, away from oxidizing materials. Keep container closed. Keep away from heat, flame or sparks. Avoid contact with eyes and prolonged or repeated skin contact. Do not take internally. For industrial use only. Use with adequate ventilation.

TBF 9-50	Path Silicones, Inc.	Page 3
----------	----------------------	--------

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

------

Exposure Limits:

Engineering Controls:

Respiratory Protection:

No components with workplace exposure limits

Eyewash equipment and safety shower.

No respiratory protection should be needed.

Protective Gloves: Plastic film or rubber gloves

**Eye and Face Protection:** Safety glasses.

Other Protective Equip: Boots, apron or coveralls as necessary to prevent skin contact.

**Ventilation:** General ventilation recommended.

Other: Wash hands at meal time and end of shifts.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### -----

PRODUCT INFORMATION

Boiling Point >65°C >149°F

Vapor Pressure (20C) (MM Hg) <10 Vapor Density (Air = 1) >1.0 Freezing Point ND Melting Point ND Physical State Liquid Odor Odorless Color Clear Odor Threshold (PPM) UNK % Volatile By Weight NA Evaporation Rate (Butyl Acetate = 1) <1.0 Specific Gravity (Water = 1) 0.96

Solubility in Water (20C) Insoluble

\_\_\_\_\_\_

#### 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Will Not Occur

Hazardous Thermal Decomposition/

Combustion Products: Carbon oxides, Silicon dioxide, Formal

dehyde.

Incompatibility (Materials To Avoid)

Oxidizing materials

None Known

Conditions to Avoid: None Known

## 11. TOXICOLOGICAL INFORMATION

**Acute Toxicology Data:** 

Oral LD50 (rat) >50 ml/kg **Special Hazard Information:** None known

# 12. ECOLOGICAL INFORMATION

TBF 9-50 Path Silicones, Inc. Page 4

**Environmental Effects:** 

Bioaccumulation:

Toxicity to Water Organisms: Product is expected to exhibit low toxicity to aquatic organisms. Experiments showed that when sewage sludge containing poly-

Dimethylsiloxane is added to soil, it has no effect on soil micro-

Organisms, earthworms or subsequent crops grown in the soil.

Due to the physical size of its molecule, this product is unable to

pass through, or be absorbed by biological membranes. This

has

been confirmed by testing or by analogy with similar products.

# Fate and Effects in Waste Water treatment Plants:

This product or similar products has been shown to be non-toxic to sewage sludge bacteria.

# .....

#### 13. DISPOSAL CONSIDERATIONS

-----

#### RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, it is not classified as hazardous waste.

<u>Disposal Method:</u> Disposal should be made in accordance with federal, state and local regulations. Do not discharge into waterways or sewer systems.

.....

#### 12. TRANSPORT INFORMATION

\_\_\_\_\_\_

DOT Shipping Name
DOT Hazard Class
None
DOT Label(s)
UN/NA Number
Placards
IATA:
NA
None
IMO IMDG-Code
None

European Class:

RID (OCTI)

ADR (ECE)

RAR (IATA)

None

------

#### 13. REGULATORY INFORMATION

------

This MSDS is in compliance with the OSHA Hazard Communication Standard 29 CFR 1910.1200

**TSCA Status:** All chemicals in this material are included or exempted

from listing on TSCA Inventory of Chemical Substances.

SARA Section 302:

CERCLA Section 304:

None
SARA (311,312) Hazard Class:

None
SARA (313) Chemicals:

CPSC Classification:

None

WHMIS Hazard Class: Non-Controlled

WHMIS Trade Secret: None

**Export:** 

Schdle B/HTSUS: 3910.00.00003

**ECCN:** 1C96G

TBF 9-50 Path Silicones, Inc. Page 5

**Hazard Rating Systems:** 

**HMIS:** Flammability: 1; Reactivity: 0; Health: 0 **NFPA:** Flammability: 1; Reactivity: 0; Health: 0

.....

#### 14. OTHER INFORMATION

-----

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is made. The recommended handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use.

C = ceiling limit REC = recommended

EST = estimated V = recommended by vendor

NA = not applicable SKN = skin

NE = none established TS = trade secret ND = none determined R = recommended

NEGL = negligible MST = mist NF = none found NT = not tested

UNK = unknown STEL = short term exposure limit

By-product = reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).

\*\*\*\***END OF MSDS**\*\*\*\*mm 04/29/2009

\_\_\_\_\_