

800A

# **MATERIAL SAFETY DATA SHEET**

**Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200**

Date of Prep: 04/04/02

## **SECTION 1**

SUNNYSIDE CORPORATION  
225 CARPENTER AVENUE  
WHEELING, ILLINOIS 60090  
EMERGENCY TELEPHONE

(847) 541-5700  
(800) 424-9300

FOR INFORMATION:

(847) 541-5700

- SUNNYSIDE CORPORATION  
- CHEM TREC

Product Class: Petroleum Hydrocarbon

Manufacturer's Code:

800A

Trade Name: ALLPRO VM&amp;P NAPHTHA

NPCA HMIS:

Health: 1  
Fire: 3  
Reactivity: 0

Product Appearance and Odor: Clear, water-white liquid; petroleum odor.

## **SECTION 2 -- HAZARDOUS INGREDIENTS**

### **OCCUPATIONAL EXPOSURE LIMITS**

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Light Aliphatic Solvent Naphtha	64742-89-8		300 PPM		300 PPM	400 PPM	45 MM Hg @ 25°C

## **SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES**

Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.  
Skin Contact: Remove contaminated clothing/shoes. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.  
Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing.  
Ingestion: Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

## **SECTION 4 -- PHYSICAL DATA**

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	235-286° (F)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	Approx. 100%
Weight Per Gallon:	6.31 lbs.		
Solubility in Water:	Negligible; less than 0.1%		

## **SECTION 5 -- FIRE AND EXPLOSION DATA**

Flammability Classification: Flammable Liquid - Class IB.  
Flash Point: 40°(F) Tag. Closed cup  
Autoignition Temperature: 482°F (Approximate)  
Lower Explosive Limit: 0.9%

Extinguishing Media: Carbon dioxide, foam, dry chemical, water spray. Do not use direct water stream; it will spread fire.

Unusual Fire and Explosion Hazards: Flammable. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

Special Fire Fighting Procedures: Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

**SECTION 6 -- HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE: See Section 2.

**EFFECTS OF OVEREXPOSURE****Acute**

Eye Contact: May cause irritation, discomfort, redness and swelling of the eye. High vapor concentrations may also be irritating.

Skin Contact: Liquid is slightly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.

Inhalation: Vapors may cause irritation to nose, throat and respiratory tract. High vapor concentrations may result in central nervous system depression.

Ingestion: Ingestion may result in vomiting, aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

Chronic: Repeated skin contact may aggravate an existing dermatitis (skin condition).

Carcinogenicity: This product has not been identified as a carcinogen by NTP, IARC, or OSHA.

**SECTION 7 -- REACTIVITY DATA**

Stability: Stable

Conditions to Avoid: Heat, sparks and flame.

Incompatibility (Materials to Avoid): Strong oxidizing agents like liquid chlorine or concentrated oxygen.

Hazardous Decomposition Products: Thermal decomposition may yield carbon monoxide.

Hazardous Polymerization: Will not occur.

**SECTION 8 -- SPILL OR LEAK PROCEDURES**

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

**SECTION 9 -- SAFE HANDLING AND USE INFORMATION**

Respiratory Protection: Appropriate vapor canister, self-contained breathing apparatus or supplied-air hose mask, if needed.

Ventilation: Exposure levels should be maintained below applicable exposure limits - see Section 2. This product should not be used in confined spaces, or in a manner that will allow accumulation of high vapor concentrations. However, for controlled industrial uses when this product is used in confined spaces, heated above ambient temperatures or agitated, the use of explosion proof ventilation equipment is necessary.

Protective Gloves: Rubber or neoprene.

Eye Protection: Chemical safety goggles. Emergency eyewash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Other Protective Equipment: Impervious clothing or boots, if needed.

**SECTION 10 -- SPECIAL PRECAUTIONS**

Dept. of Labor Storage Category:	Flammable Liquid - Class IB
Hygienic Practices:	Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.
Additional Precautions:	Ground containers when transferring liquid to prevent static accumulation and discharge. Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lighting, and Stray Currents" (American Petroleum Institute, 1720 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).
Empty Container Warning:	"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

**SECTION 11 -- ADDITIONAL INFORMATION**

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

SARA Title III Hazard Categories: Immediate (Acute) Health, Delayed (Chronic) Health, Fire Hazard

Common Names: Solvent Naphtha (Petroleum), Aliphatic Hydrocarbon, Petroleum Distillate

California Proposition 65: This product contains trace amounts of Benzene, a chemical known to the State of California to cause cancer, and Toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

**TRANSPORTATION**

U.S. D.O.T. Proper Shipping Name: Petroleum Distillates, N.O.S.

U.S. D.O.T. Hazard Class & Packing Group: Flammable Liquid, II

U.S. D.O.T. I.D. Number: UN 1268

Refer to 49 CFR for possible exceptions and exemptions.