Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Product identifier

Trade name: Blasocut® BC 35 SW

B231737

Article number: 01350-21

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation:

For industrial use only

Metalworking fluid concentrate Cooling lubricant / Cutting fluid

Lubricant

Details of the supplier of the safety data sheet

Manufacturer / Supplier:

BLASER SWISSLUBE, Inc.

31 Hatfield Lane Goshen, NY 10924

USA

Phone: +1 (0) 845 294 32 00 Fax .: +1 (0) 845 294 31 02

Mailto: mailboxusa@blaser.com

Information department:

Product Safety Department E-mail: reach@blaser.com

Emergency telephone number:

Within USA and Canada . : 1-800-424-9300

Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

Classification of the substance or mixture

Causes eye irritation.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms not applicable

Signal word Warning

Hazard statements

H320 Causes eye irritation.

Precautionary statements

Wash thoroughly after handling.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313

If eye irritation persists: Get medical advice/attention.

Chemical characterization: Mixtures

Description: Mixture of mineral oil, emulsifiers, stabilizers and inhibitors

Declarable components:

CAS no.

770-35-4 1-Phenoxypropan-2-ol 68956-41-2 Emulsifier, based on fatty acids with alkanolamines

>1.0-6.9% 68608-26-4 Sodium petroleum sulfonate

(Contd. on page 2)

>1.0-6.9%



Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Trade name: Blasocut® BC 35 SW

125304-09-8 Ethercarboxylic acid, mixture with alcanolamines

>1.0-2.9%

3811-73-2 Sodium omadine

Additional information:

The specific chemical identity and/or exact percentage concentration of proprietary components is withheld as a trade secret.

Description of first aid measures After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

y digital release measures

Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Handling:

Precautions for safe handling

The product has been classified and marked in accordance with directives on hazardous materials.

Observe the general safety regulations when handling chemicals.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

(Contd. on page 3)



Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Trade name: Blasocut® BC 35 SW

(Contd. of page 2)

Store away from oxidizing agents.

Further information about storage conditions:

Protect from heat and direct sunlight.

Storage temperature between -40°F and +104°F

Optimal storage temperature between -40 °C and +40 °C.

Keep receptacle tightly sealed.

Duration of Storage: In closed, original container, at least 24 months.

Specific end use(s) No further relevant information available.

Secretaria de la contra esta de la constancia de la const

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values at the workplace:

64742-52-5 Mineral oil, severely hydrotreated, naphthenic (>50-<80%)

ACGIH TLV (US) Long-term value: 5 mg/m³
OSHA PEL (US) Long-term value: 5 mg/m³

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory Protection: Not required.

Material of gloves (recommended):

Suitable protective gloves: Nitrile gloves, minimum thickness of 0.3 mm.

Breakthrough time of glove material:

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection (recommended):

Eve protector with side protection (framed eveglasses) ANSI Z87.1 - 2010

Body protection (recommended): Protective work clothing

Information on basic physical and chemical properties

General Information

Appearance:

Form:

Fluid

Color:

Brown

Odor:

like almonds

Odor threshold:

Not determined.

pH-value:

8.5 - 9.2 @ 5% in water (ASTM D1287)

Change in condition:

Melting point/Melting range:

Not applicable

Boiling point/Boiling range:

> 572°F (> 300 °C) ASTM D86

Flash point:

293°F (145 °C) ASTM D92

(Contd. on page 4)

USA



(Contd. of page 3)

Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Trade name: Blasocut® BC 35 SW

Not applicable.

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Explosion limits (@1013 mbar):

Flammability (solid, gaseous):

Lower: Upper:

Not determined. Not determined.

Vapor pressure: Not determined.

Density:

Relative density
Vapour density

0.95 @ 68°F (20 °C) ASTM D1217

Vapour density Not determined. Evaporation rate Not determined.

Solubility in / Miscibility with

Water:

Emulsifiable.

Partition coefficient (n-octanol/water): Not determined.

Viscosity

Dynamic:

Not determined.

VOC content

26.4 g/L (ASTM E1868-10) @ Maximum concentration 15%

176 g/l (ASTM E1868-10); Concentrate in the packaging as

sold.

Other information:

nonę

Reactivity None known if used as directed.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products

(in case of fire or oxidation):

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx) Sulfur oxides (SOx)

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

> 2000 - < 5000 mg / kg (oral, rat)

> 5,100 mg/m³ 4h (inhalation, rat)

Primary irritant effect:

on the skin: No irritant effect. on the eye: To be slightly irritating.

Sensitization: No sensitizing effects known.

(Contd. on page 5)

USA



Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Trade name: Blasocut® BC 35 SW

(Contd. of page 4)

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed in groups 1, 2A, or 2B.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects No further relevant information available.

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Used containers

Recommendation: Disposal must be made according to official regulations.

DOT, ADR, IMDG, IATA

not applicable

DOT, ADR

not applicable

DOT, IMDG, IATA

Hazard Classification:

not applicable

DOT, ADR, IMDG, IATA

not applicable

Environmental hazards

Marine pollutant (according to IMDG): No

Special precautions for user

Not applicable.

Transport/Additional information:

Not hazardous according to the above specifications.

UN "Model Regulation":

(Contd. on page 6)



Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Trade name: Blasocut® BC 35 SW

(Contd. of page 5)

Safety, health and environmental regulations/legislation specific for the substance or mixture:

SARA (Superfund Amendments and Reauthorization)

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

This product does not contain a chemical that are listed in Section 313.

TSCA (Toxic Substances Control Act):

All ingredients are listed or exempt from notification requirements.

California Proposition 65

This product does not intentionally contain any chemicals known by the State of California to cause cancer and/or birth defects. Moreover, we do not routinely analyze its products for impurities which may be such chemicals.

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories:

EPA (Environmental Protection Agency)

None of the ingredients is listed.

NIOSH-Carcinogen list

None of the ingredients is listed.

California SCAQMD Rule 1144:

Category: Metalworking Fluid – Metal Removal – General. Recordkeeping requirement: Super Compliant.

(< 50 g/L, VOC @ max. use concentration)

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

IP346:

The mineral oil used in this product passes IP346 for DMSO extractable PAH's (Polycyclic aromatic hydrocarbons).

Department issuing SDS: Product Stewardship

Editor's notice:

The above mentioned data correspond to our present state of knowledge and experience. The safety data sheet serves as description of the products in regard to necessary safety measures. The indications have not the meaning of guarantees on properties.

Date of preparation / last revision 05/30/2015 / -

Abbreviations and acronyms:

RoHS: Restriction of Hazardous Substances

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 7)

Page 7/7

Safety Data Sheet acc. to 29 CFR 1910.1200 (OSHA Hazcom 2012)



Issued on 05/30/2015

Edition number 1

Reviewed on 05/30/2015

Trade name: Blasocut® BC 35 SW

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) ISO: International Organisation for Standardisation

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent DMSO: Dimethyl sulphoxide extract

IP 346: Institute of Petroleum and related for testing methods for petroleum and fuel products.

PBT: Persistent, Bioaccumulative and Toxic chemicals

vPvB: very Persistent and very Bioaccumulative chemicals NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

* Data compared to the previous version altered.

The asterisk (*) on the left side indicate the respective changes from the previous version.