Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



Product: Granite & Stone Sealer- 5186, 5187 **Revision Date:** 26-Oct-2016

SECTION 1 – IDENTIFICATION

Product Identifier

Product Name: Granite & Stone Sealer

Product Code: 5186, 5187

Recommended Use of the Chemical and Restrictions for Use

Recommended Use: Sealant

Restrictions for Use: Use only as directed.

Details of the Supplier

Manufacturer: Stone Care International

755 Tri-State Parkway Gurnee, IL 60031 800-839-1654

Emergency Phone Number

24-Hour Number: 1-800-535-5053 **International:** 1-352-323-3500

SECTION 2 – HAZARDS IDENTIFICATION

Classification

Hazard Class	Category
Flammable liquid	3
Specific target organ toxicity- repeated exposure	1

Label Elements

Hazard Symbols(s):





Signal Word(s): Danger

Hazard Statement(s): Flammable liquid and vapor. Causes damage to organs through prolonged or repeated exposure.

Precautionary Statement(s): Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measure against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. Store in a well-ventilated place. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other Hazards

None known.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Wt %
2-Butoxyethanol	111-76-2	1-5
Isopropyl alcohol	67-63-0	1-5

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4 - FIRST AID MEASURES

First Aid Measures

Document No.: 130529-5 Page 1 of 5

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



Product: Granite & Stone Sealer- 5186, 5187 Revision Date: 26-Oct-2016

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.

Ingestion: If swallowed do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Most Important Symptoms and Effects (Acute and Delayed)

Inhalation: May cause respiratory tract irritation.

Eye Contact: May cause eye irritation. Symptoms may include discomfort of pain, excess blinking and tear production, with possible redness and swelling.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physician: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

Suitable: Treat for surrounding material.

Unsuitable: None known.

Specific Hazards Arising from Chemical

Flammable liquid and vapor. Products of combustion include but are not limited to: oxides of carbon.

Protective Equipment and Precautions for Firefighters

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

Environmental Precautions: See Section 12 for ecological information.

Methods and Material for Containment and Cleaning Up

Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Scoop up material and place in a disposal container. Provide ventilation.

SECTION 7 – HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Keep away from sources of ignition. No smoking. Take precautionary measure against static discharge. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapor/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only non-sparking tools.

General Hygiene Advice: Launder contaminated clothing before use. Wash hands before eating, drinking, or smoking.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions: Proper grounding procedures to avoid static electricity should be followed. Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Keep cool.

Incompatible Materials: Oxidizers

Document No.: 130529-5 Page 2 of 5

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

STONE CARE

Product: Granite & Stone Sealer- 5186, 5187 **Revision Date:** 26-Oct-2016

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Guidelines:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol (11-76-2)	20 ppm TWA	240 mg/m ³ TWA	Not available
Isopropyl alcohol (67-63-0)	200 ppm TWA	980 mg/m ³ TWA	Not available

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Individual Protection Measures

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Skin and Body Protection: Wear suitable protective clothing.

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

General Work/Hygienic Practices: Do not eat, smoke or drink where material is handled, processed or stored. Wash

hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid

Odor: Solvent

Odor threshold: Not determined

pH: 8.8

Melting point/freezing point: Not determined

Initial boiling point and boiling range: Not determined

Flash point: 58.9°C (138°F) TCC Evaporation rate: Not determined Flammability (solid, gas): Flammable

Upper/lower flammability or explosive limits: Not determined

Vapor pressure: Not determined Vapor density: Not determined

Relative density: 1.01

Solubility(ies): Not determined

Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: Not determined

Decomposition temperature: Not determined

Viscosity: Not determined

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Stable under recommended storage conditions. May form flammable/explosive vapor-air mixture.

Possibility of hazardous reactions: None under normal use.

Conditions to avoid: Heat. Incompatible materials. Sources of ignition.

Incompatible materials: Oxidizers

Document No.: 130529-5 Page 3 of 5



Revision Date: 26-Oct-2016 Product: Granite & Stone Sealer- 5186, 5187

Hazardous decomposition products: May include and are not limited to: oxides of carbon.

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Likely Routes of Exposure: Inhalation, skin contact, eye contact, ingestion

Information Related to Physical, Chemical, and Toxicological Effects

See section 4 of this SDS.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

IARC: No OSHA: No Carcinogenicity: NTP: No

Numerical Measures of Toxicity

Product	
ATE (oral)	>2000 mg/kg, rat
ATE (dermal)	>2000 mg/kg, rabbit
ATE (inhalation)	>20 mg/l/4h,rat

Component Information:

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butoxyethanol (11-76-2)	470 mg/kg (rat)	99 mg/kg (rabbit)	450 ppm/4h (rat)
Isopropyl alcohol (67-63-0)	1870 mg/kg (rat)	4059 mg/kg (rabbit)	72600 mg/m ³ /4h (rat)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: Not established

Persistence and degradability: Not established Bioaccumulative potential: Not established

Mobility in soil: No additional information available

Other adverse effects: No additional information available.

SECTION 13 – DISPOSAL CONSIDERATIONS

See section 8 of this SDS for exposure controls and personal protection.

Dispose of the product and container in accordance with all applicable local, state, and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

Note: Classification changes based on quantity, packaging, and method of shipment. See current shipping paper for most up to date shipping information.

UN1993, Flammable liquids, n.o.s. (2-Butoxyethanol, Isopropyl alcohol), 3, PG III

DOT (Ground): Limited quantity

IATA (Air): DO NOT SHIP- Required testing has not been completed

IMDG (Vessel): Limited quantity

SECTION 15 – REGULATORY INFORMATION

All ingredients in this product are listed or are excluded from listing on the US Toxic Substances Act (TSCA) Chemical Substance Inventory.

SECTION 16 – OTHER INFORMATION

Issue Date: 26-Oct-2016 Revision Date: 26-Oct-2016

Page 4 of 5 Release Date: 1/10/2014

Document No.: 130529-5

Product:

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012



Granite & Stone Sealer- 5186, 5187 Revision Date: 26-Oct-2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designed and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Document No.: 130529-5 Page 5 of 5