

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Easyarc® 6013

Product Size: 5.0 mm

Other means of identification

SDS number: 200000002712

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: SMAW (Shielded Metal Arc Welding)

Uses advised against: Not known. Read this SDS before using this product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Importer/Supplier/Distributor Information

Company Name: The Shanghai Lincoln Electric Co., Ltd.

Address: No. 195, Lane 5008, Hu Tai Road
Shanghai 201907
China

Telephone: +86 21 6673 4530

Contact Person: Safety Data Sheet Questions: www.lincolnelectric.com/sds
Arc Welding Safety Information: www.lincolnelectric.com/safety

Company Name: Lincoln Electric Europe B.V.

Address: Nieuwe Dukenburgseweg 20
Nijmegen 6534AD
The Netherlands

Telephone: +31 243 522 911

Contact Person: Safety Data Sheet Questions: www.lincolnelectric.com/sds
Arc Welding Safety Information: www.lincolnelectric.com/safety

1.4 Emergency telephone number:

USA/Canada/Mexico +1 (888) 609-1762

Americas/Europe +1 (216) 383-8962

Asia Pacific +1 (216) 383-8966

Middle East/Africa +1 (216) 383-8969

3E Company Access Code: 333988

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous according to the legislation in force.

Classification according to Regulation (EC) No 1272/2008 as amended.

Not classified as hazardous according to applicable GHS hazard classification criteria.

Supplemental label information

EUH210: Safety data sheet available on request.
Safety data sheet available for professional user on request.

2.3 Other hazards

Electrical Shock can kill. If welding must be performed in damp locations or with wet clothing, on metal structures or when in cramped positions such as sitting, kneeling or lying, or if there is a high risk of unavoidable or accidental contact with work piece, use the following equipment: Semiautomatic DC Welder, DC Manual (Stick) Welder, or AC Welder with Reduced Voltage Control.

Arc rays can injure eyes and burn skin. Welding arc and sparks can ignite combustibles and flammable materials. Overexposure to welding fumes and gases can be hazardous. Read and understand the manufacturer's instructions, Safety Data Sheets and the precautionary labels before using this product. Refer to Section 8.

Substance(s) formed under the conditions of use:

The welding fume produced from this welding electrode may contain the following constituent(s) and/or their complex metallic oxides as well as solid particles or other constituents from the consumables, base metal, or base metal coating not listed below.

| Chemical name | CAS-No. |
|------------------|------------|
| Carbon dioxide | 124-38-9 |
| Carbon monoxide | 630-08-0 |
| Nitrogen dioxide | 10102-44-0 |
| Ozone | 10028-15-6 |
| Manganese | 7439-96-5 |

SECTION 3: Composition/information on ingredients

Reportable Hazardous Ingredients

3.2 Mixtures

| Chemical name | Concentration | CAS-No. | EC No. | Classification | Notes | REACH Registration No. |
|--|---------------|------------|-----------|--|-------|------------------------|
| Iron | 50 - <100% | 7439-89-6 | 231-096-4 | Not classified | | 01-2119462838-24; |
| Titanium dioxide (naturally occurring) | 10 - <20% | 13463-67-7 | 236-675-5 | Not classified | # | No data available. |
| Mica | 1 - <5% | 12001-26-2 | | Not classified | # | No data available. |
| Potassium silicate | 1 - <5% | 1312-76-1 | 215-199-1 | Eye Irrit.: 2: H319; Skin Corr.: 2: H315; | | 01-2119456888-17; |
| Manganese | 1 - <5% | 7439-96-5 | 231-105-1 | Not classified | # | 01-2119449803-34; |
| Calcium carbonate | 0,1 - <1% | 471-34-1 | 207-439-9 | Not classified | # | 01-2119486795-18; |
| Magnesite | 0,1 - <1% | 546-93-0 | 208-915-9 | Not classified | # | No data available. |

| | | | | | | |
|-----------------------------|-----------|------------|-----------|--|---|--------------------|
| Quartz | 0,1 - <1% | 14808-60-7 | 238-878-4 | STOT RE: 1: H372; | # | No data available. |
| Iron oxide | 0,1 - <1% | 1309-37-1 | 215-168-2 | Not classified | # | No data available. |
| Zirconium oxide | 0,1 - <1% | 1314-23-4 | 215-227-2 | Not classified | # | No data available. |
| Aluminum oxide | 0,1 - <1% | 1344-28-1 | 215-691-6 | Not classified | # | 01-2119529248-35; |
| Cellulose, pulp | 0,1 - <1% | 65996-61-4 | 265-995-8 | Not classified | | No data available. |
| Feldspar | 0,1 - <1% | 68476-25-5 | 270-666-7 | Not classified | | No data available. |
| Silicon dioxide (amorphous) | 0,1 - <1% | 7631-86-9 | 231-545-4 | Not classified | # | No data available. |
| Hydroxyethyl cellulose | 0,1 - <1% | 9004-62-0 | | Not classified | | No data available. |
| Silicon | 0,1 - <1% | 7440-21-3 | 231-130-8 | Not classified | # | 01-2119480401-47; |
| Vanadium pentoxide | 0,1 - <1% | 1314-62-1 | 215-239-8 | Muta.: 2: H341; Repr.: 2: H361d; Acute Tox.: 4: H332; Acute Tox.: 4: H302; STOT RE: 1: H372; STOT SE: 3: H335; Eye Dam.: 1: H318; Aquatic Chronic: 2: H411; | # | No data available. |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

This substance has workplace exposure limit(s).

This substance is listed as SVHC

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.

Composition Comments:

The term "Hazardous Ingredients" should be interpreted as a term defined in Hazard Communication standards and does not necessarily imply the existence of a welding or allied process hazard. The product may contain additional non-hazardous ingredients or may form additional compounds under the condition of use. Refer to Sections 2 and 8 for more information.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation:

Move to fresh air if breathing is difficult. If breathing has stopped, perform artificial respiration and obtain medical assistance at once.

Skin Contact:

Remove contaminated clothing and wash the skin thoroughly with soap and water. For reddened or blistered skin, or thermal burns, obtain medical assistance at once.

Eye contact: Dust or fume from this product should be flushed from the eyes with copious amounts of clean, tepid water until transported to an emergency medical facility. Do not allow victim to rub or keep eyes tightly closed. Obtain medical assistance at once.

Arc rays can injure eyes. If exposed to arc rays, move victim to dark room, remove contact lenses as necessary for treatment, cover eyes with a padded dressing and rest. Obtain medical assistance if symptoms persist.

Ingestion: Avoid hand, clothing, food, and drink contact with fluxes, metal fume or powder which can cause ingestion of particulate during hand to mouth activities such as drinking, eating, smoking, etc. If ingested, do not induce vomiting. Contact a poison control center. Unless the poison control center advises otherwise, wash out mouth thoroughly with water. If symptoms develop, seek medical attention at once.

4.2 Most important symptoms and effects, both acute and delayed: Short-term (acute) overexposure to fumes and gases from welding and allied processes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long-term (chronic) overexposure to fumes and gases from welding and allied processes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects. Refer to Section 11 for more information.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: The hazards associated with welding and its allied processes such as soldering and brazing are complex and may include physical and health hazards such as but not limited to electric shock, physical strains, radiation burns (eye flash), thermal burns due to hot metal or spatter and potential health effects of overexposure to fumes, gases or dusts potentially generated during the use of this product. Refer to Section 11 for more information.

Treatment: Treat symptomatically.

SECTION 5: Firefighting measures

General Fire Hazards: As shipped, this product is nonflammable. However, welding arc and sparks as well as open flames and hot surfaces associated with brazing and soldering can ignite combustible and flammable materials. Read and understand American National Standard Z49.1, "Safety in Welding, Cutting and Allied Processes" and National Fire Protection Association NFPA 51B, "Standard for Fire Prevention during Welding, Cutting and Other Hot Work" before using this product.

5.1 Extinguishing media
Suitable extinguishing media: As shipped, the product will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

| | |
|--|--|
| 5.2 Special hazards arising from the substance or mixture: | Welding arc and sparks can ignite combustibles and flammable products. |
| 5.3 Advice for firefighters Special fire fighting procedures: | Use standard firefighting procedures and consider the hazards of other involved materials. |
| Special protective equipment for fire-fighters: | Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |

SECTION 6: Accidental release measures

| | |
|---|---|
| 6.1 Personal precautions, protective equipment and emergency procedures: | If airborne dust and/or fume is present, use adequate engineering controls and, if needed, personal protection to prevent overexposure. Refer to recommendations in Section 8. |
| 6.2 Environmental Precautions: | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages. |
| 6.3 Methods and material for containment and cleaning up: | Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk. Clean up spills immediately, observing precautions in the personal protective equipment in Section 8. Avoid generating dust. Prevent product from entering any drains, sewers or water sources. Refer to Section 13 for proper disposal. |
| 6.4 Reference to other sections: | For further specification, refer to section 8 of the SDS. |

SECTION 7: Handling and storage:

| | |
|--|---|
| 7.1 Precautions for safe handling: | Prevent formation of dust. Provide appropriate exhaust ventilation at places where dust is formed. Read and understand the manufacturer's instruction and the precautionary label on the product. Refer to Lincoln Safety Publications at www.lincolnelectric.com/safety . See American National Standard Z49.1, "Safety In Welding, Cutting and Allied Processes" published by the American Welding Society, http://pubs.aws.org and OSHA Publication 2206 (29CFR1910), U.S. Government Printing Office, www.gpo.gov . |
| 7.2 Conditions for safe storage, including any incompatibilities: | Store in closed original container in a dry place. Store in accordance with local/regional/national regulations. Store away from incompatible materials. |
| 7.3 Specific end use(s): | No data available. |

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

MAC, PEL, TLV and other exposure limit values may vary per element and form - as well as per country. All country-specific values are not listed. If no occupational exposure limit values are listed below, your local authority may still have applicable values. Refer to your local or national exposure limit values.

Control Parameters

Occupational Exposure Limits: Great Britain

| Chemical Identity | Type | Exposure Limit Values | Source |
|--|------|-------------------------|---|
| Titanium dioxide (naturally occurring) - Inhalable | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Titanium dioxide (naturally occurring) - Respirable. | TWA | 4 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Mica - Inhalable | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Mica - Respirable. | TWA | 0,8 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Manganese - Respirable fraction. - as Mn | TWA | 0,05 mg/m ³ | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (02 2017) |
| Manganese - Inhalable fraction. - as Mn | TWA | 0,2 mg/m ³ | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (02 2017) |
| Manganese - Respirable fraction. | TWA | 0,050 mg/m ³ | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended (2014) |
| Manganese - Inhalable fraction. | TWA | 0,200 mg/m ³ | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended (2014) |
| Manganese - Respirable fraction. - as Mn | TWA | 0,05 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (08 2018) |
| Manganese - Inhalable fraction. - as Mn | TWA | 0,2 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (08 2018) |
| Calcium carbonate - Respirable. | TWA | 4 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Calcium carbonate - Inhalable | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Calcium carbonate - Inhalable dust. | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Calcium carbonate - Respirable dust. | TWA | 4 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| | TWA | 4 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Calcium carbonate - Inhalable dust. | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Magnesite - Inhalable dust. | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Magnesite - Respirable dust. | TWA | 4 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Quartz - Respirable. | TWA | 0,1 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Quartz - Respirable fraction and dust | TWA | 0,1 mg/m ³ | EU. OELs, Directive 2004/37/EC on carcinogen and mutagens from Annex III, Part A (12 2017) |
| Iron oxide - Respirable. | TWA | 4 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Iron oxide - Inhalable | TWA | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Iron oxide - Fume. - as Fe | TWA | 5 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| | STEL | 10 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Zirconium oxide - as Zr | TWA | 5 mg/m ³ | UK. EH40 Workplace Exposure Limits (WELs) (2007) |

| | | | |
|--|------|------------|---|
| | STEL | 10 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Zirconium oxide - Inhalable dust. | TWA | 10 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Zirconium oxide - Respirable dust. | TWA | 4 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Aluminum oxide - Inhalable dust. | TWA | 10 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Aluminum oxide - Respirable dust. | TWA | 4 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Silicon dioxide (amorphous) - Inhalable dust. | TWA | 6 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Silicon dioxide (amorphous) - Respirable dust. | TWA | 2,4 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Silicon dioxide (amorphous) - Inhalable dust. | TWA | 10 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Silicon dioxide (amorphous) - Respirable dust. | TWA | 4 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (01 2020) |
| Silicon - Inhalable dust. | TWA | 10 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Silicon - Respirable dust. | TWA | 4 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |
| Vanadium pentoxide | TWA | 0,05 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) (2007) |

Biological Limit Values: Great Britain

None of the components have assigned exposure limits.

Biological Limit Values: ACGIH

None of the components have assigned exposure limits.

Additional exposure limits under the conditions of use: Great Britain

| Chemical Identity | Type | Exposure Limit Values | Source |
|-------------------|------|-----------------------|--|
| Carbon dioxide | TWA | 5.000 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| | TWA | 5.000 ppm | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| | STEL | 15.000 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| Carbon monoxide | STEL | 100 ppm | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| | TWA | 20 ppm | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| | STEL | 100 ppm | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended |
| | TWA | 20 ppm | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended |
| | STEL | 200 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| | TWA | 30 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| | STEL | 100 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| | TWA | 20 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| | TWA | 30 ppm | UK. EH40 Workplace Exposure Limits (WELs) (The expiration date of this limit: 21 August 2023) |
| | STEL | 200 ppm | UK. EH40 Workplace Exposure Limits (WELs) (The expiration date of this limit: 21 August 2023) |

| | | | |
|--|------|-------------|--|
| Nitrogen dioxide | TWA | 0,5 ppm | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| | STEL | 1 ppm | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| | STEL | 1 ppm | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended |
| | TWA | 0,5 ppm | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended |
| | TWA | 0,5 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| | STEL | 1 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| Ozone | STEL | 0,2 ppm | UK. EH40 Workplace Exposure Limits (WELs) |
| Manganese - Respirable fraction. - as Mn | TWA | 0,05 mg/m3 | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| Manganese - Inhalable fraction. - as Mn | TWA | 0,2 mg/m3 | EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (Indicative) |
| Manganese - Respirable fraction. | TWA | 0,050 mg/m3 | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended |
| Manganese - Inhalable fraction. | TWA | 0,200 mg/m3 | EU. Scientific Committee on Occupational Exposure Limit Values (SCOELs), European Commission - SCOEL, as amended |
| Manganese - Respirable fraction. - as Mn | TWA | 0,05 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) |
| Manganese - Inhalable fraction. - as Mn | TWA | 0,2 mg/m3 | UK. EH40 Workplace Exposure Limits (WELs) |

Additional exposure limits under the conditions of use: US

| Chemical Identity | Type | Exposure Limit Values | Source |
|--|---------|-----------------------|---|
| Carbon dioxide | TWA | 5.000 ppm | US. ACGIH Threshold Limit Values (12 2010) |
| | STEL | 30.000 ppm | US. ACGIH Threshold Limit Values (12 2010) |
| | PEL | 5.000 ppm 9.000 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Carbon monoxide | TWA | 25 ppm | US. ACGIH Threshold Limit Values (12 2010) |
| | PEL | 50 ppm 55 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Nitrogen dioxide | TWA | 0,2 ppm | US. ACGIH Threshold Limit Values (02 2012) |
| | Ceiling | 5 ppm 9 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Ozone | PEL | 0,1 ppm 0,2 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 0,05 ppm | US. ACGIH Threshold Limit Values (03 2014) |
| | TWA | 0,10 ppm | US. ACGIH Threshold Limit Values (03 2014) |
| | TWA | 0,08 ppm | US. ACGIH Threshold Limit Values (03 2014) |
| | TWA | 0,20 ppm | US. ACGIH Threshold Limit Values (02 2020) |
| Manganese - Fume. - as Mn | Ceiling | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Manganese - Inhalable fraction. - as Mn | TWA | 0,1 mg/m3 | US. ACGIH Threshold Limit Values (03 2014) |
| Manganese - Respirable fraction. - as Mn | TWA | 0,02 mg/m3 | US. ACGIH Threshold Limit Values (03 2014) |

8.2 Exposure controls

Appropriate Engineering Controls

Ventilation: Use enough ventilation and local exhaust at the arc, flame or heat source to keep the fumes and gases from the worker's breathing zone and the general area. Train the operator to keep their head out of the fumes. **Keep exposure as low as possible.**

Individual protection measures, such as personal protective equipment**General information:**

Exposure Guidelines: To reduce the potential for overexposure, use controls such as adequate ventilation and personal protective equipment (PPE). Overexposure refers to exceeding applicable local limits, the American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values (TLVs) or the Occupational Safety and Health Administration's (OSHA) Permissible Exposure Limits (PELs). Workplace exposure levels should be established by competent industrial hygiene assessments. Unless exposure levels are confirmed to be below the applicable local limit, TLV or PEL, whichever is lower, respirator use is required. Absent these controls, overexposure to one or more compound constituents, including those in the fume or airborne particles, may occur resulting in potential health hazards. According to the ACGIH, TLVs and Biological Exposure Indices (BEIs) "represent conditions under which ACGIH believes that nearly all workers may be repeatedly exposed without adverse health effects." The ACGIH further states that the TLV-TWA should be used as a guide in the control of health hazards and should not be used to indicate a fine line between safe and dangerous exposures. See Section 10 for information on constituents which have some potential to present health hazards. Welding consumables and materials being joined may contain chromium as an unintended trace element. Materials that contain chromium may produce some amount of hexavalent chromium (CrVI) and other chromium compounds as a byproduct in the fume. In 2018, the American Conference of Governmental Industrial Hygienists (ACGIH) lowered the Threshold Limit Value (TLV) for hexavalent chromium from 50 micrograms per cubic meter of air (50 µg/m³) to 0.2 µg/m³. At these new limits, CrVI exposures at or above the TLV may be possible in cases where adequate ventilation is not provided. CrVI compounds are on the IARC and NTP lists as posing a lung cancer and sinus cancer risk. Workplace conditions are unique and welding fume exposures levels vary. Workplace exposure assessments must be conducted by a qualified professional, such as an industrial hygienist, to determine if exposures are below applicable limits and to make recommendations when necessary for preventing overexposures.

Eye/face protection:

Wear helmet or use face shield with filter lens shade number 12 or darker for open arc processes – or follow the recommendations as specified in ANSI Z49.1, Section 4, based on your process and settings. No specific lens shade recommendation for submerged arc or electroslag processes. Shield others by providing appropriate screens and flash goggles.

Skin protection**Hand Protection:**

Wear protective gloves. Suitable gloves can be recommended by the glove supplier.

| | |
|--------------------------------|--|
| Other: | Protective Clothing: Wear hand, head, and body protection which help to prevent injury from radiation, open flames, hot surfaces, sparks and electrical shock. See Z49.1. At a minimum, this includes welder's gloves and a protective face shield when welding, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing when welding, brazing and soldering. Wear dry gloves free of holes or split seams. Train the operator not to permit electrically live parts or electrodes from contacting the skin . . . or clothing or gloves if they are wet. Insulate yourself from the work piece and ground using dry plywood, rubber mats or other dry insulation. |
| Respiratory Protection: | Keep your head out of fumes. Use enough ventilation and local exhaust to keep fumes and gases from your breathing zone and the general area. An approved respirator should be used unless exposure assessments are below applicable exposure limits. |
| Hygiene measures: | Do not eat, drink or smoke when using the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.2, F1.3 and F1.5, available from the American Welding Society, www.aws.org . |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---------------------------------------|
| Appearance: | Steel rod with extruded flux coating. |
| Physical state: | Solid |
| Form: | Solid |
| Color: | No data available. |
| Odor: | No data available. |
| Odor Threshold: | No data available. |
| pH: | No data available. |
| Melting Point: | No data available. |
| Boiling Point: | No data available. |
| Flash Point: | No data available. |
| Evaporation Rate: | No data available. |
| Flammability (solid, gas): | No data available. |
| Flammability Limit - Upper (%): | No data available. |
| Flammability Limit - Lower (%): | No data available. |
| Vapor pressure: | No data available. |
| Relative vapor density: | No data available. |
| Density: | No data available. |
| Relative density: | No data available. |
| Solubility(ies) | |

| | |
|---|--------------------|
| Solubility in Water: | No data available. |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Autoignition Temperature: | No data available. |
| Decomposition Temperature: | No data available. |
| SADT: | No data available. |
| Viscosity: | No data available. |
| Explosive properties: | No data available. |
| Oxidizing properties: | No data available. |

9.2 Other information

| | |
|---------------------|----------------|
| VOC Content: | Not available. |
|---------------------|----------------|

| | |
|-------------------------------------|----------------|
| Bulk density: | Not available. |
| Dust Explosion Limit, Upper: | Not available. |
| Dust Explosion Limit, Lower: | Not available. |

| | |
|---|----------------|
| Dust Explosion Description Number Kst: | Not available. |
| Minimum ignition energy: | Not available. |
| Minimum ignition temperature: | Not available. |
| Metal Corrosion: | Not available. |

SECTION 10: Stability and reactivity

| | |
|---|--|
| 10.1 Reactivity: | The product is non-reactive under normal conditions of use, storage and transport. |
| 10.2 Chemical Stability: | Material is stable under normal conditions. |
| 10.3 Possibility of hazardous reactions: | None under normal conditions. |
| 10.4 Conditions to avoid: | Avoid heat or contamination. |
| 10.5 Incompatible Materials: | Strong acids. Strong oxidizing substances. Strong bases. |

10.6 Hazardous Decomposition Products:

Fumes and gases from welding and its allied processes such as brazing and soldering cannot be classified simply. The composition and quantity of both are dependent upon the metal to which the joining or hot work is applied, the process, procedure - and where applicable - the electrode or consumable used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded or worked (such as paint, plating, or galvanizing), the number of operators and the volume of the work area, the quality and amount of ventilation, the position of the operator's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities.)

In cases where an electrode or other applied material is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc., as noted above. Reasonably expected fume constituents produced during arc welding and brazing include the oxides of iron, manganese and other metals present in the welding consumable or base metal. Hexavalent chromium compounds may be in the welding or brazing fume of consumables or base metals which contain chromium. Gaseous and particulate fluoride may be in the fume of consumables or flux materials which contain fluoride. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc associated with welding.

SECTION 11: Toxicological information**General information:**

The International Agency for Research on Cancer (IARC) has determined welding fumes and ultraviolet radiation from welding are carcinogenic to humans (Group 1). According to IARC, welding fumes cause cancer of the lung and positive associations have been observed with cancer of the kidney. Also according to IARC, ultraviolet radiation from welding causes ocular melanoma. IARC identifies gouging, brazing, carbon arc or plasma arc cutting, and soldering as processes closely related to welding. Read and understand the manufacturer's instructions, Safety Data Sheets and the precautionary labels before using this product.

Information on likely routes of exposure**Inhalation:**

Potential chronic health hazards related to the use of welding consumables are most applicable to the inhalation route of exposure. Refer to Inhalation statements in Section 11.

Skin Contact:

Arc rays can burn skin. Skin cancer has been reported.

Eye contact:

Arc rays can injure eyes.

Ingestion:

Health injuries from ingestion are not known or expected under normal use.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:

Respiratory exposure to the crystalline silica present in this welding electrode is not anticipated during normal use. Respiratory overexposure to airborne crystalline silica is known to cause silicosis, a form of disabling pulmonary fibrosis which can be progressive and may lead to death. Crystalline silica is on the IARC (International Agency for Research on Cancer) and NTP (National Toxicology Program) lists as posing a cancer risk to humans. Note: All regional authorities do not use the same criteria for assigning carcinogenic classifications to chemicals. For example, the European Union (EU) CLP does not require classifying crystalline silica as a carcinogenic compound. Short-term (acute) overexposure to fumes and gases from welding and allied processes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long-term (chronic) overexposure to fumes and gases from welding and allied processes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects.

11.1 Information on toxicological effects**Acute toxicity (list all possible routes of exposure)****Oral**

| | |
|--------------------------------|--------------------------|
| Product: | Not classified |
| Specified substance(s): | |
| Iron | LD 50 (Rat): 98,6 g/kg |
| Calcium carbonate | LD 50 (Rat): 6.450 mg/kg |
| Vanadium pentoxide | LD 50 (Rat): 221,1 mg/kg |

Dermal

| | |
|-----------------|----------------|
| Product: | Not classified |
|-----------------|----------------|

Inhalation

| | |
|--------------------------------|-----------------------------|
| Product: | Not classified |
| Specified substance(s): | |
| Vanadium pentoxide | LC 50 (Rat, 4 h): 2,21 mg/l |

Repeated dose toxicity

| | |
|-----------------|----------------|
| Product: | Not classified |
|-----------------|----------------|

Skin Corrosion/Irritation

| | |
|-----------------|----------------|
| Product: | Not classified |
|-----------------|----------------|

Serious Eye Damage/Eye Irritation

| | |
|-----------------|----------------|
| Product: | Not classified |
|-----------------|----------------|

Respiratory or Skin Sensitization

| | |
|-----------------|----------------|
| Product: | Not classified |
|-----------------|----------------|

Carcinogenicity

| | |
|-----------------|--|
| Product: | Arc rays: Skin cancer has been reported. |
|-----------------|--|

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

| | |
|---|--|
| Specified substance(s): | |
| Titanium dioxide (naturally occurring) | Overall evaluation: 2B. Possibly carcinogenic to humans. |
| Quartz | Overall evaluation: 1. Carcinogenic to humans. |

| | |
|--------------------------------|--|
| Iron oxide | Overall evaluation: 3. Not classifiable as to carcinogenicity to humans. |
| Silicon dioxide (amorphous) | Overall evaluation: 3. Not classifiable as to carcinogenicity to humans. |
| Vanadium pentoxide | Overall evaluation: 2B. Possibly carcinogenic to humans. |

Germ Cell Mutagenicity**In vitro**

Product: Not classified

In vivo

Product: Not classified

Reproductive toxicity

Product: Not classified

Specific Target Organ Toxicity - Single Exposure

Product: Not classified

Specific Target Organ Toxicity - Repeated Exposure

Product: Not classified

Aspiration Hazard

Product: Not classified

Other effects:

Organic polymers may be used in the manufacture of various welding consumables. Overexposure to their decomposition byproducts may result in a condition known as polymer fume fever. Polymer fume fever usually occurs within 4 to 8 hours of exposure with the presentation of flu like symptoms, including mild pulmonary irritation with or without an increase in body temperature. Signs of exposure can include an increase in white blood cell count. Resolution of symptoms typically occurs quickly, usually not lasting longer than 48 hours.

Symptoms related to the physical, chemical and toxicological characteristics under the condition of use**Inhalation:****Specified substance(s):**

Manganese

Overexposure to manganese fumes may affect the brain and central nervous system, resulting in poor coordination, difficulty speaking, and arm or leg tremor. This condition can be irreversible.

Additional toxicological Information under the conditions of use:**Acute toxicity****Inhalation****Specified substance(s):**

| | |
|------------------|---------------------------------|
| Carbon dioxide | LC Lo (Human, 5 min): 90000 ppm |
| Carbon monoxide | LC 50 (Rat, 4 h): 1300 ppm |
| Nitrogen dioxide | LC 50 (Rat, 4 h): 88 ppm |
| Ozone | LC Lo (Human, 30 min): 50 ppm |

Other effects:**Specified substance(s):**

Carbon dioxide Asphyxia

| | |
|------------------|------------------------------------|
| Carbon monoxide | Carboxyhemoglobinemia |
| Nitrogen dioxide | Lower respiratory tract irritation |

SECTION 12: Ecological information

12.1 Ecotoxicity

Acute hazards to the aquatic environment:

Fish

| | |
|--------------------------------|---|
| Product: | Not classified. |
| Specified substance(s): | |
| Vanadium pentoxide | LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13 mg/l |

Aquatic Invertebrates

| | |
|--------------------------------|--|
| Product: | Not classified. |
| Specified substance(s): | |
| Manganese | EC 50 (Water flea (Daphnia magna), 48 h): 40 mg/l |
| Vanadium pentoxide | LC 50 (Water flea (Daphnia magna), 48 h): 1,11 - 1,96 mg/l |

Chronic hazards to the aquatic environment:

Fish

| | |
|-----------------|-----------------|
| Product: | Not classified. |
|-----------------|-----------------|

Aquatic Invertebrates

| | |
|-----------------|-----------------|
| Product: | Not classified. |
|-----------------|-----------------|

Toxicity to Aquatic Plants

| | |
|-----------------|-----------------|
| Product: | Not classified. |
|-----------------|-----------------|

12.2 Persistence and Degradability

Biodegradation

| | |
|-----------------|--------------------|
| Product: | No data available. |
|-----------------|--------------------|

12.3 Bioaccumulative potential

Bioconcentration Factor (BCF)

| | |
|-----------------|--------------------|
| Product: | No data available. |
|-----------------|--------------------|

| | |
|-------------------------------|--------------------|
| 12.4 Mobility in soil: | No data available. |
|-------------------------------|--------------------|

| | |
|---|--------------------|
| 12.5 Results of PBT and vPvB assessment: | No data available. |
|---|--------------------|

| | |
|------------------------------------|--------------------|
| 12.6 Other adverse effects: | No data available. |
|------------------------------------|--------------------|

| | |
|-------------------------------------|--------------------|
| 12.7 Additional Information: | No data available. |
|-------------------------------------|--------------------|

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| | |
|--------------------------------|--|
| General information: | The generation of waste should be avoided or minimized whenever possible. When practical, recycle in an environmentally acceptable, regulatory compliant manner. Dispose of non-recyclable products in accordance with all applicable Federal, State, Provincial, and Local requirements. |
| Disposal instructions: | Disposal of this product may be regulated as a Hazardous Waste. The welding consumable and/or by-product from the welding process (including, but not limited to slag, dust, etc.) may contain levels of leachable heavy metals such as Barium or Chromium. Prior to disposal, a representative sample must be analyzed in accordance with US EPA's Toxicity Characteristic Leaching Procedure (TCLP) to determine if any constituents exist above regulated threshold levels. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner according to Federal, State and Local Regulations. |
| Contaminated Packaging: | Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. |

SECTION 14: Transport information**ADR**

| | |
|---------------------------------|------------------|
| 14.1 UN number or ID number: | |
| 14.2 UN Proper Shipping Name: | NOT DG REGULATED |
| 14.3 Transport Hazard Class(es) | |
| Class: | NR |
| Label(s): | — |
| Hazard No. (ADR): | — |
| Tunnel restriction code: | |
| 14.4 Packing Group: | — |
| Limited quantity | |
| Excepted quantity | |
| 14.5 Marine Pollutant | No |

ADN

| | |
|---------------------------------|------------------|
| 14.1 UN number or ID number: | |
| 14.2 UN Proper Shipping Name: | NOT DG REGULATED |
| 14.3 Transport Hazard Class(es) | |
| Class: | NR |
| Label(s): | — |
| Hazard No. (ADR): | — |
| 14.4 Packing Group: | — |
| Limited quantity | |
| Excepted quantity | |
| 14.5 Marine Pollutant | No |

RID

| | |
|---------------------------------|------------------|
| 14.1 UN number or ID number: | |
| 14.2 UN Proper Shipping Name: | NOT DG REGULATED |
| 14.3 Transport Hazard Class(es) | |
| Class: | NR |
| Label(s): | — |

14.4 Packing Group: —
14.5 Marine Pollutant No

IMDG

14.1 UN number or ID number:
14.2 UN Proper Shipping Name: NOT DG REGULATED
14.3 Transport Hazard Class(es)
Class: NR
Label(s): —
EmS No.:
14.4 Packing Group: —
Limited quantity
Excepted quantity
14.5 Marine Pollutant No

IATA

14.1 UN number or ID number:
14.2 Proper Shipping Name: NOT DG REGULATED
14.3 Transport Hazard Class(es):
Class: NR
Label(s): —
14.4 Packing Group: —
Cargo aircraft only :
Passenger and cargo aircraft :
Limited quantity:
Excepted quantity
14.5 Marine Pollutant No
Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:****EU Regulations**

Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: None

Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex II, New Substances: None

EU. REACH Annex XIV, Substances Subject to Authorization: None

EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended: None

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: None

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended: None

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended: None

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended:
None

EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC): None

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

| Chemical name | CAS-No. | Concentration |
|--------------------|-----------|---------------|
| Vanadium pentoxide | 1314-62-1 | 0,1 - 1,0% |

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens and mutagens at work.:

| Chemical name | CAS-No. | Concentration |
|---------------|------------|---------------|
| Quartz | 14808-60-7 | 0,1 - 1,0% |

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.:

| Chemical name | CAS-No. | Concentration |
|--|------------|---------------|
| Titanium dioxide (naturally occurring) | 13463-67-7 | 10 - 20% |
| Vanadium pentoxide | 1314-62-1 | 0,1 - 1,0% |

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:

Not applicable

EU. Regulation No. 166/2006 PRTR (Pollutant Release and Transfer Registry), Annex II: Pollutants:

| Chemical name | CAS-No. | Concentration |
|---|-----------|---------------|
| Chromium oxide | 1308-38-9 | 0 - <0,1% |
| Copper and/or copper alloys and compounds (as Cu) | 7440-50-8 | 0 - <0,1% |

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

| Chemical name | CAS-No. | Concentration |
|---|------------|---------------|
| Titanium dioxide (naturally occurring) | 13463-67-7 | 10 - 20% |
| Vanadium pentoxide | 1314-62-1 | 0,1 - 1,0% |
| Copper and/or copper alloys and compounds (as Cu) | 7440-50-8 | 0 - <0,1% |

National Regulations

Water Hazard Class (WGK): WGK 3: severely water-endangering.

TA Luft, Technical Guidance Air:

| | |
|--------------------|--|
| Chromium oxide | Number 5.2.2 Class III, Inorganic dust-forming substance |
| Vanadium pentoxide | Number 5.2.2 Class III, Inorganic dust-forming substance |

| | |
|---|--|
| Manganese | Number 5.2.2 Class III, Inorganic dust-forming substance |
| Copper and/or copper alloys and compounds (as Cu) | Number 5.2.2 Class III, Inorganic dust-forming substance |

INRS, maladies professionnelles, table of work-related illnesses

Listed: A
44 bis
44
94
66

15.2 Chemical safety assessment:

No Chemical Safety Assessment has been carried out.

International regulations
Inventory Status:

| | |
|--|---|
| Australia AICS: | One or more components are not listed or are exempt from listing. |
| Canada DSL Inventory List: | One or more components are not listed or are exempt from listing. |
| Canada NDSL Inventory: | One or more components are not listed or are exempt from listing. |
| Ontario Inventory: | One or more components are not listed or are exempt from listing. |
| China Inv. Existing Chemical Substances: | On or in compliance with the inventory |
| Japan (ENCS) List: | One or more components are not listed or are exempt from listing. |
| Japan ISHL Listing: | One or more components are not listed or are exempt from listing. |
| Japan Pharmacopoeia Listing: | One or more components are not listed or are exempt from listing. |
| Korea Existing Chemicals Inv. (KECI): | On or in compliance with the inventory |
| Mexico INSQ: | One or more components are not listed or are exempt from listing. |
| New Zealand Inventory of Chemicals: | On or in compliance with the inventory |
| Philippines PICCS: | On or in compliance with the inventory |
| Taiwan Chemical Substance Inventory: | On or in compliance with the inventory |
| US TSCA Inventory: | One or more components are not listed or are exempt from listing. |
| EINECS, ELINCS or NLP: | One or more components are not listed or are exempt from listing. |

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

SECTION 16: Other information

Definitions:**References**

PBT PBT: persistent, bioaccumulative and toxic substance.
vPvB vPvB: very persistent and very bioaccumulative substance.

Key literature references and sources for data: According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

Wording of the H-statements in section 2 and 3

H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Other information: Additional information is available by request.

Issue Date: 26.01.2022

Disclaimer: The Lincoln Electric Company urges each end user and recipient of this SDS to study it carefully. See also www.lincolnelectric.com/safety. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond Lincoln Electric's control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and local laws and regulations remain the responsibility of the user.

© 2022 Lincoln Global, Inc. All Rights Reserved.

Annex to the extended Safety Data Sheet (eSDS)

Exposure Scenario:

Read and understand the “**Recommendations for Exposure Scenarios, Risk Management Measures and to identify Operational Conditions under which metals, alloys and metallic articles may be safely welded**”, which is available from your supplier and at <http://european-welding.org/health-safety>.

Welding/Brazing produces fumes which can affect human health and the environment. Fumes are a varying mixture of airborne gases and fine particles which, if inhaled or swallowed, constitute a health hazard. The degree of risk will depend on the composition of the fume, concentration of the fume and duration of exposure. The fume composition is dependent upon the material being worked, the process and consumables being used, coatings on the work such as paint, galvanizing or plating, oil or contaminants from cleaning and degreasing activities. A systematic approach to the assessment of exposure is necessary, taking into account the particular circumstances for the operator and ancillary worker that can be exposed.

Considering the emission of fumes when welding, brazing or cutting of metals, it is recommended to (1) arrange risk management measures through applying general information and guidelines provided by this exposure scenario and (2) using the information provided by the Safety Data Sheet, issued in accordance with REACH, by the welding consumable manufacturer.

The employer shall ensure that the risk from welding fumes to the safety and health of workers is eliminated or reduced to a minimum. The following principle shall be applied:

- 1- Select the applicable process/material combinations with the lowest class, whenever possible.
- 2- Set welding process with the lowest emission parameter.
- 3- Apply the relevant collective protective measure in accordance with class number. In general, the use of PPE is taken into account after all other measures is applied.
- 4- Wear the relevant personal protective equipment in accordance with the duty cycle.

In addition, compliance with the National Regulations regarding the exposure to welding fumes of welders and related personnel shall be verified.