

# SAFETY DATA SHEET



## MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

---

### SECTION 1. IDENTIFICATION

Product name : MM SUPER CONC FUEL INJ CLNR 12/12 OZ

Product code : M5212

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : OCTANE TREATMENT

Restrictions on use : Use only outdoors or in a well-ventilated area.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure

Specific target organ toxicity : Category 2 (Liver, thymus, Bone marrow)  
- repeated exposure

Aspiration hazard : Category 1

#### GHS label elements

**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

---

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

Flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Harmful if inhaled.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May cause damage to organs (Liver, thymus, Bone marrow) through prolonged or repeated exposure.

Precautionary statements

:

**Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version 6.0      Revision Date: 02/20/2019      SDS Number: 600000001450      Date of last issue: 10/26/2018  
Date of first issue: 07/13/2018

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Diesel fuel no. 2	68476-34-6	$\geq 90 - < 100$
Kerosene	8008-20-6	$\geq 30 - < 50$
Alkanes, C10-C20 branched and linear	928771-01-1	$\geq 1 - < 5$
Naphthalene	91-20-3	$\geq 1 - < 5$
Ethylbenzene	100-41-4	$\geq 0.1 - < 1$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.  
If unconscious, place in recovery position and seek medical advice.  
Keep patient warm and at rest.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.
- If swallowed : Obtain medical attention.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Harmful if inhaled.

**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Ensure adequate ventilation.  
Avoid breathing dust.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

# MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version 6.0      Revision Date: 02/20/2019      SDS Number: 600000001450      Date of last issue: 10/26/2018  
Date of first issue: 07/13/2018

miculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.  
Keep away from open flames, hot surfaces and sources of ignition.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Avoid contact with skin and eyes.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diesel fuel no. 2	68476-34-6	TWA (Inhalable fraction and vapor)	100 mg/m <sup>3</sup> (total hydrocarbons)	ACGIH
Kerosene	8008-20-6	TWA	100 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon)	ACGIH

## SAFETY DATA SHEET


**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

 Version  
6.0

 Revision Date:  
02/20/2019

 SDS Number:  
600000001450

 Date of last issue: 10/26/2018  
Date of first issue: 07/13/2018

			vapor)	
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0

**Hazardous components without workplace control parameters**

Components	CAS-No.
Alkanes, C10-C20 branched and linear	928771-01-1

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

# SAFETY DATA SHEET



## MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

Remarks	: Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.
Eye protection	: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Impervious clothing Safety shoes
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not smoke. When using do not eat or drink.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: red
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 154 - 366 °C
Flash point	: 58 °C Method: closed cup
Evaporation rate	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: 4.7 %(V)
Lower explosion limit / Lower flammability limit	: 0.6 %(V)
Vapour pressure	: 0.4 hPa (40 °C)
Relative vapour density	: No data available
Density	: 0.8014 g/cm3

# SAFETY DATA SHEET



## MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

---

Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Molecular weight	: No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents Strong acids Strong bases
Hazardous decomposition products	: Carbon oxides

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Eye contact  
Skin contact  
Ingestion

#### Acute toxicity

Harmful if inhaled.

#### **Product:**

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: 3.69 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method



**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

---

**Components:****Diesel fuel no. 2:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat, male and female): 4.1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): > 4,300 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Kerosene:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 420
- Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Alkanes, C10-C20 branched and linear:**

- Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

**Naphthalene:**

- Acute oral toxicity : LD50 (Mouse, male): 533 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,500 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Ethylbenzene:**

- Acute oral toxicity : LD50 (Rat): ca. 3,500 mg/kg

**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

---

Acute inhalation toxicity : LC50 (Rat): 4000 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 17,800 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:****Diesel fuel no. 2:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: Irritating to skin.

**Kerosene:**

Result: Irritating to skin.

**Naphthalene:**

Result: Possibly irritating to skin

**Ethylbenzene:**

Result: Irritating to skin.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****Diesel fuel no. 2:**

Species: Rabbit  
Result: Possibly irritating to eyes  
Method: OECD Test Guideline 405

**Kerosene:**

Result: Possibly irritating to eyes

**Naphthalene:**

Result: Possibly irritating to eyes

**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

---

**Ethylbenzene:**

Result: Irritating to eyes.

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Diesel fuel no. 2:**

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Diesel fuel no. 2:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)  
Result: positive

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**Carcinogenicity**

Suspected of causing cancer.

**Components:****Diesel fuel no. 2:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

**Naphthalene:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**Ethylbenzene:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

**MOTOR MEDIC® CONCENTRATED FUEL  
INJECTION SYSTEM TREATMENT**

Version 6.0	Revision Date: 02/20/2019	SDS Number: 600000001450	Date of last issue: 10/26/2018 Date of first issue: 07/13/2018
----------------	------------------------------	-----------------------------	---

**IARC** Group 2B: Possibly carcinogenic to humans

Naphthalene 91-20-3

Ethylbenzene 100-41-4

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** Reasonably anticipated to be a human carcinogen

Naphthalene 91-20-3

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Kerosene:**

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

May cause damage to organs (Liver, thymus, Bone marrow) through prolonged or repeated exposure.

**Components:****Diesel fuel no. 2:**

Target Organs: Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: thymus

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Bone marrow

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Ethylbenzene:**

Target Organs: Auditory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Components:****Diesel fuel no. 2:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET



## MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

### **Kerosene:**

May be fatal if swallowed and enters airways.

### **Alkanes, C10-C20 branched and linear:**

May be fatal if swallowed and enters airways.

### **Ethylbenzene:**

May be fatal if swallowed and enters airways.

### **Further information**

#### **Product:**

Remarks: No data available

## SECTION 12. ECOLOGICAL INFORMATION

### **Toxicity**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### **International Regulations**

#### **IATA-DGR**

UN/ID No. : UN 1268  
Proper shipping name : Petroleum distillates, n.o.s.  
Class : 3  
Packing group : III  
Labels : 3  
Packing instruction (cargo aircraft) : 366

# SAFETY DATA SHEET



## MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version 6.0      Revision Date: 02/20/2019      SDS Number: 600000001450      Date of last issue: 10/26/2018  
Date of first issue: 07/13/2018

Packing instruction : 355  
(passenger aircraft)

### IMDG-Code

UN number : UN 1268  
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### 49 CFR

UN/ID/NA number : UN 1268  
Proper shipping name : Petroleum distillates, n.o.s.  
  
Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Benzene	71-43-2	10	10 (D018)
Naphthalene	91-20-3	100	3932

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Acute toxicity (any route of exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

# SAFETY DATA SHEET



## MOTOR MEDIC® CONCENTRATED FUEL INJECTION SYSTEM TREATMENT

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2018
6.0	02/20/2019	600000001450	Date of first issue: 07/13/2018

Naphthalene	91-20-3	$\geq 1 - < 5 \%$
Ethylbenzene	100-41-4	$\geq 0.1 - < 1 \%$


### California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



Revision Date : 02/20/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN