

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

#### 1. Identification

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

**Product Code:** MAG62625

Other means of identification:

**Synonyms:** No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Motor Oil

**Restrictions on use:**Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

importer, or other responsible party:

Warren Distribution, Inc.

950 S. 10th St., Suite 300

Omaha, NE 68108-3296

**Phone number:** +01 (800) 825-1235 +01 (402) 341-9397

**E-mail address:** sds@wd-wpp.com

**Emergency phone number:** CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Not classified as hazardous under OSHA

Hazards not otherwise classified: No data available

### 3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	No data available	72623-87-1	30 - 60
Highly refined synthetic base stocks	No data available	64742-54-7	10 - 30
1-Decene, homopolymer, hydrogenated	No data available	68037-01-4	7 - 13
Petroleum distillates, hydrotreated heavy paraffinic	No data available	64742-54-7	5 - 10
Distillates, petroleum, solvent-	No data available	64742-56-9	1 - 5

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

**Product Code:** MAG62625 **Revision Date: 03-18-2021 Replaces:** 03-09-2021

dewaxed light paraffinic			
Paraffin oils, petroleum, catalytic	No data available	64742-70-7	1 - 5
dewaxed heavy			
Distillates, petroleum, solvent-	No data available	64742-65-0	1 - 5
dewaxed heavy paraffinic			
Amines, polyethylenepoly-,	No data available	84605-20-9	1 - 5
reaction products with Succinic			
anhydride polyisobutenyl			
derivitives			
Benzenamine, ar-nonyl-N-	No data available	36878-20-3	1 - 5
(nonylphenyl)-			
Alkyl phenol	No data available	125643-61-0	1 - 5

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

#### 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

Flush eyes with plenty of water for at least 20 minutes retracting eyelids Eye Contact:

often. Tilt the head to prevent chemical from transferring to the

uncontaminated eye. Get immediate medical attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or

persists.

Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical Ingestion:

attention immediately. Provide medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

No data available

Indication of immediate medical attention and special treatment

needed, if necessary:

No additional first aid information available.

#### 5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

**Product Code:** MAG62625 **Revision Date: 03-18-2021 Replaces:** 03-09-2021

> Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

> > fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the Material may be ignited only if preheated to temperatures above the

chemical: high flash point, for example in a fire.

**Hazardous combustion products:** Carbon monoxide, Sulfur containing gases, Nitrogen containing gases,

oxides of phosphorus, Hydrogen sulfide

Special protective equipment and

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the precautions for fire-fighters:

surrounding fire.

#### 6. Accidental release measures

Personal precautions, protective No health affects expected from the clean up of this material if contact equipment and emergency procedures: can be avoided. Follow personal protective equipment recommendations

found in Section 8 of this SDS.

Methods and materials for containment

and cleaning up:

No special spill clean up considerations. Collect and discard in regular

trash.

#### 7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. Follow all

protective equipment recommendations provided in Section 8.

Conditions for safe storage, including

any incompatibilities:

Safe storage conditions: Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

#### 8. Exposure controls/personal protection

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Lubricating oils	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available
(petroleum), C20-50,				
hydrotreated neutral oil-				
based				
Highly refined synthetic	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available
base stocks				
Petroleum distillates,	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available
hydrotreated heavy				
paraffinic				
Distillates, petroleum,	5 mg/m3 TWA	5 mg/m3 TWA	10 mg/m3 STEL	No data available
solvent-dewaxed heavy				
paraffinic				

**Appropriate engineering controls:** Use local exhaust ventilation or other engineering controls to minimize

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

**Respiratory Protection:** Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

**Respirator Type(s):**None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

**Eye protection:** Wear chemically resistant safety glasses with side shields when handling

this product. Do not wear contact lenses.

**Skin protection:** Where use can result in skin contact, practice good personal hygiene and

wear impervious gloves. Wash hands and other exposed areas with mild

soap and water before eating, drinking, and when leaving work.

Gloves: Nitrile, Neoprene

**General hygiene conditions:** Follow all protective equipment recommendations provided in Section 8.

#### 9. Physical and chemical properties

Appearance (physical state, color etc.):

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

Physical state: Liquid
Color: Brown
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data availableInitial boiling point and boiling rangeNo data available

(°C):

Flash Point (°C): 224

**Evaporation Rate**: No data available **Flammability (solid, gas)**: No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Not established

Lower flammability or explosive

limits:

Not established

Vapor pressure:No data availableVapor density:No data available

Relative density: 0.86

Solubility(ies):

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

No data available

No data available

No data available

Not determined

Viscosity: 87.42

#### 10. Stability and reactivity

**Reactivity:** There are no known reactivity hazards associated with this product.

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** None expected under standard conditions of storage.

**Conditions to avoid (e.g., static**Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

Moisture (will lead to product performance degradation).

**Incompatible materials:** Strong oxidizing agents

**Hazardous decomposition products:** Carbon monoxide, Sulfur containing gases, Nitrogen containing gases,

oxides of phosphorus, Hydrogen sulfide

### 11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Skin contact, Inhalation, Ingestion, Eye contact

Symptoms related to the physical,

chemical and toxicological

characteristics:

No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

**Ingestion:** Estimated to be > 5.0 g/kg.

**Skin Contact:** This material is likely to be slightly irritating to skin based on animal

data. Can cause minor skin irritation, defatting, and dermatitis.

**Absorption:** May be harmful in contact with skin.

**Inhalation:** No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

**Eye Contact:** The material is likely to be moderately irritating to eyes based on animal

data. Can cause moderate irritation, tearing and reddening, but not likely

to permanently injure eye tissue.

Sensitization: Non-hazardous under Respiratory Sensitization category. No data

available to indicate product or components may be a skin sensitizer.

**Mutagenicity:**No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

**Carcinogenicity:** Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

**Reproductive toxicity**Not known or reported to cause reproductive or developmental toxicity.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

**Aspiration hazard:** Based on available data, the classification criteria are not met.

Other information: None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Amines, polyethylenepoly- , reaction products with Succinic anhydride polyisobutenyl derivitives	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/L	
Benzenamine, ar-nonyl-N- (nonylphenyl)-	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	
Distillates, petroleum, solvent-dewaxed light paraffinic	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 5399 MG/M3
Paraffin oils, petroleum, catalytic dewaxed heavy	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	
Distillates, petroleum, solvent-dewaxed heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 2400 MG/M3
Petroleum distillates, hydrotreated heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	
1-Decene, homopolymer, hydrogenated	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	
Highly refined synthetic base stocks	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.2 mg/L

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

### 12. Ecological information

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

**Product Code: MAG62625 Revision Date: 03-18-2021 Replaces:** 03-09-2021

Ecotoxicity (aquatic and terrestrial, where available):

Slight ecological hazard. In high concentrations, this product may be

dangerous to plants and/or wildlife.

**Ecological Toxicity Data:** 

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Alkyl phenol	125643-61-0	No data available	No data available	LC50 (96h) DANIO RERIO > 1000 mg/L
Benzenamine, ar-nonyl-N- (nonylphenyl)-	36878-20-3	EC50 (48h) Daphnia magna > 100 mg/L	EC50 (72h) Green Algae > 100 mg/L	LC50 (96h) Pimephales promelas (Fathead Minnow) > 1000 mg/L
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9	LC50 (48h) > 1000 mg/L	No data available	LC50 (96h) > 5000 mg/L
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
1-Decene, homopolymer, hydrogenated	68037-01-4	EC50 (48h) Daphnia magna 190 mg/L	No data available	LC50 (96h) Rainbow Trout > 1000 mg/L
Highly refined synthetic base stocks	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability: Biodegrades slowly.

Bioaccumulative potential: Bioconcentration may occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as hazardous to the ozone layer):

None known.

13. Disposal considerations

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

Spent or discarded material is non-hazardous according to environmental

regulations.

packaging:

**Contaminated packaging:** Recycle containers whenever possible.

### 14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

**DOT Basic Description:**Not regulated for road transport

International carriage of dangerous goods by sea (IMDG/IMO):

**UN number:**Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

**UN number:**Not regulated by IATA

UN Proper shipping name:Not applicableTransport hazard class(es):Not applicablePacking group, if applicable:Not applicable

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

#### 15. Regulatory information

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

### Safety, health and environmental regulations specific for the product in question:

**TSCA Status:** All components of this material are on the Active US TSCA Inventory or

are exempt.

### **Regulated Components:**

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N
Highly refined synthetic base stocks	64742-54-7	N	N	N	N
1-Decene, homopolymer, hydrogenated	68037-01-4	N	N	N	N
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N
Distillates, petroleum, solvent- dewaxed light paraffinic	64742-56-9	N	N	N	N
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	N	N	N	N
Paraffin oils, petroleum, catalytic dewaxed heavy	64742-70-7	N	N	N	N
Amines, polyethylenepoly-, reaction products with Succinic anhydride polyisobutenyl derivitives	84605-20-9	N	N	N	N
Alkyl phenol	125643-61- 0	N	N	N	N
Benzenamine, ar- nonyl-N- (nonylphenyl)-	36878-20-3	N	N	N	N

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N
Highly refined synthetic base stocks	64742-54-7	N	N	N	N
1-Decene, homopolymer, hydrogenated	68037-01-4	N	N	N	N
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N
Distillates, petroleum, solvent- dewaxed light paraffinic	64742-56-9	N	N	N	N
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	N	N	N	N
Paraffin oils, petroleum, catalytic dewaxed heavy	64742-70-7	N	N	N	N
Amines, polyethylenepoly-, reaction products with Succinic anhydride polyisobutenyl derivitives	84605-20-9	N	N	N	N
Alkyl phenol	125643-61- 0	N	N	N	N
Benzenamine, ar- nonyl-N- (nonylphenyl)-	36878-20-3	N	N	N	N

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

Chemical Name	CAS#	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N	N
Highly refined synthetic base stocks	64742-54-7	N	N	N	N	N
1-Decene, homopolymer, hydrogenated	68037-01-4	N	N	N	N	N
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N	N
Distillates, petroleum, solvent- dewaxed light paraffinic	64742-56-9	Υ	N	N	N	N
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	N	N	N	N	N
Paraffin oils, petroleum, catalytic dewaxed heavy	64742-70-7	Υ	N	N	N	N
Amines, polyethylenepoly-, reaction products with Succinic anhydride polyisobutenyl derivitives	84605-20-9	N	N	N	N	N
Alkyl phenol	125643-61- 0	N	N	N	N	N
Benzenamine, ar- nonyl-N- (nonylphenyl)-	36878-20-3	N	N	N	N	N

16. Other information, including date of preparation or last revision.

Product identifier used on the label: MAG 1 FLT 5W40 CK4FS 6/1Q

Product Code: MAG62625 Revision Date: 03-18-2021 Replaces: 03-09-2021

SDS Prepared by: MCHONGOOFAFA

**Revision Date:** 03-18-2021

Revision Number: 25

**Reason for revision:** Activated by Document Formulation Generation

References: No data available
Other Info: No data available

**Disclaimer:** This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.