



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Full Synthetic Moly Fortified Gray Grease
Product code : VV985

Details of the supplier of the safety data sheet

Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling.
Wear eye protection/ face protection.
Response:
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:
98.9999 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	Skin Irrit. 2; H315 Eye Dam. 1; H318	≥ 1.00 - < 1.50
MOLYBDENUM DISULFIDE	1317-33-5	Not a hazardous substance or mixture.	≥ 1.00 - < 1.50

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and : No symptoms known or expected.
Causes serious eye irritation.



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

delayed

Notes to physician : No hazards which require special first aid measures.
Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Unsuitable extinguishing media : High volume water jet

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

- Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
MOLYBDENUM DISULFIDE	1317-33-5	TWA	15 mg/m3 total dust (Molybdenum)	OSHA Z-1
		TWA	10 mg/m3 Inhalable particulate matter (Molybdenum)	ACGIH
		TWA	3 mg/m3 Respirable particulate matter (Molybdenum)	ACGIH
		TWA	10 mg/m3 Total dust (Molybdenum)	OSHA P0
		PEL	10 mg/m3 Total dust (Molybdenum)	CAL PEL
		PEL	3 mg/m3 respirable dust fraction (Molybdenum)	CAL PEL

Personal protective equipment

- Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

No personal respiratory protective equipment normally required.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: dark grey
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: 500 °F / 260 °C
Boiling point/boiling range	: 700 °F / 371 °C
Flash point	: 439 °F / 226 °C



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9084 g/cm ³ (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 599 °F / > 315 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: None known. None known. No data available
Incompatible materials	: Strong oxidizing agents Not applicable
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): 93,458 mg/kg
Method: Acute toxicity estimate

Acute dermal toxicity : LD50 (Rabbit): 2,599 mg/kg
Method: Acute toxicity estimate

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Remarks: The toxicological data has been taken from products of similar composition.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: The toxicological data has been taken from products of similar composition.

MOLYBDENUM DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

Product:

Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result : Irritating to skin.

MOLYBDENUM DISULFIDE:

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result : Corrosive

MOLYBDENUM DISULFIDE:

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Aquatic invertebrates): > 10 - 100 mg/l
Exposure time: 48 h
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to algae : EC50 (green algae): > 10 - 100 mg/l
Exposure time: 72 h
Remarks: The toxicological data has been taken from products of similar composition.

Persistence and degradability

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Biodegradability : Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

CFR_ROAD

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	>= 1 - < 5 %
---	------------	--------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	>= 1 - < 5 %
---	------------	--------------

This product does not contain any priority pollutants related to the U.S. Clean Water Act

The components of this product are reported in the following inventories:



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

TCSI	: Not in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory
AIIC	: Not in compliance with the inventory
DSL	: This product contains the following components that are not on the Canadian DSL nor NDSL.
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: Not in compliance with the inventory
TECI	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : R0257033

NFPA:

HMIS III:



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p>	<table border="1"><tr><td>HEALTH</td><td>2/</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table>	HEALTH	2/	FLAMMABILITY	1	PHYSICAL HAZARD	0
	HEALTH	2/					
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H315 Causes skin irritation.
H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).



SAFETY DATA SHEET

Valvoline™ Full Synthetic Moly Fortified Gray Grease

Version: 1.4

Revision Date: 10/22/2021

Print Date:
04/26/2023

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System