

Race Glaze Polish Sealant

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives

SECTION 1. PRODUCT IDENTIFICATION

1.1 TRADE NAME (AS LABELED): RACE GLAZE POLISH SEALANT - 15159, 15165

SYNONYMS: Polymer Emulsion

CAS#: Mixture

1.2 PRODUCT USE:Automotive Polish/Sealant1.3 MANUFACTURER'S NAME:ChemRite CoPac, Inc

ADDRESS: 19725 W. Edgewood Dr., Lannon, WI 53046

BUSINESS PHONE: 1-262-255-3880

WEB SITE INFORMATION: http://chemritecopac.com/

1-262-255-3880

DATE OF CURRENT REVISION:

DATE OF LAST REVISION:

1-262-255-3880

January 23, 2019

September 17, 2014

SECTION 2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: This product is an opaque white liquid with a solvent odor.

Health Hazards: May cause eye irritation. Harmful if swallowed, aspiration hazard.

Flammability Hazards: This product is a combustible liquid with a flash point of 152°F (66.6°C).

Reactivity Hazards: None known

Environmental Hazards: The Environmental effects of this product have not been investigated. Release of this

product is not anticipated to have significant adverse effects in the aquatic environment.

2.1 GHS LABELING AND CLASSIFICATION:

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 and regulation (EU) No. 2015/830 and regulation (EC) No. 1272/2008.

Index Number:

EC# 265-067-2 This substance is classified in the Annex VI Index# 649-275-00-4

EC# 265-149-8 This substance is classified in the Annex VI Index# 649-422-00-2

Remaining components are not classified in Annex VI

Substances not listed either individually or in group entries must be self-classified.

Component(s) Contributing to Classification(s)

Naphtha, Petroleum, Heavy Alkylate, Distillates (Petroleum) Hydrotreated Light

2.2 LABEL ELEMENTS

GHS Hazard Symbol(s)



Signal Word: Danger!

GHS Hazard Classification(s):

Flammable Liquid Category 4

Aspiration Hazard Category 1

Hazard Statement(s):

H227: Combustible liquid

H304: May be fatal if swallowed and enters airways

Prevention Statement(s):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P262: Do not get in eyes, on skin, or on clothing

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves/protective clothing/eye protection/face protections.



Harley Glaze Poly Sealant 15060, 15062

Response Statement(s):

P370+P378: In case of fire: Use media defined in Section 5 to extinguish.

P314: Get medical advice/attention if you feel unwell.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

Storage Statement(s):

P403: Store in a well-ventilated place.

P405: Store locked up. Disposal Statement(s):

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 OTHER HAZARDS:

None Applicable

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS#	EINECS#	Hazard Classification
Water	55-65%	7732-18-5	231-731-2	Not Classified
Naphtha, Petroleum, Heavy Alkylate	5-15%	64741-65-7	265-067-2	Asp. Tox Cat 1 (Note P)
Distillates (Petroleum) Hydrotreated Light	1-10%	64742-47-8	265-149-8	Asp. Tox Cat 1
Anhydrous Aluminum Silicate	1-10%	22708-90-3	245-167-2	Not Classified
Aminofunctional Siloxane	1-5%	71750-80-6	615-337-4	Skin Irrit. Cat 2, Eye Irrit. Cat 2A

Exact concentrations withheld as trade secret.

4. FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for several minutes. Remove contact lenses if present and easy to do. Continue rinseing for at least 15 minutes. Seek medical attention.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with pre-existing skin conditions may be more susceptible to adverse effects.

4.2 SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

May cause eye irritation. Harmful if swallowed, aspiration hazard.

4.3 RECOMMENDATIONS TO PHYSICIANS:

Treat symptoms and eliminate overexposure.

SECTION 5. FIRE-FIGHTING MEASURES

5.1 FIRE EXTINGUISHING MATERIALS:

Use fire extinguishing methods below:

Water Spray:YesCarbon Dioxide:YesFoam:YesDry Chemical:Yes

Halon: Yes Other: Any "C" Class

5.2 UNUSUAL FIRE AND EXPLOSION HAZARDS:

None anticipated

Explosion Sensitivity to Mechanical Impact: No Explosion Sensitivity to Static Discharge: No





Harley Glaze Poly Sealant 15060, 15062

5.3 SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive area.

NFPA RATING SYSTEM





Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Provide adequate ventilation. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas. Do not touch or walk through spilled material.

6.2 ENVIRONMENTAL PRECAUTIONS:

Construct a dike to prevent spreading. Runoff from fire control or dilution water may cause pollution. Spills may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies.

6.3 SPILL AND LEAK RESPONSE:

Move containers from spill area. Prevent entry into sewers, water courses, basement or confined areas. Stop the flow of material, if this can be done safety. Eliminate sources of ignition. Contain discharged material. Absorb spill using an absorbent, non-combustible material such as earth, sand, or vermiculite. Place in a proper container for disposal. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

SECTION 7. HANDLING and STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

To prevent skin and eye contact under the foreseeable conditions of use, wear appropriate protective clothing and safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Handle in a well-ventilated work area.

7.2 STORAGE AND HANDLING PRACTICES:

Store in original container. Keep container closed. Store in a cool, dry, well ventilated area. Avoid freezing or extended storage in high temperatures and away from incompatible materials.

7.3 SPECIFIC USES:

Automotive Polish/Sealant

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 EXPOSURE PARAMETERS:

No data available for this product.



Harley Glaze Poly Sealant 15060, 15062

8.2 EXPOSURE CONTROLS:

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Not normally required when using this product. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or goggles are recommended. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

HAND PROTECTION: Gloves are recommended to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

BODY PROTECTION: Use body protect appropriate to task being performed. If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

SECTION 9. PHYSICAL and CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE (Physical State) and COLOR: This product is an opaque white liquid with a solvent odor.

ODOR: Mild

ODOR THRESHOLD: Not Applicable

pH: Not Available

MELTING/FREEZING POINT: Not Available

BOILING POINT: Not Available **FLASH POINT:** 152°F (66.6°C)

EVAPORATION RATE (Water=1): 1.38

FLAMMABILITY (SOILD, GAS): Not Applicable

UPPER/LOWER FLAMMABILITY OR EXLOSION LIMITS: Not Applicable

VAPOR PRESSURE (mm Hg @ 20°C (68°F): >.50 MMHG

VAPOR DENSITY: Not Available RELATIVE DENSITY: Not Available SPECIFIC GRAVITY: 0.9768 (Typical) SOLUBILITY IN WATER: Insoluble WEIGHT PER GALLON: Not Available

PARTITION COEFFICENT (n-octanol/water): Not Available

AUTO-IGNITION TEMPERATURE: Not Applicable DECOMPOSITION TEMPERATURE: Not Available

VISCOSITY: Not Available 9.2 OTHER INFORMATION:

No additional information available at this time.

SECTION 10. STABILITY and REACTIVITY

10.1 REACTIVITY:

No data available

10.2 STABILITY:

Stable under conditions of normal storage and use.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Will not occur.

10.4 CONDITIONS TO AVOID:

Incompatible materials and sources of ignition.

ChemRite CoPac, Inc.

Page 4 of 7



Harley Glaze Poly Sealant 15060, 15062

10.5 MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:

Strong oxidizing materials.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition products include carbon dioxide and carbon monoxide.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

TOXICITY DATA:

Naphtha Petroleum CAS# 64741-65-7

Acute oral toxicity (LD50): >2000 mg/kg [Rat].

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Based on available data, the classification criteria are not met
Serious eye damage / irritation	Based on available data, the classification criteria are not met
Respiratory or skin sensitization	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Aspiration Hazard Category 1

ROUTE OF EXPOSURE: The most significant routes of overexposure for this product are by contact with skin or eyes. The symptoms of overexposure are described below.

ACUTE:

INHALATION: No data available

CONTACT WITH SKIN: Prolonged and repeated contact may cause irritation to skin.

EYE CONTACT: Direct eye contact can cause irritation with redness, tearing and blurred vision.

INGESTION: Aspiration hazard. Ingestion of large amounts may cause gastrointestinal irritation, nausea and vomiting.

CHRONIC: Prolonged exposure can be irritating to skin.

TARGET ORGANS: Acute: Lungs Chronic: Central Nervous System

SUSPECTED CANCER AGENT: Ingredients within this product are not found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

IRRITANCY OF PRODUCT: This product may be irritating to the eyes.

SENSITIZATION TO THE PRODUCT: This product is not expected to be a skin or respiratory sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No specific information is available concerning the effects of this product and its components on the human reproductive system.

SECTION 12. ECOLOGICAL INFORMATION

12.1 TOXICITY:

No specific data available on this product.

12.2 PERSISTENCE AND DEGRADABILITY:

No specific data available on this product.

12.3 BIOACCUMULATIVE POTENTIAL:

No specific data available on this product.

12.4 MOBILITY IN SOIL:

No specific data available on this product.

12.5 RESULTS OF PBT AND vPvB ASSESSMENT:

No specific data available on this product.

12.6 OTHER ADVERSE EFFECTS:

No specific data available on this product.

12.7 WATER ENDANGERMENT CLASS:

May be water endangering in accordance with EU Guideline 91/155-EWG. Do not allow product to reach ground water, water course or sewage system. At present there are no ecotoxicological assessments for this product.

ChemRite CoPac, Inc.



Harley Glaze Poly Sealant 15060, 15062

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS:

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

13.2 EU WASTE CODE:

Not determined.

SECTION 14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

14.1 U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

NOTE: Combustible liquids may be shipped as Limited Quantities if packaged as described in 49 CFR 173.150 (b) if the inner packaging is not over 5 L. The requirements of 49 CFR Subchapter C do not apply to any material classed as a combustible liquid in a non-bulk packaging (49 CFR 173.150 (f)(2). Bulk packaging means packaging other than vessel or barge that has a maximum capacity greater than 450 L (119 gal) for liquid (49 CFR 171.8).

UN IDENTIFICATION NUMBER: NA1993

PROPER SHIPPING NAME: Combustible liquid, n.o.s. (Contains Naphtha Petroleum)

HAZARD CLASS NUMBER and DESCRIPTION: Class 3, combustible liquid

PACKING GROUP: PGIII

DOT LABEL(S) REQUIRED: Combustible liquid **NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER:** 128

RQ QUANTITY: None

MARINE POLLUTANT: The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is considered as dangerous goods.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): This product is considered as dangerous goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.

SECTION 15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE: UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA 311/312: Acute Health Hazard.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory or are exempted from listing.

OTHER U.S. FEDERAL REGULATIONS: None known

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product does not contain ingredients on the Proposition 65 Lists.

15.2 CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: Components are DSL Listed, NDSL Listed and/or are exempt from listing **OTHER CANADIAN REGULATIONS:** Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This product has been classified per WHMIS 2015.



Harley Glaze Poly Sealant 15060, 15062

15.3 EUROPEAN ECONOMIC COMMUNITY INFORMATION:

This product does meet the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

See Section 2 for Details

CHEMICAL SAFETY ASSESSMENT:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 AUSTRALIAN INFORMATION FOR PRODUCT: Components of this product are listed on the International Chemical Inventory list.

15.5 JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Listed

Australian Inventory of Chemical Substances (AICS): Listed

Korean Existing Chemicals List (ECL): Listed

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed Philippines Inventory if Chemicals and Chemical Substances (PICCS): Listed

Swiss Giftliste List of Toxic Substances: Listed

U.S. TSCA: Listed

SECTION 16. OTHER INFORMATION

PREPARED BY:Chris EigbrettMSDS to GHS ComplianceDATE OF PRINTING:January 23, 2019www.MSDStoGHS.com

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. ChemRite CoPac, Inc. assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are no adhered to as stipulated in the data sheet. Furthermore, ChemRite CoPac, Inc. assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.

END OF SDS SHEET

ChemRite CoPac, Inc.