

SAFETY DATA SHEET

Revision Date 21-Jun-2018 Version 2

1. IDENTIFICATION

Product identifier

Product Name Rain-X Original Glass Water Repellent Wipes

Other means of identification

Product Code 11891

Document SKU: 630021;630061

Recommended use of the chemical and restrictions on use

Recommended Use Glass Treatment, Consumer Use

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address Manufactured and Distributed by:

ITW Global Brands 16200 Park Row, Suite 120 Houston, TX 77084

Distributor May Also Be Distributed by:

Company Phone Number 1-855-888-1988

24-hour emergency phone number

(CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)

(RMPDC) 1-877-504-9352 (U.S.)

E-mail address: SDS@itwgb.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2	
Specific target organ toxicity (single exposure)	Category 3	

Label elements

Emergency Overview

Signal word Warning

Causes serious eye irritation May cause drowsiness or dizziness



Revision Date 21-Jun-2018

Appearance Clear Colorless Physical state Liquid Odor Alcohol

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
ETHANOL	64-17-5	30 - 60
ACETONE	67-64-1	10 - 30
Isopropanol	67-63-0	10 - 30

Any concentration shown as a range is due to batch variation.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Take off contaminated clothing and wash before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Revision Date 21-Jun-2018

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, sand, earth, water spray or regular foam

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable vapors may be present even at temperatures below the flash point.

Explosion data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge No information available.

May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and

inhalation of vapors. Use personal protective equipment as required. ELIMINATE all ignition

sources (no smoking, flares, sparks or flames in immediate area).

Environmental precautions

Environmental precautions See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity). Keep out of the reach of children.

Incompatible materials None known

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Isopropanol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses or goggles if splashing is likely to occur.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Clear Colorless

Odor Alcohol

Odor threshold No information available

Property Values Remarks • Method

pH 1.5 - 2.5

Melting point / freezing pointNo information availableBoiling point / boiling rangeNo information available No

information available

Flash point -3 °C / 27 °F Setaflash Closed Cup

11891 - Rain-X Original Glass Water Repellent Wipes

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Relative density 0.810 - 0.812 Water solubility Soluble in water

Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity Dynamic viscosity No information available No information available **Explosive properties** Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 89

Density 0.806 - 0.808 g/cm3 **Bulk density** No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Excessive heat.

Incompatible materials

None known

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract. May be harmful if inhaled.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes. May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
64-17-5			
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h

67-64-1			
Isopropanol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
67-63-0			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHANOL	A3	-	Known	Χ
64-17-5				
Isopropanol 67-63-0	-	Group 3	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Blood, Central nervous system, Eyes, Liver, Reproductive System, Respiratory system,

Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 9100 mg/kg ATEmix (dermal) 27060 mg/kg ATEmix (inhalation-dust/mist) 120.1 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.75 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

Chemical Name	Partition coefficient
ETHANOL	-0.32
64-17-5	
ACETONE	-0.24
67-64-1	
Isopropanol	0.05
67-63-0	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations. Recover or recycle if possible. This material, as supplied, is a hazardous waste

according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001, U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
ETHANOL	Toxic	
64-17-5	Ignitable	
ACETONE	Ignitable	
67-64-1	-	
Isopropanol	Toxic	
67-63-0	Ignitable	

14. TRANSPORT INFORMATION

DOT

UN/ID no UN 1987

Proper shipping name: Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ)

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN/ID no UN 1987

Proper shipping name: Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ)

Hazard Class 3
Packing Group ||

IMDG

UN/ID no UN 1987

Proper shipping name: Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ)

Hazard Class 3
Packing Group ||

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Does not comply Complies **IECSC KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	=	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as a alcoholic beverage, Intended use for this product does not include consumption

Chemical Name	California Proposition 65	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ETHANOL 64-17-5	Х	X	Х
ACETONE 67-64-1	Х	X	X
Isopropanol 67-63-0	X	X	X
WATER 7732-18-5	-	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials, B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 -

Health hazards 2 Flammability 3 Physical hazards 1 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

21-Jun-2018

Revision Note 4

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet