

MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/02/2019

 2.0
 07/25/2019
 600000001756
 Date of first issue: 04/02/2019

SECTION 1. IDENTIFICATION

Product name : MM PSF - EUROPEAN & NISSAN 12/12OZ

Product code : M2712SYN

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : POWER STEERING FLUID

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : May cause an allergic skin reaction.

Precautionary statements : Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the

workplace.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/02/2019

 2.0
 07/25/2019
 600000001756
 Date of first issue: 04/02/2019

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-55-8	>= 1 - < 5
Mineral Oil (described by one of more of	Not Assigned	>= 1 - < 5
following CAS No : 64742-54-7, 64742-65-		
0, 64742-55-8 and 64742-56-9)		
Substituted hydrocarbyl sulfide	Not Assigned	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If no CAS number is identified, the component is considered trade secret.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

IF INHALED: Call a POISON CENTER/ doctor if you feel un-

well.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Seek medical advice.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms : May cause an allergic skin reaction.



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

Version Revision Date: SDS Number: Date of last issue: 04/02/2019 2.0 07/25/2019 600000001756 Date of first issue: 04/02/2019

and effects, both acute and delayed

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations pear the

lights, other flames and ignition sources at locations near the point of release.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

Version Revision Date: SDS Number: Date of last issue: 04/02/2019 2.0 07/25/2019 600000001756 Date of first issue: 04/02/2019

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Avoid contact with skin and eyes.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal-	5 mg/m3	ACGIH
		able fraction)		
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Mineral Oil (described by one of more of following CAS No: 64742-54-7, 64742-65-0, 64742-55-8 and 64742-56-9)	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Hazardous components without workplace control parameters

Components	CAS-No.
Substituted hydrocarbyl sulfide	Not Assigned

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

Version Revision Date: SDS Number: Date of last issue: 04/02/2019 2.0 07/25/2019 600000001756 Date of first issue: 04/02/2019

applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : green-brown

Odour : not determined

Odour Threshold : not determined

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : > 220 °C

Value for Component

Flash point : 153 °C

Method: closed cup Value for Component

Evaporation rate : not determined

Flammability (solid, gas) : No data available

Self-ignition : not determined

Upper explosion limit / Upper

flammability limit

not determined



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/02/2019

 2.0
 07/25/2019
 600000001756
 Date of first issue: 04/02/2019

Lower explosion limit / Lower

flammability limit

not determined

Vapour pressure : not determined

Relative vapour density : not determined

Density : 0.8367 g/cm3

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

octanol/water

not determined

Decomposition temperature : not determined

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: 6.44 mg/l

Exposure time: 4 h



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/02/2019

 2.0
 07/25/2019
 600000001756
 Date of first issue: 04/02/2019

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 3,066 mg/kg

Method: Calculation method

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Distillates (petroleum):

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin. Unlikely to cause eye irritation or injury.

Components:

Distillates (petroleum):

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: May cause allergic skin reaction.

Components:

Substituted hydrocarbyl sulfide:

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/02/2019

 2.0
 07/25/2019
 600000001756
 Date of first issue: 04/02/2019

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Mineral Oil (described by one of more of following CAS No : 64742-54-7, 64742-65-0, 64742-55-8 and 64742-56-9):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

Version Revision Date: SDS Number: Date of last issue: 04/02/2019 2.0 07/25/2019 600000001756 Date of first issue: 04/02/2019

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Butanol normal	71-36-3	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Phosphoric acid	7664-38-2	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Sulfur dioxide	7446-09-5	500	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



MOTOR MEDIC® EUROPEAN & NISSAN POWER STEERING FLUID

Version Revision Date: SDS Number: Date of last issue: 04/02/2019 2.0 07/25/2019 600000001756 Date of first issue: 04/02/2019


California Prop. 65

WARNING: This product can expose you to chemicals including Trimethyl phosphate, Ethyl Acrylate, Naphthalene, Benzene, which is/are known to the State of California to cause cancer, and Sulfur dioxide, Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 07/25/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN