



Hybrid Solutions Wet Wax

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
US GHS SDS
Revision Date: 10/28/2020

Supersedes Date:
07/23/2019

Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Hybrid Solutions Wet Wax

Product Code: 53410

1.2. Intended Use of the Product

Use of the Substance/Mixture: Automotive Wax, Polish, Sealant & Glaze – Instant Detailer

1.3. Name, Address, and Telephone of the Responsible Party

Manufacturer

Turtle Wax, Inc.

2250 W. Pinehurst Blvd., Suite 150

Addison, IL 60101-6103

Phone Number: 1(630)455-3700

Toll-Free Number: 1(800)887-8539

1.4. Emergency Telephone Number

Emergency Number

: CHEMTREC

Within USA and Canada: 1-800-424-9300 or +1-703-527-3887 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Not classified

2.2. Label Elements

GHS-US Labeling

No labeling applicable according to 29 CFR 1910.1200.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	%	GHS US classification
Isopropyl alcohol	Isopropanol / 2-Hydroxypropane / 2-Propyl alcohol / 2-Propanol	(CAS-No.) 67-63-0	1-5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-Butoxyethanol	Butoxyethanol / 2-Butoxy-1-ethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether	(CAS-No.) 111-76-2	0.1-1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Hybrid Solutions Wet Wax

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Wash with plenty of soap and water. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: No data available

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Thermal decomposition generates: Oxides of silicon and carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: As supplied, this product is a liquid. However, when dried this product may produce combustible dust when processed. Use caution when working with combustible dusts. Use appropriate engineering controls to keep generation of airborne dust to a minimum.

Hybrid Solutions Wet Wax

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.
Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Automotive Wax, Polish, Sealant & Glaze – Instant Detailer

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background, nonspecific)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) [ppm]	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) [ppm]	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	200 mg/g Kreatinin Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	24 mg/m ³
USA NIOSH	NIOSH REL (TWA) [ppm]	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption

8.2. Exposure Controls

Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye and Face Protection

: Chemical goggles or safety glasses.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Thermal Hazard Protection

: If material is hot, wear thermally resistant protective gloves.

Hybrid Solutions Wet Wax

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Environmental Exposure Controls	: Avoid contamination of soil, drains, and water during handling.
Consumer Exposure Controls	: Wear recommended personal protective equipment.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Translucent/Hazy White
Odor	: Fruity
Odor Threshold	: No data available
pH	: 4.00
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: > 93 °C - Closed Cup (199.4 °F)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 0.984
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Viscosity, Dynamic	: Water Thin
%Voc	: 1.75
%Nvm	: 2.0

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition may produce : Silicon oxides. Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified (Based on available data, the classification criteria are not met)

Acute Toxicity (Dermal): Not classified (Based on available data, the classification criteria are not met)

Acute Toxicity (Inhalation): Not classified (Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
LD50 Dermal Rabbit	12956 mg/kg (16.4 mL/kg bw)
LC50 Inhalation Rat	72600 mg/m ³ (Exposure time: 4 h)
2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rabbit	435 mg/kg
LC50 Inhalation Rat	2.2 mg/l/4h
LC50 Inhalation Rat	486 ppm/4h

Skin Corrosion/Irritation: Not classified (Based on available data, the classification criteria are not met)

pH: 4.00

Serious Eye Damage/Irritation: Not classified (Based on available data, the classification criteria are not met)

Hybrid Solutions Wet Wax

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

pH: 4.00

Respiratory or Skin Sensitization: Not classified (Based on available data, the classification criteria are not met)

Germ Cell Mutagenicity: Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity: Not classified (Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
IARC group	3
2-Butoxyethanol (111-76-2)	
IARC group	3

Reproductive Toxicity: Not classified (Based on available data, the classification criteria are not met)

Specific Target Organ Toxicity (Single Exposure): Not classified (Based on available data, the classification criteria are not met)

Specific Target Organ Toxicity (Repeated Exposure): Not classified (Based on available data, the classification criteria are not met)

Aspiration Hazard: Not classified (Based on available data, the classification criteria are not met)

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodemus subspicatus)
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
2-Butoxyethanol (111-76-2)	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

12.2. Persistence and Degradability

Hybrid Solutions Wet Wax	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Hybrid Solutions Wet Wax	
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (at 25 °C)
2-Butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (at 25 °C)

12.4. Mobility in Soil

Hybrid Solutions Wet Wax	
Ecology - Soil	Adsorbs into the soil.

12.5. Other Adverse Effects

Other Adverse Effects : None known.

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Treatment Methods: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Sewage Disposal Recommendations: Do not dispose of waste into sewer.

Hybrid Solutions Wet Wax

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

Waste Disposal Recommendations: Non hazardous waste – landfill or incinerate. Comply with local regulations for disposal.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

Isopropyl alcohol (67-63-0)	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (only if manufactured by the strong acid process, no supplier notification)

15.2. US State Regulations

Isopropyl alcohol (67-63-0)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
2-Butoxyethanol (111-76-2)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 10/28/2020

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:


Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness

Hybrid Solutions Wet Wax

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
US GHS SDS

NFPA Health Hazard	: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
NFPA Fire Hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA Reactivity Hazard	: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.
HMIS III Rating	
Health	: 0 Minimal Hazard
Flammability	: 1 Slight Hazard
Physical	: 0 Minimal Hazard
Personal protection	: B



Legal disclaimer: Turtle Wax, Inc. All rights reserved.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date issued. No warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the responsibility of the user or processor to satisfy themselves as to the suitability of such information for their own particular circumstances, conditions or use, including transportation, storage and disposal which are outside of our control.

SDS US (GHS HazCom)